

This guide explains how to use the finding evidence table token in reports using a query string-like syntax.

BASIC STRUCTURE

The token uses URL-style parameters separated by `&` characters. For example:

```
{FindingEvidence_Table?
columns=title,ip,port,protocol,issue_details&setting.filter.type=Vulnerability}
```

This will be replaced by a **table per Finding** of Evidences of type Vulnerability, with the following columns: *title, ip, port, protocol, issue_details*.

All evidences will be displayed, including the ones with 'Not visible in Report'.

1. REQUIRED PARAMETERS

These are the required parameters and their options. You can find all the available fields [here \(Evidence Fields section\)](#):

```
columns=[field1, field2]&
```

2. GROUPING

Finding Evidences can be grouped by finding or asset, if desired:

```
group_by=[asset/finding]&
```

3. FILTERING AND SORTING (OPTIONAL)

Filter findings by various criteria:

```
setting.filter.type=Vulnerability&
setting.filter.status=ReadyRetest,PendingFix&
setting.filter.severity=Critical,High&
setting.filter.labels=Security,PCI-DSS&
setting.sort.direction=Ascending&
```

HTML STRUCTURE AND CSS CLASSES

The Finding Evidence Table token generates tabular evidence data organized by findings with configurable columns.

ROOT CONTAINER

```
<div class="finding-evidences-container">
```

Purpose: Top-level container for all evidence table content.

CSS Class: `finding-evidences-container`

GROUP HEADERS

```
<h5 class="finding-evidences-table-header">SSH Weak Key Exchange Algorithms
Enabled</h5>
```

Purpose: Displays the finding name when `group_by` is configured.

CSS Class: `finding-evidences-table-header`

TABLE STRUCTURE

```
<table class="findings-evidence-table">
  <thead>
    <tr>
      <th>Column Display Name</th>
```

```
        </tr>
      </thead>
      <tbody>
        <tr>
          <td class="evidence-[column-name]">Cell Content</td>
        </tr>
      </tbody>
    </table>
```

CSS Classes:

- `findings-evidence-table` : Base table styling
- `evidence-[column-name]` : Column-specific cell class (e.g., `evidence-title` , `evidence-ip` , `evidence-port` , `evidence-protocol`)