

This guide explains how to customize the display of attack chain steps in reports using a query string-like syntax.

BASIC STRUCTURE

The token uses URL-style parameters separated by `&` characters. For example:

```
{AttackChain_Details?scenario=Scenario
1&group.1.title=Overview&group.1.fields=title,mitre_attack_tactic,mitre_attack_technique}
```

CONFIGURATION SECTIONS

1. HEADER TABLE (OPTIONAL)

Display key information at the top of each step:

```
header_table.title=Summary Table&
header_table.fields=title,severity&
header_table.cols=2&
```

2. TABLES

Add tables anywhere in your layout:

```
table.1.title=Summary&
table.1.fields=severity,status&
table.1.cols=2&
```

3. GROUPS

Organize fields into logical groups:

```
group.1.title=Overview&
group.1.fields=title,description&

group.2.title=Details&
group.2.fields=mitre_attack_tactic,mitre_attack_technique&
```

4. DISPLAY SETTINGS

TITLE SETTINGS

```
setting.title.html_tag=h1&
setting.title.display_severity=true&
setting.title.show=true&
```

LAYOUT SETTINGS

Choose between table or headings layout:

```
setting.layout=table&
```

```
setting.layout=headings&
```

5. FILTERING AND SORTING (OPTIONAL)

Filter attack steps by various criteria:

```
setting.filter.type=attack&
```

You can filter them by **attack**, **mitigation**, **goal** or **fact**.

IMPORTANT NOTE ABOUT NUMBERING

When using tables and groups, the numbers after `table.` and `group.` determine the overall order of appearance. These numbers should be distinct across both tables and groups. For example:

```
header_table... (always appears first)
group.1... (appears second)
table.2... (appears third)
group.3... (appears fourth)
```

AVAILABLE FIELDS

6. SHOWING SEQUENCE (OPTIONAL)

There is also a parameter that can be used to select which scenario to include when you have multiple scenarios available and don't specify a name (starting from 1). This adds a scenario according to its order in the Attack Chains tab in the pentest. If you use the name of the scenario, this will be ignored

```
scenario_seq=1
```

EXAMPLES

Here's an example combining multiple settings:

```
{AttackChain_Details?
scenario=<scenario>&
group.1.fields=title,description&
group.2.title=Mitre Fields&
group.2.fields=mitre_attack_tactic,mitre_attack_technique,mitre_attack_mitigation&
setting.title.html_tag=h1&
setting.title.show=true&
setting.layout=headings&
setting.filter.type=attack&
setting.sort=timestamp&
}
```