

This guide explains how to use the attack chain table token in reports using a query string-like syntax.

BASIC STRUCTURE

The token uses URL-style parameters separated by `&` characters. For example:

```
{AttackChain_Table?scenario=<scenario>&columns=title,description,timestamp}
```

This will be replaced by a **table** of Attack Chain steps, with the following columns: *title*, *description* and *timestamp*.

CONFIGURATION SECTIONS

1. REQUIRED PARAMETERS

These are the required parameters and their options. You can find all the available fields [here](#):

```
columns=[field1, field2]&
```

2. FILTERING AND SORTING (OPTIONAL)

Filter findings by various criteria:

```
setting.filter.type=attack&
setting.sort.direction=ascending&
```

3. SHOWING SEQUENCE (OPTIONAL)

There is also a parameter that can be used to select which scenario to include when you have multiple scenarios available and don't specify a name (starting from 1). This adds a scenario according to its order in the Attack Chains tab in the pentest. If you use the name of the scenario, this will be ignored

```
scenario_seq=1
```

EXAMPLES

TABLE WITH ATTACK STEPS ORDERED BY TIMESTAMP:

```
{AttackChain_Table?scenario=
<scenario>&columns=title,description,timestamp&setting.sort.field=timestamp}
```

Table with mitigations:

```
{AttackChain_Table?scenario=
<scenario>&fields=title,mitre_attack_mitigation&setting.filter.type=mitigation}
```