

Cyver allows administrators to configure **custom email (SMTP) settings** to control how system emails, such as account activation, password reset, and notification emails, are sent. This feature enables organizations to use their **own email domain and infrastructure** instead of Cyver's default email configuration.

Using custom email settings helps organizations align Cyver with their internal IT, security, and compliance requirements.


WHEN TO USE CUSTOM EMAIL SETTINGS

You may want to configure custom email settings if you:

- Want emails to be sent from your **own corporate email domain**
- Need emails to go through your **internal SMTP servers**
- Have strict security or compliance requirements
- Prefer full control over email delivery and authentication

HOW TO ENABLE CUSTOM EMAIL SETTINGS

1. Navigate to **Administration > Portal > Email**
2. Locate the option "**Use default email settings**"



3. **Uncheck** this option

- This disables Cyver's default email delivery
- Custom SMTP configuration fields will become available

CUSTOM EMAIL CONFIGURATION FIELDS

Once default email settings are disabled, configure the following fields:

EMAIL IDENTITY

- **Email Display Name**
The name shown as the sender (e.g., your organization name)
- **From Address**
The sender email address that will appear in the "From" field

SMTP SERVER SETTINGS

- **SMTP Host**
Your organization's SMTP server
- **SMTP Port**
The port used by your SMTP service
- **Use SSL**

Enable if your SMTP server requires encrypted connections


AUTHENTICATION OPTIONS

- **Username / Password**
Standard SMTP authentication
- **Use Default Credentials**
Uses Windows/Active Directory credentials in corporate environments where the SMTP server trusts domain authentication
- **Domain Name**
Domain context for authentication

TESTING THE CONFIGURATION

After entering the SMTP details:

1. Enter a recipient email address under **Test Email Settings**
2. Click **Send a Test Email**



3. Confirm the email is delivered successfully

This step ensures the SMTP configuration is valid before it is used by the platform.