

This guide explains how to use the Link\_Finding token in reports to create internal hyperlinks to findings.

## BASIC STRUCTURE

The token uses URL-style parameters separated by `&` characters. For example:

```
{Link_Finding?code=VULN-001&text=See SQL Injection details}
```

## CONFIGURATION SECTIONS

### 1. REQUIRED PARAMETERS

**code=[finding\_code]**

- The code of the finding to link to
- Case-insensitive matching
- Must match a finding code in the current project
- Example: `code=VULN-001`

### 2. OPTIONAL PARAMETERS

**text=[custom\_text]**

- Custom text to display for the link
- If not specified, defaults to "Code - Finding Name" (e.g., "VULN-001 - SQL Injection")
- Example: `text=Click here to view the vulnerability`

**display=[inline|block]**

- Controls how the link is rendered
- Available values: `inline` (default), `block`
- `inline`: Renders as a span element, suitable for use within paragraphs
- `block`: Renders as a div element, suitable for standalone links

- Example: `display=block`

## HOW IT WORKS

The Link\_Finding token creates clickable hyperlinks that navigate to the corresponding finding's detail section within the same PDF document.

- When the report is generated, the token looks up the finding by its code
- It generates an anchor link pointing to the finding's detail section (created by Finding\_Details or similar tokens)

### For this to work properly:

- The finding must exist in the project
- The finding must be included in the report (via Finding\_Details token or similar)

## ERROR HANDLING

The token displays error messages in the following cases:

### Missing code parameter:

```
[Invalid Link: No finding  
code specified]
```

### Finding not found:

```
[Finding 'VULN-XXX' not  
found]
```

## HTML STRUCTURE AND CSS CLASSES

The Link\_Finding token generates hyperlinks that navigate to finding detail sections within the document.

### LINK CONTAINER (INLINE MODE - DEFAULT)

```
<span class="internal-link-
```

```
text">Link Text</span>
```

#### CSS Classes:

- `internal-link-text`: Base styling for the link text in preview

### LINK CONTAINER (BLOCK MODE)

```
<div class="internal-link-text">Link Text</div>
```

#### CSS Classes:

- `internal-link-text`: Base styling for the link text in preview

### GENERATED LINK (IN PDF)

```
<a href="#finding-vuln-001" class="internal-link internal-link-finding">Link Text</a>
```

#### CSS Classes:

- `internal-link`: Base class for all internal links
- `internal-link-finding`: Specific class for finding links

### BLOCK DISPLAY WRAPPER (IN PDF)

```
<div class="internal-link-block">
  <a href="#finding-vuln-001" class="internal-link internal-link-finding">Link Text</a>
</div>
```

#### CSS Classes:

- `internal-link-block`: Wrapper for block-level links

### ERROR DISPLAY

```
<span class="link-error">[Error message]</span>
```

#### CSS Classes:

- `link-error`: Styling for error messages

## EXAMPLES

### BASIC LINK WITH DEFAULT TEXT

```
{Link_Finding?code=VULN-001}
```

Creates a link displaying "VULN-001 - SQL Injection" (assuming that's the finding's name) that navigates to the finding's detail section.

### LINK WITH CUSTOM TEXT

```
{Link_Finding?code=VULN-001&text=See the SQL Injection finding for more details}
```

Creates a link with custom display text while still navigating to the VULN-001 finding.

### BLOCK-LEVEL LINK

```
{Link_Finding?code=VULN-001&text=View Finding Details&display=block}
```

Creates a standalone block-level link, useful for prominent navigation elements.

### INLINE LINK WITHIN TEXT

```
For more information about this vulnerability, refer to {Link_Finding?code=VULN-001&text=the detailed analysis} in the Findings section.
```

Creates an inline link that flows naturally within a paragraph.

### MULTIPLE FINDING REFERENCES

```
The following
```

vulnerabilities are related:

- {Link\_Finding?code=VULN-001&text=SQL Injection}
- {Link\_Finding?code=VULN-002&text=XSS Vulnerability}
- {Link\_Finding?code=VULN-003&text=CSRF Attack}

Creates a list of links to different findings in the report.