



## Metadassess

### How to Silently Extend Classes (Part 2)

Walter Cazzola

Dipartimento di Informatica e Comunicazione  
Università degli Studi di Milano  
e-mail: cazzola@dico.unimi.it



## Metadassess

### What's a Metaclass?

Metadassess are a mechanism to gain a **high-level of control** over how a set of classes work.

- They permit to intercept and augment class creation;
- they provide an API to insert extra-logic at the end of **class** statement;
- they provide a general protocol to manage class objects in a program.

Note,

- the added logic does not rebind the class name to a decorator callable, but rather routes creation of the class itself to specialized logic.
- metadassess add code to be run at class creation time and not at instance creation time



## Metadassess

### The Metaclass Model

#### Classes Are Instances of type

```
[11:44]cazzola@ulik:~/esercizi-pa>python3
>>> from circle import *
>>> type(circle)
<class 'type'>
>>> circle.__class__
<class 'type'>
>>> c = circle(3)
>>> type(c)
<class 'circle.circle'>
>>> c.__class__
<class 'circle.circle'>
>>> type([])
<class 'list'>
>>> type(type([]))
<class 'type'>
```

#### Metadassess Are Subclasses of type

- type is a class that generates user-defined classes.
- Metadassess are subclasses of the type class.
- Class objects are instances of the type class, or a subclass thereof.
- Instance objects are generated from a class.

#### Class Statement Protocol

- at the end of class statement, after filling \_\_dict\_\_, python calls

```
class = type(classname, superclasses, attributedict)
```

to create the **class** object.

- type object defines a \_\_call\_\_ operator that calls \_\_new\_\_ (to create class objects) and \_\_init\_\_ (to create instance objects) when type object is called



## Metadassess

### The Metaclass Declaring ≠ Coding

#### Declaring Metadassess

To create a class with a custom metaclass you have just to list the desired metaclass as a keyword argument in the **class** header.

```
class Spam(metaclass=Meta): pass
```

#### Coding Metadassess

- subtype type
- override \_\_new\_\_, \_\_init\_\_ and \_\_call\_\_ operators





# Metaclasses

## The Metaclass Declaring ≠ Coding (Cont'd)

### Metaclasses

Walter Cazzola

### Metaclasses

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based augmentation  
Metaclasses at work

### References

```
class MetaOne(type):
    def __new__(meta, classname, supers, classdict):
        print('In MetaOne.new:', classname, supers, classdict, sep='\n...')
        return type.__new__(meta, classname, supers, classdict)
    def __init__(Class, classname, supers, classdict):
        print('In MetaOne init:', classname, supers, classdict, sep='\n...')
        print('...init class object:', list(Class.__dict__.keys()))
```

```
class Eggs: pass
print('making class')
class Spam(Eggs, metaclass=MetaOne):
    data = 1
    def meth(self, arg): pass
print('making instance')
X = Spam()
print('data:', X.data)
```

```
[17:13]cazzola@ulik:~/esercizi-pa/metaclass>python3 metaone.py
making class
In MetaOne.new:
...Spam
...(<class 'main...Eggs'>,)
...{'__module__': 'main', 'data': 1, 'meth': <function meth at 0xb79d99ac>}
In MetaOne init:
...Spam
...(<class 'main...Eggs'>,)
...{'__module__': 'main', 'data': 1, 'meth': <function meth at 0xb79d99ac>}
...init class object: ['__module__', 'data', 'meth', '__doc__']
making instance
data: 1
```



Slide 5 of 12



# Metaclasses

## Metaclasses vs Superclasses

### Metaclasses

Walter Cazzola

### Metaclasses

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based augmentation  
Metaclasses at work

### References

In spite of the syntax meta- and superclasses are quite different

- Metaclasses inherit from the type class
- Metaclass declarations are inherited by subclasses
- Metaclass attributes are not inherited by class instances

```
class MetaOne(type):
    def __new__(meta, classname, supers, classdict):
        print('In MetaOne.new:', classname)
        return type.__new__(meta, classname, supers, classdict)
    def toast(self):
        print('toast')
class Super(metaclass=MetaOne):
    def spam(self):
        print('spam')
class C(Super):
    def eggs(self):
        print('eggs')
X = C()
X.eggs()
X.spam()
X.toast()
```

```
[17:29]cazzola@ulik:~/esercizi-pa/metaclass>python3 MetaAndSuper.py
In MetaOne.new: Super
In MetaOne.new: C
eggs
spam
Traceback (most recent call last):
  File "MetaAndSuper.py", line 16, in <module>
    X.toast()
AttributeError: 'C' object has no attribute 'toast'
```



Slide 6 of 12



# Metaclasses

## Metaclass-Based Augmentation

### Metaclasses

Walter Cazzola

### Metaclasses

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based augmentation  
Metaclasses at work

### References

```
def eggfunc(obj): return obj.value * 4
def hamfunc(obj, value): return value + 'ham'
class Extender(type):
    def __new__(meta, classname, supers, classdict):
        classdict['eggs'] = eggfunc
        classdict['ham'] = hamfunc
        return type.__new__(meta, classname, supers, classdict)
```

```
class Client1(metaclass=Extender):
    def __init__(self, value): self.value = value
    def spam(self): return self.value * 2
```

```
class Client2(metaclass=Extender): value = 'ni?'
```

```
X = Client1('Ni!')
print(X.spam())
print(X.eggs())
print(X.ham('bacon'))
Y = Client2()
print(Y.eggs())
print(Y.ham('bacon'))
```

```
[18:01]cazzola@ulik:~/esercizi-pa/metaclass>python3 extender.py
Ni!Ni!
Ni!Ni!Ni!Ni!
baconham
ni?ni?ni?ni?
baconham
```



Slide 7 of 12



# Metaclasses

## Applying Decorators to Methods

### Metaclasses

Walter Cazzola

### Metaclasses

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based augmentation  
Metaclasses at work

### References

```
[21:18]cazzola@ulik:~/aux_work/projects/python/esercizi-pa/metaclass/decorators>ls
__init__.py timer.py tracer.py
```

```
import time
def timer(label='', trace=True):
    def onDecorator(func):
        def onCall(*args, **kwargs):
            start = time.clock()
            result = func(*args, **kwargs)
            elapsed = time.clock() - start
            onCall.alltime += elapsed
            print('{0}{1}: {2:.5f}, {3:.5f}'.format(
                label, func.__name__, elapsed, onCall.alltime))
            return result
        return onCall
    onCall.alltime = 0
    return onDecorator
def tracer(func):
    calls = 0
    def onCall(*args, **kwargs):
        nonlocal calls
        calls += 1
        print('call {0} to {1}'.format(calls, func.__name__))
        return func(*args, **kwargs)
    return onCall
```



Slide 8 of 12



# Metaclasses

## Applying Decorators to Methods

Metadassess

Walter Cazzola

Metadassess

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based  
autoveneration  
Metadassess at  
work

References

```
from decorators.tracer import tracer

class Person:
    @tracer
    def __init__(self, name, pay):
        self.name = name
        self.pay = pay
    @tracer
    def giveRaise(self, percent): # giveRaise = tracer(giveRaise)
        self.pay *= (1.0 + percent) # onCall remembers giveRaise
    @tracer
    def lastName(self): # lastName = tracer(lastName)
        return self.name.split()[-1]

bob = Person('Bob Smith', 50000)
sue = Person('Sue Jones', 100000)
print(bob.name, sue.name)
sue.giveRaise(.10) # Runs onCall(sue, .10)
print(sue.pay)
print(bob.lastName(), sue.lastName()) # Runs onCall(bob), remembers lastName
```

```
[21:30]cazzola@ulik:~/esercizi-pa/metaclass>python3 Person1.py
call 1 to __init__
call 2 to __init__
Bob Smith Sue Jones
call 1 to giveRaise
110000.0
call 1 to lastName
call 2 to lastName
Smith Jones
```



Slide 9 of 12



# Metaclasses

## Applying Decorators to Methods

Metadassess

Walter Cazzola

Metadassess

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based  
autoveneration  
Metadassess at  
work

References


```
from types import FunctionType
from decorators.tracer import tracer

class MetaTrace(type):
    def __new__(meta, classname, supers, classdict):
        for attr, attrval in classdict.items():
            if type(attrval) is FunctionType:
                classdict[attr] = tracer(attrval)
        return type.__new__(meta, classname, supers, classdict)

class Person(metaclass=MetaTrace):
    def __init__(self, name, pay):
        self.name = name
        self.pay = pay
    def giveRaise(self, percent):
        self.pay *= (1.0 + percent)
    def lastName(self): return self.name.split()[-1]

bob = Person('Bob Smith', 50000)
sue = Person('Sue Jones', 100000)
print(bob.name, sue.name)
sue.giveRaise(.10)
print(sue.pay)
print(bob.lastName(), sue.lastName())
```

```
[21:45]cazzola@ulik:~/esercizi-pa/metaclass>python3 Person2.py
call 1 to __init__
call 2 to __init__
Bob Smith Sue Jones
call 1 to giveRaise
110000.0
call 1 to lastName
call 2 to lastName
Smith Jones
```



Slide 10 of 12



# Metaclasses

## Applying Decorators to Methods

Metadassess

Walter Cazzola

Metadassess

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based  
autoveneration  
Metadassess at  
work

References

```
from types import FunctionType
from decorators.tracer import tracer
from decorators.timer import timer

def decorateAll(decorator):
    class MetaDecorate(type):
        def __new__(meta, classname, supers, classdict):
            for attr, attrval in classdict.items():
                if type(attrval) is FunctionType:
                    classdict[attr] = decorator(attrval)
            return type.__new__(meta, classname, supers, classdict)
    return MetaDecorate

class Person(metaclass=decorateAll(tracer)):
    ...

print('--- tracer')
bob = Person('Bob Smith', 50000)
sue = Person('Sue Jones', 100000)


print(bob.name, sue.name)
sue.giveRaise(.10)
print(sue.pay)
print(bob.lastName(), sue.lastName())

class Person(
    metaclass=decorateAll(timer(label='**'))):
    ...

print('--- timer')
bob = Person('Bob Smith', 50000)
sue = Person('Sue Jones', 100000)
print(bob.name, sue.name)
sue.giveRaise(.10)
print(sue.pay)
print(bob.lastName(), sue.lastName())
print('{0:.5f}'.format(Person.__init__.alltime))
print('{0:.5f}'.format(Person.giveRaise.alltime))
print('{0:.5f}'.format(Person.lastName.alltime))
```

```
[21:47]cazzola@ulik:~/esercizi-pa/metaclass>python3 Person3.py
--- tracer
call 1 to __init__
call 2 to __init__
Bob Smith Sue Jones
call 1 to giveRaise
110000.0
call 1 to lastName
call 2 to lastName
Smith Jones
```

```
--- timer
**__init__: 0.00000, 0.00000
**__init__: 0.00000, 0.00000
Bob Smith Sue Jones
**giveRaise: 0.00000, 0.00000
110000.0
**lastName: 0.00000, 0.00000
**lastName: 0.00000, 0.00000
Smith Jones
0.00000
0.00000
0.00000
```



Slide 11 of 12



# References

Metadassess

Walter Cazzola

Metadassess

Definition  
Metaclass model  
Metaclass coding  
Meta vs super  
Metaclass-based  
autoveneration  
Metadassess at  
work

References

- ▶ Jennifer Campbell, Paul Gries, Jason Montojo, and Greg Wilson.  
*Practical Programming: An Introduction to Computer Science Using Python*.  
The Pragmatic Bookshelf, second edition, 2009.
- ▶ Mark Lutz.  
*Learning Python*.  
O'Reilly, fourth edition, November 2009.
- ▶ Mark Pilgrim.  
*Dive into Python 3*.  
Apress\*, 2009.
- ▶ Mark Summerfield.  
*Programming in Python 3: A Complete Introduction to the Python Language*.  
Addison-Wesley, October 2009.



Slide 12 of 12