



Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

Closures ≠ Generators

Walter Cazzola

Dipartimento di Informatica e Comunicazione
Università degli Studi di Milano
e-mail: cazzola@dico.unimi.it



Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

Closures On a Real Problem

English, from singular to plural

- if a word ends in **S**, **X**, or **Z**, add **ES**, e.g., fax becomes faxes;
- if a word ends in a **noisy H**, add **ES**, e.g., coach becomes coaches;
- if it ends in a **silent H**, just add **S**, e.g., cheetah becomes cheetahs.
- if a word ends in **Y that sounds like I**, change the **Y** to **IES**, e.g., vacancy becomes vacancies;
- if the **Y** is combined with a vowel to sound like something else, just add **S**, e.g., day becomes days;
- if all else fails, just add **S** and hope for the best.

We will design a Python library that automatically pluralizes English nouns.



Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

Closures Regular Expressions

A **Regular Expression** (RE) specifies a set of strings matched by it.

- the functions in re module permits to check if a string matches the regular expression and to get the result of the match.

Few Bytes of syntax

```
'.' any character BUT a newline
'^' the begin of the string
'$' the end of the string
'*', '+' 0 (or 1) or more repetitions of the preceding RE
'?' 0 or 1 repetitions of the preceding RE
'[]' a set of characters
'()' matching groups
```

RE at work

```
[22:55]cazzola@ulik:~/esercizi-pa>python3
>>> email = 'cazzola@diremove_thisco.unimi.it'
>>> import re
>>> m = re.search("remove_this", email)
>>> email[:m.start()]+email[m.end():]
'cazzola@dico.unimi.it'
```



Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

Closures Pluralizes via Regular Expressions

```
import re

def plural(noun):
    if re.search('[sxz]$', noun):
        return re.sub('$', 'es', noun)
    elif re.search('[^aeioudgkprt]h$', noun):
        return re.sub('$', 'es', noun)
    elif re.search('[^aeiou]ys$', noun):
        return re.sub('ys$', 'ies', noun)
    else: return noun + 's'
```

- the 1st regular expression looks for words ending by s, x or z
- the 2nd regular expression looks for words ending by a not silent h by excluding the letters that combined with it will mute the h
- the 3rd regular expression looks for words ending by a y that doesn't sound as a i similarly to the previous.





Closures

Do Some Abstraction: A List of Functions

Closures +
Generators

Walter Cazzola

Closures

our case study
"regular"
expressions
plural() via
res. expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Pisano's
Generator
plural() via
generators

References

To abstract we have

- to limit the number of tests to be done;
- to generalize the approach

```
import re

def match_sxz(noun): return re.search('[sxz]$', noun)
def apply_sxz(noun): return re.sub('$', 'es', noun)
def match_h(noun): return re.search('[^aeioudgkprt]h$', noun)
def apply_h(noun): return re.sub('$', 'es', noun)
def match_y(noun): return re.search('[^aeiou]y$', noun)
def apply_y(noun): return re.sub('y$', 'ies', noun)
def match_default(noun): return True
def apply_default(noun): return noun + 's'

rules = ((match_sxz, apply_sxz), (match_h, apply_h), (match_y, apply_y),
         (match_default, apply_default))

def plural(noun):
    for matches_rule, apply_rule in rules:
        if matches_rule(noun):
            return apply_rule(noun)
```

Advantages

- to add new rules simply means to add a couple of functions and a tuple in the rules tuple



Slide 5 of 11



Closures

Do Some Abstraction: A List of Patterns

Closures +
Generators

Walter Cazzola

Closures

our case study
"regular"
expressions
plural() via
res. expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Pisano's
Generator
plural() via
generators

References

To do better, we have

- to avoid to write the single functions (boring & error-prone task)

```
import re

def build_match_and_apply_functions(pattern, search, replace):
    def matches_rule(word):
        return re.search(pattern, word)
    apply_rule = lambda word: \
        re.sub(search, replace, word)
    return (matches_rule, apply_rule)

patterns = ( \
    ('[sxz]$', '$', 'es'), ('[^aeioudgkprt]h$', '$', 'es'),
    ('(qu|[^aeiou])y$', 'y$', 'ies'), ('$', '$', 's')
)

rules = [ \
    build_match_and_apply_functions(pattern, search, replace)
    for (pattern, search, replace) in patterns ]
```

The technique of using the values of outside scope within a dynamic function is called **closures**.

- It defines defining constants within the function it is building:
 - Both `matches_rule` and `apply_rule` take one parameter `word`, they act on that plus three other values (`pattern`, `search` and `replace`), which were set when you defined the functions.



Slide 6 of 11



Closures

Do Some Abstraction: A File of Patterns

Closures +
Generators

Walter Cazzola

Closures

our case study
"regular"
expressions
plural() via
res. expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Pisano's
Generator
plural() via
generators

References

Separate data from code.

- By moving the patterns in a separate file.

```
[sxz]$      $ es
[^aeioudgkprt]h$ $ es
[^aeiou]y$  y$ ies
$          $ s
```

Everything is still the same but

- how the rules list is filled

```
rules = []
with open('plural-rules.txt', encoding='utf-8') as pattern_file:
    for line in pattern_file:
        pattern, search, replace = line.split(None, 3)
        rules.append(build_match_and_apply_functions(pattern, search, replace))
```

Benefits & Drawbacks

- no change in the code to add a new rule
- to read a file is slower than to hardwire the data in the code



Slide 7 of 11



Generators

Introduction By Example

Closures +
Generators

Walter Cazzola

Closures

our case study
"regular"
expressions
plural() via
res. expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Pisano's
Generator
plural() via
generators

References

A **generator** is a function that generates value one at a time

- a sort of resumable function or function with a memory

```
def make_counter(x):
    print('entering make_counter')
    while True:
        yield x
        print('incrementing x')
        x = x + 1
```

Let look at what happens here.

```
[12:53]cazzola@ulik:~/esercizi-pa/python3
>>> import counter
>>> counter = counter.make_counter(2)
>>> next(counter)
entering make_counter
2
>>> next(counter)
incrementing x
3
```

- a call to the function initializes the generator;
- the `next()` will "synchronize" with the **yield** statement
- **yield** suspends the execution of the function and returns a value;
- the `next()` resumes the computation from the **yield** and continues until it reaches another **yield** or the function end.



Slide 8 of 11



Generators

Fibonacci's Generator

Closures +
Generators

Walter Cazzola

Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators


References

```
def gfib(max):
    a, b = 0, 1
    while a < max:
        yield a
        a, b = b, a + b

if __name__ == "__main__":
    for n in gfib(1000):
        print(n, end=' ')
    print()
```

```
[15:43]cazzola@ulik:~/esercizi-pa>python3 gfib.py
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377 610 987
[15:52]cazzola@ulik:~/aux_work/projects/python/esercizi-pa>python3
>>> import gfib
>>> list(gfib.gfib(1000))
[0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, 233, 377, 610, 987]
```

- a Generator can be used in a for statement, the next() is automatically called at each iteration
- the list constructor has a similar behavior.



Slide 9 of 11



Generators

Pluralizes Via Generators

Closures +
Generators

Walter Cazzola

Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

```
def rules(rules_filename):
    with open(rules_filename, encoding='utf-8') as pattern_file:
        for line in pattern_file:
            pattern, search, replace = line.split(None, 3)
            yield build_match_and_apply_functions(pattern, search, replace)

def plural(noun, rules_filename='plural-rules.txt'):
    for matches_rule, apply_rule in rules(rules_filename):
        if matches_rule(noun):
            return apply_rule(noun)
    raise ValueError('no matching rule for {}'.format(noun))
```

Benefits & Drawbacks

- shorter start-up time (it just read a row not the whole file)
lazy approach
- performance losses (every call to plural() the file is reopened and read from the beginning).

To get the benefits from both approaches you need to define your own iterator.



Slide 10 of 11



References

Closures +
Generators

Walter Cazzola

Closures

our case study
regular
expressions
plural() via
res expressions
function objects
list of patterns
file of patterns

Generators

a counter
generator
Fibonacci's
Generator
plural() via
generators

References

- Jennifer Campbell, Paul Gries, Jason Montojo, and Greg Wilson.
Practical Programming: An Introduction to Computer Science Using Python.
The Pragmatic Bookshelf, second edition, 2009.
- Mark Lutz.
Learning Python.
O'Reilly, third edition, November 2001.
- Mark Pilgrim.
Dive into Python 3.
Apress*, 2009.



Slide 11 of 11