

22 References in Plain Text Writing

Jacques Mock Schindler

14.01.2026

References in Plain Text Writing (Markdown)

Three additional files are required to insert references in Markdown files:

- a file for information about the text format (.yaml),
- a file for bibliographical information (.bib), and
- a file for display format of the bibliographical information (.bib).

Out of these three files only the one containing text format information has to be created manually. Zotero will create the .bib file and the .csl file can be downloaded from the [Zotero Style Repository](#).

Text Format File (.yaml)

The .yaml file controls both the styling of the text and the output format. The file can be given any name. Because the file is responsible for the formatting of the text in this tutorial the file is called format.yaml. The following listing shows an example that uses both a .bib file and a .csl file.

```
1 # input and output
2 input-files:
3   - my-text.md # there can be more files
4   # - second_part.md
5   # - thrid_part.md
6 output-file: output.pdf
7
8 # basic settings
9 from: markdown
10 to: pdf
11 # lualatex is better for special characters
12 pdf-engine: lualatex # or xelatex, pdflatex
13
```

```

14 # activate citeproc - responsible for loading the bibliography
15 citeproc: true
16
17 table-of-contents: true
18
19 # variables und metadata
20 variables:
21   lang: en # for Switzerland: de-CH
22   lof: true
23   lot: true
24   number-sections: true
25   header-includes:
26     - \setcounter{secnumdepth}{3}
27     - \setcounter{tocdepth}{3}
28
29 metadata:
30   title: "Title of the Document"
31   author: "Authors Name"
32   date: "Today"
33   bibliography: bibliography.bib
34   csl: chicago-notes-bibliography-access-dates.csl
35   link-citations: true

```

The following list provides explanations for the entries in the configuration file:

- input-files A list of the files to be included in the final output. As shown in the example the different files are listed one below the other.
- output-file This key sets the path to the output file.
- from This is the key of the file format of the input-files.
- to This is the key of the file format of the output-file.
- pdf-engine sets the pdf-engine responsible for the conversion from Markdown to PDF. lualatex is chosen for its ability to handle Swiss umlaute.
- citeproc is the software responsible to handle the bibliographic information. The value true activates the software.
- table-of-contents If true there will be a table of contents.
- variables bundles the details for the display of the output file.
- lang is the variable to store the language settings. For Swiss German documents it has to be set to de-CH. This observes the Swiss German typographical conventions.
- lof creates a list of figures.
- lot creates a list of tables.
- number-sections numbers the sections according to their hierarchical position.
- header-includes This key allows the inclusion of LaTeX commands.
 - \setcounter{secnumdepth}{3} This numbers sections down to the third level.
 - \setcounter{tocdepth}{3} This excludes sections below the third level from the table of contents.

- `metadata` bundles the metadata of the file.
- `title` The title for the front matter.
- `author` The author's name. Multiple authors can be provided as a list (analogue to the input files).
- `date` The Date.
- `bibliography` Stores the path to the bibliography (.bib) file.
- `csl` Stores the path to the .csl file.

For additional configurations check the [Pandoc User Guide](#).

Bibliographic Information

Zotero will create the file `bibliography.bib` automatically. Nevertheless, there is an example entry from the file `bibliography.bib` below.

```

1 @book{healy2020,
2   title = {The {{Plain Person}}'s {{Guide}} to {{Plain Text Social}},
3   author = {Healy, Kieran},
4   year = 2020,
5 }
```

This entry represents a book, hence the `@book` key. The citation key can be found immediately after the curly bracket. Zotero assigns this key arbitrarily. However, it is possible to set a citation key at will. The details are explained in [?@sec-zotero_entry](#).

Citation Style

The `.csl` (Citation Style Language) file defines the citation style. The `.csl` format is a variant of the [xml](#) language. Even if it is possible to write a csl definition from scratch it is far easier to download a style from the [Zotero Style Repository](#).

Setting references in Markdown

To transfer references from the `.bib` file into the Markdown text, use the citation key ([@citation_key]). If you want to include page numbers in your reference, add them to the citation key ([@citation_key, 25]). If you need to include multiple authors in one reference, you can combine multiple citation keys ([@citation_key_1, 25; @citation_key_2, 33]).

There is no need to know memorise the citation keys as Zotero displays them as the first item in the metadata.

Creating a PDF containing references

If there exists a `.yaml` file, the pdf can be created with the

```
1 pandoc -d format.yaml
```

command. The command must be executed from the same directory in which the `format.yaml` file is located.