

Work kit: information for IT

Ubuntu x86_64 · Skryx-L-A

Work tools for one user on a company laptop. The installer places them under the user's home directory. The module menu leaves approval-sensitive parts unticked.

FETCH

The user clones the public repository and runs `setup/fetch-offline.sh` (about 15 GB). Downloads resume and use SHA-256 checks.

INSTALL

`setup/install-kit.sh` checks the fetched files again and opens the module menu. Installation uses no network.

USER PATHS

`~/.local/bin`, `~/.local/share/work-kit`,
`~/.config/work-kit`, `~/work`.

ROOT ACCESS

None required for the normal path. Optional apt and dictation keyboard steps are separate.

CLOUD AI

Only approved tools, after sign-in. They can send prompts and code to their vendors.

REMOVAL

`~/work/kit/install --uninstall all`; user data is handed over or removed separately.

Approval choices

Part	What it does	Decision
AI coding assistants	Send prompts and read code to the selected vendor after sign-in.	Approved vendors, accounts and data classes.
Document Q&A	Indexes approved local documents. Ships disabled.	Allowed documents.
Local models	Run on the laptop CPU.	About 6 GB of storage.
Dictation	Local speech to text.	Keyboard mode needs a separate root step.
Design tools	Render slides, documents and PDFs.	Headless Chrome uses <code>--no-sandbox</code> .
Desktop layout	Changes GNOME or KDE settings after a backup.	Approve desktop changes.

Network and account changes

- The fetch uses GitHub and pinned vendor sources. The installer checks the downloaded hashes and runs offline.
- Approved AI assistants connect to their vendors. Optional workbench helpers may reach `framer.com`, `api.browserbase.com`, `pypi.org`, `registry.npmjs.org` and `nodejs.org`.
- Local listeners bind to `127.0.0.1: 8080` (model), `4011` (usage), `4020` (model endpoint), `8765` (speech), and a random transcription port while in use.
- Optional `apt.sh` uses the offline package folder. Optional dictation keyboard mode changes `input group`, `udev` and `uinput`; `--undo` reverses it.
- The kit can change marked blocks in shell startup files, `git core.hooksPath`, AI tool settings, VS Code extensions, systemd user units and desktop settings.

Check and remove

```
cd ~/work-kit/kit/offline && sha256sum -c SHA256SUMS
```

```
~/work/kit/install --uninstall all
```