

EXP NO: 1 Date: 24-7-26	SETTING UP THE ENVIRONMENT AND PREPROCESSING THE DATA
--	--

AIM:

To set up a fully functional machine learning development environment and to perform data preprocessing operations like handling missing values, encoding categorical variables, feature scaling, and splitting datasets.

ALGORITHM:

1. Install Required Libraries:

- Install numpy, pandas, matplotlib, seaborn, and scikit-learn using pip.

2. Import Libraries.

3. Load Dataset:

- Load any dataset (e.g., Titanic or Iris) using pandas.

4. Data Exploration:

- Use `df.info()`, `df.describe()`, `df.isnull().sum()` to understand the data.

5. Handle Missing Values:

- Use `.fillna()` or `.dropna()` depending on the strategy.

6. Encode Categorical Data:

- Use `pd.get_dummies()` or `LabelEncoder`.

7. Feature Scaling:

- Normalize or standardize the numerical features using `StandardScaler` or `MinMaxScaler`.

8. Split Dataset:

- Use `train_test_split()` from `sklearn` to create training and testing sets.

9. Display the Preprocessed Data.

CODE:

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler, LabelEncoder
import seaborn as sns
import matplotlib.pyplot as plt

# 3. Load dataset
df = sns.load_dataset('titanic') # Titanic dataset
print(df.head())

# 4. Explore the dataset
print(df.info())
print(df.describe())
print(df.isnull().sum())

# 5. Handle missing values
# Fill age with median
df['age'].fillna(df['age'].median(), inplace=True)

# Fill embark_town with mode
df['embark_town'].fillna(df['embark_town'].mode()[0], inplace=True)

# Drop deck column (too many missing values)
df.drop(columns=['deck'], inplace=True)

# 6. Encode categorical variables
le = LabelEncoder()

df['sex'] = le.fit_transform(df['sex'])
df['embark_town'] = le.fit_transform(df['embark_town'])

# Drop unnecessary columns
df.drop(columns=[
    'embarked',
    'class',
    'who',
    'alive',
    'adult_male',
    'alone'
], inplace=True)
```

```
scaler = StandardScaler()
numerical_cols = ['age', 'fare']
df[numerical_cols] = scaler.fit_transform(df[numerical_cols])

# 8. Split dataset
X = df.drop('survived', axis=1)
y = df['survived']

X_train, X_test, y_train, y_test = train_test_split(
    X,
    y,
    test_size=0.2,
    random_state=42
)

# 9. Show final preprocessed data
print("Training Data Shape:", X_train.shape)
print("Test Data Shape:", X_test.shape)

print(X_train.head())
```

OUTPUT:

```
survived  pclass    sex  age  sibsp  parch    fare embarked  class  \
0         0         3  male  22.0    1     0   7.2500      S  Third
1         1         1  female 38.0    1     0  71.2833      C  First
2         1         3  female 26.0    0     0   7.9250      S  Third
3         1         1  female 35.0    1     0  53.1000      S  First
4         0         3  male   35.0    0     0   8.0500      S  Third

      who  adult_male deck  embark_town alive  alone
0  man      True   NaN  Southampton    no  False
1 woman    False    C   Cherbourg    yes  False
2 woman    False   NaN  Southampton    yes   True
3 woman    False    C   Southampton    yes  False
4  man      True   NaN  Southampton    no   True
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 15 columns):
#   Column      Non-Null Count  Dtype
---  ---
0   survived    891 non-null     int64
1   pclass      891 non-null     int64
2   sex         891 non-null     object
3   age         714 non-null     float64
4   sibsp       891 non-null     int64
5   parch       891 non-null     int64
6   fare        891 non-null     float64
7   embarked    889 non-null     object
8   class       891 non-null     category
9   who         891 non-null     object
10  adult_male  891 non-null     bool
11  deck        203 non-null     category
12  embark_town 889 non-null     object
13  alive       891 non-null     object
14  alone       891 non-null     bool
dtypes: bool(2), category(2), float64(2), int64(4), object(5)
memory usage: 80.7+ KB
None
count  survived    891.000000  pclass    891.000000  age    714.000000  sibsp    891.000000  parch    891.000000  fare    891.000000
mean    0.383838    2.308642    29.699118    0.523008    0.381594    32.204208
std     0.486592    0.836071    14.526497    1.102743    0.806057    49.693429
min     0.000000    1.000000    0.420000    0.000000    0.000000    0.000000
25%     0.000000    2.000000    20.125000    0.000000    0.000000    7.910400
50%     0.000000    3.000000    28.000000    0.000000    0.000000    14.454200
75%     1.000000    3.000000    38.000000    1.000000    0.000000    31.000000
max     1.000000    3.000000    80.000000    8.000000    6.000000    512.329200
survived    0
pclass      0
sex         0

survived    0
pclass      0
sex         0
age         177
sibsp       0
parch       0
fare        0
embarked    2
class       0
who         0
adult_male  0
deck        688
embark_town 2
alive       0
alone       0
dtype: int64
Training Data Shape: (712, 7)
Test Data Shape: (179, 7)
pclass  sex    age  sibsp  parch    fare  embark_town
331     1    1  1.240235    0    0 -0.074583    2
733     2    1 -0.488887    0    0 -0.386671    2
382     3    1  0.202762    0    0 -0.488854    2
704     3    1 -0.258337    1    0 -0.490280    2
813     3    0 -1.795334    4    2 -0.018709    2
```

RESULT:

The Python environment was successfully set up and the dataset was pre-processed by handling missing values, encoding categorical data, performing feature scaling, and splitting the data into training and testing sets. The dataset is now ready for model training and analysis.