PART NUMBER	ITEM ① BODY	ITEM ② CONTACT	ITEM ③ INSULATOR	CONTACT
142-0701-231	BRASS GOLD PL .00001 MIN OVER NICKEL PL .DDDD5 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER NICKEL PL .DDDD5 MIN OVER COPPER PL .00005 MIN	TEFLON	
142-0701-235	BRASS GOLD PL .00001 MIN OVER NICKEL PL .DDDD5 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER NICKEL PL .DDDD5 MIN OVER COPPER PL .00005 MIN	TEFLON	△2
142-0701-236	BRASS NICKEL PL .DDD1 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER NICKEL PL .DDDD5 MIN OVER COPPER PL .00005 MIN	TEFLON	





NOTES:

1. SPECIFICATIONS:

IMPEDANCE: 50 OHMS
FREQUENCY RANGE: 0-18 GHz
VSWR: NOT APPLICABLE
WORKING VOLTAGE: 335 VRMS MAX AT SEA LEVEL
DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS MIN AT SEA LEVEL
INSULATION RESISTANCE: 5000 MEGOHM MIN
CONTACT RESISTANCE:
CENTER CONTACT - INITIAL 3.0 MILLIOHM MAX, AFTER ENVIRONMENTAL 4.0 MILLIOHM MAX
OUTER CONDUCTOR - INITIAL 2.0 MILLIOHM MAX AFTER ENVIRONMENTAL NOT APPLICABLE
BRAID TO BODY - NOT APPLICABLE
CORONA LEVEL: 250 VOLTS MIN AT 70,000 FEET
INSERTION LOSS: NOT APPLICABLE
RF LEAKAGE: NOT APPLICABLE
RF HIGH POTENTIAL WITHSTANDING VOLTAGE: 670 VRMS MIN AT 4 AND 7 MHz

MECHANICAL:

ENGAGE/DISENGAGE TORQUE: 2 INCH-POUNDS MAX
MATING TORQUE: 7-10 INCH POUNDS
COUPLING PROOF TORQUE: NOT APPLICABLE
COUPLING NUT RETENTION: NOT APPLICABLE
CONTACT RETENTION: 6 LBS MIN AXIAL FORCE
4 IN-OZ MIN RADIAL TORQUE
CABLE ACCEPTABILITY: NOT APPLICABLE
CABLE HEX CRIMP SIZE: NOT APPLICABLE
CABLE RETENTION: NOT APPLICABLE
DURABILITY: 500 CYCLES MIN

ENVIRONMENTAL:

(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-PRF-39D121
THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B
OPERATING TEMPERATURE: -65 DEG C TO 165 DEG C
CORROSION: MIL-STD-202, METHOD 101, CONDITION B
SHOCK: MIL-STD-202, METHOD 213, CONDITION I
VIBRATION: MIL-STD-202, METHOD 204, CONDITION D
MOISTURE RESISTANCE: MIL-STD-202, METHOD 106
MOISTURE SEAL: EFJ DD3-6000-501

△2 CONNECTOR MOUNTING LEADS 60%/40% TIN/LEAD DIPPED (SOLDER PLATE)



MOUNTING HOLE LAYOUT
8:1

DRAWING NO. C - 142-0701-231/240

0	REVISIONS								
	ENGINEERING RELEASE								
1	9-16-92	R H	V E T	☒	R J B	☒	9-25-92	ECO 41247	
	CHANGED: UPDATED GRAPHICS, CONTACT GOLD PL .DDDD5 WAS .00003								
1a	6-6-94	R H	S W E	T A K	R J B	☐		ECN 42501	
	VERSION UPDATE								
2	2-25-99	R H	T A K	R J B	☒ A			ECN 46212	
	VERSION UPDATE								
	* REVISION NUMBER FOLLOWED BY AN ALPHA * CHARACTER INDICATES DRAWING CLARIFI- * CATION OR PART NUMBER ADDITION ONLY. *								
2a	10-17-01	R H	J T	☒	☒	☐		ECN 47956	

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED PER ANSI Y 14.5M - 1982

"μSTATION"

COMPANY CONFIDENTIAL

TOLERANCE UNLESS OTHERWISE SPECIFIED	DRAWN BY VET	DATE 7-10-92	JOHNSON a cinch connectivity solutions brand — Cinch Connectivity Solutions, 299 Johnson Ave. Ste. 100, Waseca, MN 56093, 1-800-247-8256
DECIMALS .XX ___ mm ___ .XXX ___ ___	CHECKED BY	DATE	TITLE: JACK ASSEMBLY, STRAIGHT PC MOUNT SMA
MATL	APPROVED BY VET	DATE 9-16-92	CODE NO.
FINISH	APPROVED BY TAK/RJB	DATE 9-22-92	DRAWING NO. C - 142-0701-231/240
	RELEASE DATE 9-25-92		SCALE 10:1 U/M INCH SHEET 2 OF 2