



UNIVERSIDAD
POLITÉCNICA
P U E R T O R I C O

Computer Science

Coral S. Schmidt Montilla

#148830

Database Systems

FA 2024 CECS4202-81

Contents

Part I. Review Question and Exercises from the book Database Systems: Design, Implementation, & Management by Carlos Coronel and Steven Morris (Use Edition 12 that is not so expensive) (50 points).	3
Chapter 1.	3
Chapter 2.	8
Chapter 3.	12
Chapter 4.	18
Part II: SQL (60 points)	24
A. Review Questions (Module Quiz) Chapter 2-4 of the book A Guide to SQL (2015): Odd Review Questions. Copy the question in bold face above the answer. Do not use bold face for the answers.	24
Chapter 2: Odd Numbers: pg. 46-47	24
Chapter 3: Odd Numbers: pg. 92-93	30
Chapter 4: Odd Numbers: pg. 131-132	32
B. Except for Chapters 1 and 2, please show the complete question, query used, and print the query results.	35
Chapter 1 (A Guide to SQL) Use the Staywell student Accommodation database only.	35
Chapter 2 (A Guide to SQL) Use the Staywell student Accommodation database only.	39
For Chapters 3 and 4 please show the screen print out of the Oracle or MySql (among others) output. Use the Staywell student Accommodation database only.	44
Chapter 3 (A Guide to SQL) Use the Staywell student Accommodation database only.	44
Chapter 4 (A Guide to SQL) Use the Staywell student Accommodation database only.	56

Part I. Review Question and Exercises from the book Database Systems: Design, Implementation, & Management by Carlos Coronel and Steven Morris (Use Edition 12 that is not so expensive) (50 points).

Chapter 1.

Review Questions: 1-6: Page 32

1. Define each of the following terms:

a. data: Raw facts, such as a phone number or a birth date.

b. field: A character or group of characters (alphabetic or numeric) that has a specific meaning.

c. record: A logically connected set of one or more fields that describes a person, place, or thing.

d. file: A collection of related records.

2. What is data redundancy, and which characteristics of the file system can lead to it?

Data redundancy occurs when the same data is stored in multiple places within a system.

Characteristics of file systems that lead to redundancy include a lack of data sharing and the absence of a central database, resulting in duplicated data across different files.

3. What is data independence, and why is it lacking in file systems?

Data independence refers to the separation of data descriptions from the application programs that use the data. File systems lack data independence because changes in the file structure require modifications to the application programs.

4. What is a DBMS, and what are its functions?

A Database Management System (DBMS) is a collection of programs that manage the database structure and control access to the data stored in the database. Its functions include data storage, retrieval, update, and management of data integrity and security.

5. What is structural independence, and why is it important?

Structural independence exists when changes to the database schema do not affect application programs. It is important because it allows the database structure to be altered without requiring changes to applications.

6. Explain the differences among data, information, and a database.

Data are raw facts. Information is processed data that conveys meaning. A database is a collection of organized data.

FIGURE P1.1 THE FILE STRUCTURE FOR PROBLEMS 1–4

PROJECT_CODE	PROJECT_MANAGER	MANAGER_PHONE	MANAGER_ADDRESS	PROJECT_BID_PRICE
21-5Z	Holly B. Parker	904-338-3416	3334 Lee Rd., Gainesville, FL 37123	16833460.00
25-2D	Jane D. Grant	615-898-9909	218 Clark Blvd., Nashville, TN 36362	12500000.00
25-5A	George F. Dorts	615-227-1245	124 River Dr., Franklin, TN 29185	32512420.00
25-9T	Holly B. Parker	904-338-3416	3334 Lee Rd., Gainesville, FL 37123	21563234.00
27-4Q	George F. Dorts	615-227-1245	124 River Dr., Franklin, TN 29185	10314545.00
29-2D	Holly B. Parker	904-338-3416	3334 Lee Rd., Gainesville, FL 37123	25559999.00
31-7P	William K. Moor	904-445-2719	216 Morton Rd., Stetson, FL 30155	56850000.00

Given the file structure shown in Figure P1.1, answer Problems 1–4.

1. How many records does the file contain? How many fields are there per record?

The file contains 7 records. Each record contains 5 fields: PROJECT_CODE, PROJECT_MANAGER, MANAGER_PHONE, MANAGER_ADDRESS, and PROJECT_BID_PRICE.

2. What problem would you encounter if you wanted to produce a listing by city? How would you solve this problem by altering the file structure?

The problem is that the MANAGER_ADDRESS field contains the full address, including street, city, state, and ZIP code in a single field. This makes it difficult to sort or filter by city. To solve this, you could split the MANAGER_ADDRESS field into separate fields for STREET, CITY, STATE, and ZIP_CODE. This would allow you to easily produce listings sorted by the city.

3. If you wanted to produce a listing of the file contents by last name, area code, city, state, or zip code, how would you alter the file structure?

For last name you would need to separate the PROJECT_MANAGER field into two fields: MANAGER_FIRST_NAME and MANAGER_LAST_NAME. For area code you need to separate the MANAGER_PHONE field into AREA_CODE and PHONE_NUMBER. Finally for city, state, or zip code: As mentioned in Problem 2, split the MANAGER_ADDRESS field into STREET, CITY, STATE, and ZIP_CODE.

4. What data redundancies do you detect? How could those redundancies lead to anomalies?

The current file structure exhibits redundancies where `PROJECT_MANAGER`, `MANAGER_PHONE`, and `MANAGER_ADDRESS` information are repeated for managers who oversee more than one project, such as Holly B. Parker and George F. Dorts. This repetition can lead to several potential anomalies. An update anomaly occurs if a project manager's phone number changes; you would need to update multiple records, and any oversight could result in inconsistent data. A deletion anomaly arises when deleting a project record, such as `21-5Z`, which could inadvertently remove all contact information for a project manager if no other records exist with their details. An insertion anomaly could also occur when adding a new project manager, as it would require entering redundant data into the table. To address these issues, the database should be normalized by creating a separate `MANAGERS` table that contains the `PROJECT_MANAGER`, `MANAGER_PHONE`, and `MANAGER_ADDRESS` fields. The `PROJECTS` table would then include a foreign key to reference the `MANAGERS` table, effectively reducing redundancy and minimizing the risk of anomalies.

Chapter 2.

Review Questions: 1-6: Pages 65-66

1. Discuss the importance of data models.

Data models are essential because they provide a structured way to organize data, ensuring consistency and accuracy in how data is stored, retrieved, and used within a database. They also serve as a blueprint for database design, guiding the creation of databases that reflect real-world entities and relationships.

2. What is a business rule, and what is its purpose in data modeling?

Data models are essential because they provide a structured way to organize data, ensuring consistency and accuracy in how data is stored, retrieved, and used within a database. They also serve as a blueprint for database design, guiding the creation of databases that reflect real-world entities and relationships.

3. How do you translate business rules into data model components?

Business rules are translated into data model components by identifying the entities, attributes, relationships, and constraints they imply. For example, a rule like "a customer can place many orders" would lead to creating a Customer entity, an Order entity, and a one-to-many relationship between them.

4. Describe the basic features of the relational data model and discuss their importance to the end user and the designer

The relational data model organizes data into tables (relations) where each table represents an entity. The model allows for powerful querying capabilities using SQL and ensures data integrity through primary and foreign keys. For the end user, this model provides a straightforward way to interact with data, while for the designer, it offers flexibility and a strong theoretical foundation for database design.


5. Explain how the entity relationship (ER) model helped produce a more structured relational database design environment.

The ER model provides a visual representation of entities and their relationships, which helps designers structure a database in a more organized way. It enables the identification of all necessary entities and relationships upfront, reducing the risk of errors and omissions in the database design process.

6. Consider the scenario described by the statement “A customer can make many payments, but each payment is made by only one customer.” Use this scenario as the basis for an entity relationship diagram (ERD) representation.

The scenario can be represented in an ERD with two entities: Customer and Payment. There would be a one-to-many (1) relationship from Customer to Payment, indicating that each customer can make multiple payments, but each payment is associated with only one customer.

FIGURE 2.10 INTERNAL MODEL FOR TINY COLLEGE



Problems 1-2: Page 66

Use the contents of Figure 2.1 to work Problems 1–3.

1. Write the business rule(s) that govern the relationship between AGENT and CUSTOMER.

The figure provided represents an internal model for Tiny College, illustrating the relationships between various entities such as PROFESSOR, CLASS, ROOM, and COURSE. Although the original question asked about the relationship between AGENT and CUSTOMER, which are not depicted in this figure, we can instead analyze the business rules relevant to Tiny College. According to the model, a PROFESSOR teaches multiple CLASSES, but each CLASS is taught by only one PROFESSOR. Additionally, a CLASS is scheduled in one ROOM, though a ROOM can host many CLASSES over time. Lastly, each COURSE generates multiple CLASSES, and each CLASS is associated with only one COURSE. These relationships reflect the structure and operations of Tiny College as represented in the provided diagram.

2. Given the business rule(s) you wrote in Problem 1, create the basic Crow's Foot ERD.

Based on the analysis of the Tiny College internal model, we can create a basic Crow's Foot Entity-Relationship Diagram (ERD). The entities involved are PROFESSOR, CLASS, ROOM, and COURSE. The relationships between these entities are as follows: A PROFESSOR can teach many CLASSES, but each CLASS is taught by only one PROFESSOR, indicating a one-to-many (1) relationship. A CLASS must be scheduled in one ROOM, but a ROOM can host many CLASSES over time, also forming a one-to-many (1) relationship. Additionally, each COURSE generates multiple CLASSES, creating a one-to-many (1) relationship. The cardinality and optionality indicate that each PROFESSOR must teach at least one CLASS, each CLASS must be assigned to a ROOM, and each COURSE must generate at least one CLASS. This ERD provides a clear and structured visualization of how these entities interact within the context of Tiny College.

1. What is the difference between a database and a table?

A database is a structured collection of data stored in a way that facilitates easy access, management, and updating. It can contain multiple tables. A table, on the other hand, is a specific structure within a database that organizes data into rows and columns, where each row represents a record, and each column represents an attribute of the data.

2. What does it mean to say that a database displays both entity integrity and referential integrity?

Entity integrity ensures that each table has a primary key and that this key is unique and not null for all records in the table. Referential integrity means that foreign keys in a table must match primary keys in another table, ensuring that relationships between tables remain consistent.

3. Why are entity integrity and referential integrity important in a database?

Entity integrity is crucial because it ensures that each record in a table can be uniquely identified, preventing duplication and ensuring data accuracy. Referential integrity is important because it maintains consistency across related tables, ensuring that data referenced in one table has a corresponding, valid entry in another table.

4. What are the requirements that two relations must satisfy to be considered union-compatible?

For two relations (tables) to be union-compatible, they must have the same number of attributes (columns), and corresponding attributes must have the same domain (i.e., the same data type and meaning).

5. Which relational algebra operators can be applied to a pair of tables that are not union-compatible?

For tables that are not union-compatible, the following relational algebra operators can be applied: Cartesian Product (or Cross Join), Theta Join, and Division.

6. Explain why the data dictionary is sometimes called “the database designer’s database.”

The data dictionary is often referred to as “the database designer’s database” because it contains metadata—information about the structure, organization, and constraints of the database itself. This includes details about tables, columns, data types, and relationships, which are essential for designing and maintaining the database.

FIGURE P3.1 THE CH03_STORECO DATABASE TABLES

Table name: EMPLOYEE

Database name: Ch03_StoreCo

EMP_CODE	EMP_TITLE	EMP_LNAME	EMP_FNAME	EMP_INITIAL	EMP_DOB	STORE_CODE
1	Mr.	vWilliamson	John	vV	21-May-64	3
2	Ms.	Ratula	Nancy		09-Feb-69	2
3	Ms.	Greenboro	Lottie	R	02-Oct-61	4
4	Mrs.	Rumpersfro	Jennie	S	01-Jun-71	5
5	Mr.	Smith	Robert	L	23-Nov-59	3
6	Mr.	Renselaer	Cary	A	25-Dec-65	1
7	Mr.	Ogallo	Roberto	S	31-Jul-62	3
8	Ms.	Johnsson	Elizabeth	I	10-Sep-68	1
9	Mr.	Eindsmar	Jack	vV	19-Apr-55	2
10	Mrs.	Jones	Rose	R	06-Mar-66	4
11	Mr.	Broderick	Tom		21-Oct-72	3
12	Mr.	vWashington	Alan	Y	08-Sep-74	2
13	Mr.	Smith	Peter	N	25-Aug-64	3
14	Ms.	Smith	Sherry	H	25-May-66	4
15	Mr.	Olenko	Howard	U	24-May-64	5
16	Mr.	Archialo	Barry	V	03-Sep-60	5
17	Ms.	Grimaldo	Jeanine	K	12-Nov-70	4
18	Mr.	Rosenberg	Andrew	D	24-Jan-71	4
19	Mr.	Rosten	Peter	F	03-Oct-68	4
20	Mr.	Mckee	Robert	S	06-Mar-70	1
21	Ms.	Baumann	Jennifer	A	11-Dec-74	3

Table name: STORE

STORE_CODE	STORE_NAME	STORE_YTD_SALES	REGION_CODE	EMP_CODE
1	Access Junction	1003455.76	2	8
2	Database Corner	1421987.39	2	12
3	Tuple Charge	986783.22	1	7
4	Attribute Alley	944568.56	2	3
5	Primary Key Point	2930098.45	1	15

Table name: REGION

REGION_CODE	REGION_DESCRIPT
1	East
2	vWest

Problems: 1-6: Page 110

Use the database shown in Figure P3.1 to answer Problems 1–9.

1. For each table, identify the primary key and the foreign key(s). If a table does not have a foreign key, write None.

EMPLOYEE Table:

Primary Key: EMP_CODE

Foreign Key: STORE_CODE

STORE Table:

Primary Key: STORE_CODE

Foreign Key: REGION_CODE, EMP_CODE

REGION Table:

Primary Key: REGION_CODE

Foreign Key: None

2. Do the tables exhibit entity integrity? Answer yes or no, and then explain your answer.

Yes, the tables exhibit entity integrity. Each table has a primary key (EMP_CODE for EMPLOYEE, STORE_CODE for STORE, and REGION_CODE for REGION), and all the primary key fields have unique, non-null values.

3. Do the tables exhibit referential integrity? Answer yes or no, and then explain your answer. Write NA (Not Applicable) if the table does not have a foreign key.

EMPLOYEE Table:

NA (No foreign key in EMPLOYEE).

STORE Table:

Yes, the STORE table exhibits referential integrity because the REGION_CODE and EMP_CODE foreign keys refer to valid entries in the REGION and EMPLOYEE tables, respectively.


REGION Table:

NA (No foreign key in REGION).


4. Describe the type(s) of relationship(s) between STORE and REGION.

There is a one-to-many (1) relationship between REGION and STORE, where each REGION can have multiple STORE locations, but each STORE is associated with only one REGION.

5. Create the ERD to show the relationship between STORE and REGION.



6. Create the relational diagram to show the relationship between STORE and REGION.



Chapter 4.

Review Questions: 1-6: Page 153-154

1. What two conditions must be met before an entity can be classified as a weak entity?

Give an example of a weak entity.

A weak entity is an entity that cannot be uniquely identified by its own attributes alone.

Two conditions must be met for an entity to be classified as a weak entity:

It must have a mandatory relationship with a strong entity (one that can be uniquely identified by its own attributes).

It must have a partial key or discriminator that, in combination with the primary key of the strong entity, uniquely identifies its instances.

Example: An example of a weak entity could be a "Dependent" entity in a database where the "Employee" entity is strong. Dependents rely on the employee entity for identification since they are identified through a combination of their attributes (like Dependent Name) and the employee's attributes (like Employee ID).

2. What is a strong (or identifying) relationship, and how is it depicted in a Crow's Foot ERD?

A strong (or identifying) relationship is a relationship where the primary key of the parent entity is part of the primary key in the child entity. In Crow's Foot notation, it is depicted by a solid line connecting the entities, with a key symbol on the parent entity's side and a dashed underline in the child entity to denote the foreign key.


3. Given the business rule “an employee may have many degrees,” discuss its effect on attributes, entities, and relationships. (Hint: Remember what a multivalued attribute is and how it might be implemented.)

The business rule implies that an "Employee" entity and a "Degree" entity should be created with a one-to-many relationship. The "Degree" entity would likely have attributes like Degree Type, Degree Field, and Graduation Year. Each degree would be related to one employee, but each employee could have multiple related degree entries.

4. What is a composite entity, and when is it used?

A composite entity (or associative entity) is used to capture a many-to-many relationship between two or more entities. It typically includes foreign keys from the entities it connects and may also contain additional attributes specific to the relationship. For example, a StudentCourse composite entity might connect Student and Course entities, with foreign keys from both and additional attributes like Enrollment Date.

FIGURE Q4.5 THE CONCEPTUAL MODEL FOR QUESTION 5



5. Suppose you are working within the framework of the conceptual model in Figure Q4.5.

Given the conceptual model in Figure Q4.5:

a. Write the business rules that are reflected in it.

The conceptual model presented reflects several key business rules that define the relationships between entities in a maintenance management system. Firstly, the model shows that a customer can own one or more cars, indicating a one-to-many relationship between customers and cars. Each car, however, is owned by exactly one customer, ensuring exclusivity in this relationship. Secondly, the model indicates that each car can undergo one or more maintenance procedures, emphasizing that maintenance activities are directly tied to specific cars. This relationship ensures that every maintenance record is associated with a single car.

Furthermore, the model details that a maintenance procedure can include one or more maintenance lines, which represent the detailed tasks or operations performed during the maintenance. Each of these maintenance lines is specific to one maintenance procedure, reinforcing the one-to-many relationship. Lastly, the model captures the fact that maintenance lines may require parts, and this relationship is many-to-many. This means that a single part can be used in multiple maintenance lines, and each maintenance line can involve several parts. These business rules ensure that the system can accurately track ownership, maintenance history, and the parts used in each maintenance task.

b. Identify all of the cardinalities.

The conceptual model illustrates several important cardinalities that define the relationships between entities. The relationship between Customer and Car is defined as a one-to-many

(1) relationship. This indicates that while a customer can own multiple cars, each car is associated with exactly one customer. This ensures that the ownership of cars is uniquely tied to individual customers within the database.

Similarly, the relationship between Car and Maintenance is also a one-to-many (1) relationship, meaning that a single car can have multiple maintenance records over time, but each maintenance record pertains to one specific car. This relationship helps to maintain a clear history of maintenance activities for each car.

The relationship between Maintenance and Maintenance Line is again one-to-many (1). This shows that each maintenance procedure can consist of multiple detailed tasks, or maintenance lines, but each of these lines is associated with a specific maintenance procedure. Finally, the relationship between Maintenance Line and Part is a many-to-many (M) relationship, indicating that parts can be used in various maintenance lines, and each maintenance line may involve multiple parts. This many-to-many relationship allows the system to track the usage and allocation of parts across different maintenance tasks comprehensively.

These cardinalities are essential for defining how the entities interact within the database, ensuring that the system can accurately represent the relationships and constraints necessary for effective maintenance management.


6. What is a recursive relationship? Give an example.

A recursive relationship occurs when an entity is related to itself. For example, in an employee database, a recursive relationship might model a situation where one employee (a manager) supervises other employees. In this case, the "Employee" entity might have a relationship with itself, representing the "supervises" relationship.

Problems: 1: Page 156

1. Use the following business rules to create a Crow's Foot ERD. Write all appropriate connectivities and cardinalities in the ERD.

- A department employs many employees, but each employee is employed by only one department.
- Some employees, known as “rovers,” are not assigned to any department.
- A division operates many departments, but each department is operated by only one division.
- An employee may be assigned many projects, and a project may have many employees assigned to it.
- A project must have at least one employee assigned to it.
- One of the employees manages each department, and each department is managed by only one employee.
- One of the employees runs each division, and each division is run by only one employee.



Part II: SQL (60 points)

A. Review Questions (Module Quiz) Chapter 2-4 of the book A Guide to SQL (2015): Odd Review Questions. Copy the question in bold face above the answer. Do not use bold face for the answers.

Chapter 2: Odd Numbers: pg. 46-47

1. What is an entity?

An entity in the context of databases is a distinct object or concept about which data is stored.

3. What is a relationship? What is a one-to-many relationship?

In a database, a relationship is an association between entities. A One-to-Many relationship means that one entity is related to multiple entities.

5. What is a relation?

A relation is a two-dimensional table in a relational database.

7. Describe the shorthand representation of the structure of a relational database.

Why is it important to be able to represent the structure of a database in a shorthand fashion?

The shorthand representation of the structure of a relational database involves listing each table's name followed by its columns within parentheses. For example, a table named CUSTOMER with columns CustomerID, Name, and Address would be represented as CUSTOMER (CustomerID, Name, Address). This method is crucial because it provides a clear, concise overview of the database's structure, making it easier to understand and communicate the relationships and dependencies between different tables. It simplifies the design and documentation process, ensuring that all stakeholders have a consistent understanding of the database schema. Additionally, this representation aids in identifying primary keys, foreign keys, and other constraints, which are essential for maintaining data integrity and optimizing database performance.

9. What does it mean for a column to be functionally dependent on another column?

In a relational database, functional dependence refers to a relationship between two columns. Column B is functionally dependent on column A if, at any given time, a value for column A determines a single value for column B. This means that knowing the value of column A allows you to uniquely identify the value of column B. For example, in a table of sales representatives, if each representative has a unique ID (REP ID), then the last name (LAST NAME) of the representative is functionally dependent on REP ID. Given a specific REP ID, you can determine the corresponding LAST NAME. This concept is crucial for database design as it helps in organizing data efficiently and ensuring data integrity.

11. A database at a college must support the following requirements:

a. For a department, store its number and name.

 DEPARTMENT_NUMBER (Primary Key)

 DEPARTMENT_NAME

b. For an advisor, store his or her number, last name, first name, and the department number to which the advisor is assigned.

 ADVISOR_NUMBER (Primary Key)

 ADVISOR_LAST_NAME

 ADVISOR_FIRST_NAME

 ADVISOR_DEPARTMENT_NUMBER (Foreign Key referencing Department)

c. For a course, store its code and description (for example, DBA210, SQL Programming).

✚ COURSE_CODE (Primary Key)

✚ COURSE_DESCRIPTION

d. For a student, store his or her number, first name, and last name. For each course the student takes, store the course code, course description, and grade earned. Also, store the number and name of the student's advisor. Assume that an advisor might advise any number of students but that each student has just one advisor.

✚ STUDENTS (STUDENT_NUMBER, STUDENT_FIRST_NAME, STUDENT_LAST_NAME, ADVISOR_NUMBER)

❖ STUDENT_NUMBER (Primary Key)

❖ STUDENT_FIRST_NAME

❖ STUDENT_LAST_NAME

❖ ADVISOR_NUMBER


✚ ENROLLMENT (STUDENT_NUMBER, COURSE_CODE, GRADE_EARNED)

❖ STUDENT_NUMBER (Foreign Key referencing STUDENTS)

❖ COURSE_CODE (Foreign Key referencing COURSES)

❖ GRADE_EARNED





Design the database for the preceding set of requirements. Use your own experience as a student to determine any functional dependencies. List the tables, columns, and relationships. In addition, represent your design with an E-R diagram.



13. Define second normal form. What types of problems might you encounter using tables that are not in second normal form?

Second Normal Form (2NF) is a stage in the normalization process of database design. A table is in 2NF if it is in First Normal Form (1NF) and all non-key columns are fully dependent on the entire primary key, not just part of it. This means that there should be no partial dependency of any column on the primary key.

Problems with tables not in 2NF include:

-  Redundancy: Data may be duplicated, wasting storage space.
-  Update Anomalies: Changes in data may require multiple updates, increasing the risk of inconsistencies.
-  Insertion Anomalies: Adding new data may be problematic if certain fields are missing.
-  Deletion Anomalies: Deleting data can inadvertently remove other valuable information.

These issues can lead to inefficiencies and inaccuracies in database management.

15. Using the functional dependencies that you determined in Question 11, convert the following table to an equivalent collection of tables that are in third normal form.

<code>STUDENT (STUDENT_NUM, STUDENT_LAST_NAME, STUDENT_FIRST_NAME, ADVISOR_NUM, ADVISOR_LAST_NAME, ADVISOR_FIRST_NAME, (COURSE_CODE, DESCRIPTION, GRADE))</code>
--

1. Student

Columns: STUDENT_NUM (PK), STUDENT_LAST_NAME, STUDENT_FIRST_NAME, ADVISOR_NUM

2. Advisor

Columns: ADVISOR_NUM (PK), ADVISOR_LAST_NAME, ADVISOR_FIRST_NAME

3. Course

Columns: COURSE_CODE (PK), DESCRIPTION

4. Enrollment

Columns: STUDENT_NUM, COURSE_CODE, GRADE

Primary Key: Composite (STUDENT_NUM, COURSE_CODE)

Chapter 3: Odd Numbers: pg. 92-93

1. How do you create a table using SQL?

To create a table using SQL, you use the CREATE TABLE command. This command is followed by the table name and a list of columns, each with its specified data type, enclosed within parentheses.

3. What are common data types used to define columns using SQL?

In SQL, several common data types are used to define columns in a table.

CHAR(n) is used to store a fixed-length character string, where 'n' specifies the length. VARCHAR(n) is similar but stores variable-length strings, using only as much space as needed. DATE stores date values, with formats varying by SQL implementation. DECIMAL(p,q) stores decimal numbers, where 'p' is the total number of digits and 'q' is the number of digits to the right of the decimal point. INT and SMALLINT store integer values, with SMALLINT using less space. These data types help ensure that the data stored in a database is accurate and efficiently managed.

5. Identify the following column names as valid or invalid in MySQL:

- a. **COMMISSIONRATE** - Valid - This name follows MySQL's rules for column names.
- b. **POSTAL_CODE_5CHAR** - Valid - This name is valid as it uses underscores instead of spaces.
- c. **SHIP TO ADDRESS** - Invalid - Column names cannot contain spaces.
- d. **INVOICE-NUMBER** - Invalid - Column names cannot contain hyphens.

7. Which SQL command do you use to add a row to a table?

To add a row to a table in SQL, you use the INSERT INTO command. This command allows you to specify the table into which you want to insert the new row and the values for each column in that row.

9. Which SQL command do you use to change the value in a column in a table?

To change the value in a column in a table using SQL, you use the UPDATE command. This command allows you to modify existing data within a table.

11. How do you display the columns in a table and their characteristics in MySQL?

To display the columns in a table and their characteristics in MySQL, you can use the DESCRIBE command. This command provides a detailed description of the table's structure, including the column names, data types, and any constraints such as whether a column can accept null values.

Chapter 4: Odd Numbers: pg. 131-132

1. Describe the basic form of the SQL SELECT command.

The basic form of the SQL SELECT command is structured as SELECT-FROM-WHERE. This command is used to query a database and retrieve specific data. The SELECT clause specifies the columns to be included in the query results. Following this, the FROM clause identifies the table that contains these columns. Optionally, the WHERE clause can be included to list any conditions or restrictions that apply to the data being retrieved. This structure allows users to filter and sort data efficiently, making it a fundamental aspect of SQL querying.

3. How do you form a compound condition?

In SQL, a compound condition is created by combining two or more simple conditions using logical operators such as AND, OR, and NOT. For example, to find records where a customer's balance is greater than 100 and their credit limit is less than 500, you would use: WHERE balance > 100 AND credit_limit < 500. This ensures that both conditions must be true for a record to be included in the results.

5. How do you use a computed column in SQL? How do you name the computed column?

A computed column in SQL is a column that is derived from an expression involving other columns in the table. For instance, to calculate the total price of items ordered, you might use: SELECT item_id, quantity * price AS total_price FROM orders. Here, quantity * price is the computed column, and AS total_price names the computed column total_price.

7. What wildcards are available in MySQL, and what do they represent?

MySQL supports several wildcards for pattern matching in queries. The percent sign (%) represents zero or more characters, while the underscore (_) represents a single character. For example, LIKE 'a%' matches any string starting with 'a', and LIKE ' _b%' matches any string with 'b' as the second character.

9. How do you sort data?

To sort data in SQL, you use the ORDER BY clause followed by the column name(s) you want to sort by. By default, the sorting is in ascending order. For example, SELECT * FROM customers ORDER BY last_name sorts the customers by their last names in ascending order.

11. How do you sort data in descending order?

To sort data in descending order, you use the ORDER BY clause followed by the column name and the keyword DESC. For example, SELECT * FROM customers ORDER BY last_name DESC sorts the customers by their last names in descending order.

13. How do you avoid including duplicate values in a query's results?

To avoid including duplicate values in a query's results, you use the DISTINCT keyword. For example, SELECT DISTINCT last_name FROM customers retrieves unique last names from the customers table, eliminating any duplicates.

15. How do you group data in an SQL query?

To group data in SQL, you use the GROUP BY clause followed by the column name(s) you want to group by. This is often used with aggregate functions like COUNT, SUM, AVG, etc. For example, SELECT department, COUNT(*) FROM employees GROUP BY department groups the employees by department and counts the number of employees in each department.

17. How do you find rows in which a particular column contains a null value?

To find rows where a particular column contains a null value, you use the IS NULL condition. For example, `SELECT * FROM customers WHERE email IS NULL` retrieves all customers who do not have an email address listed.

B. Except for Chapters 1 and 2, please show the complete question, query used, and print the query results.

Chapter 1 (A Guide to SQL) Use the Staywell student Accommodation database only.

Case Exercises: Odd number Case Exercises, pg. 13.

Answer each of the following questions using the StayWell data shown in Figures 1-4 through 1-9. No computer work is required.

OWNER

OWNER_NUM	LAST_NAME	FIRST_NAME	ADDRESS	CITY	STATE	ZIP_CODE
MO100	Moore	Elle-May	8006 W. Newport Ave.	Reno	NV	89508
PA101	Patel	Makesh	7337 Sheffield St.	Seattle	WA	98119
AK102	Aksoy	Ceyda	411 Griffin Rd.	Seattle	WA	98131
CO103	Cole	Meerab	9486 Circle Ave.	Olympia	WA	98506
KO104	Kowalczyk	Jakub	7431 S. Bishop St.	Bellingham	WA	98226
SI105	Sims	Haydon	527 Primrose Rd.	Portland	OR	97203
BU106	Burke	Ernest	613 Old Pleasant St.	Twin Falls	ID	83303
RE107	Redman	Seth	7681 Fordham St.	Seattle	WA	98119
LO108	Lopez	Janine	9856 Pumpkin Hill Ln.	Everett	WA	98213
BI109	Bianchi	Nicole	7990 Willow Dr.	New York	NY	10005
JO110	Jones	Ammarah	730 Military Ave.	Seattle	WA	98126

FIGURE 1-5 Sample data for the owners of StayWell properties

PROPERTY

PROPERTY_ID	OFFICE_NUM	ADDRESS	SQ_FOOT	BDRMS	FLOORS	MONTHLY_RENT	OWNER_NUM
1	1	30 West Thomas Rd.	1,600	3	1	1,400	BU106
2	1	782 Queen Ln.	2,100	4	2	1,900	AK102
3	1	9800 Sunbeam Ave.	1,005	2	1	1,200	BI109
4	1	105 North Illinois Rd.	1,750	3	1	1,650	KO104
5	1	887 Vine Rd.	1,125	2	1	1,160	SI105
6	1	8 Laurel Dr.	2,125	4	2	2,050	MO100
7	2	447 Goldfield St.	1,675	3	2	1,700	CO103
8	2	594 Leatherwood Dr.	2,700	5	2	2,750	KO104
9	2	504 Windsor Ave.	700	2	1	1,050	PA101
10	2	891 Alton Dr.	1,300	3	1	1,600	LO108
11	2	9531 Sherwood Rd.	1,075	2	1	1,100	JO110
12	2	2 Bow Ridge Ave.	1,400	3	2	1,700	RE107

FIGURE 1-6 Sample data for StayWell properties

OFFICE

OFFICE_NUM	OFFICE_NAME	ADDRESS	AREA	CITY	STATE	ZIP_CODE
1	StayWell-Columbia City	1135 N. Wells Avenue	Columbia City	Seattle	WA	98118
2	StayWell-Georgetown	986 S. Madison Rd	Georgetown	Seattle	WA	98108

FIGURE 1-4 Sample data for StayWell offices

SERVICE_CATEGORY	CATEGORY_NUM	CATEGORY_DESCRIPTION
1	1	Plumbing
2	2	Heating
3	3	Painting
4	4	Electrical systems
5	5	Carpentry
6	6	Furniture replacement

SERVICE_REQUEST

SERVICE_ID	PROPERTY_ID	CATEGORY_NUMBER	OFFICE_NUM	DESCRIPTION	STATUS	EST_HOURS	SPENT_HOURS	NEXT_SERVICE_DATE
1	11	2	2	The second bedroom upstairs is not heating up at night.	Problem has been confirmed. Central heating engineer has been scheduled.	2	1	11/01/2019
2	1	4	1	A new strip light is needed for the kitchen.	Scheduled	1	0	10/02/2019
3	6	5	1	The bathroom door does not close properly.	Service rep has confirmed issue. Scheduled to be refitted.	3	1	11/09/2019
4	2	4	1	New outlet has been requested for the first upstairs bedroom. (There is currently no outlet).	Scheduled	1	0	10/02/2019
5	8	3	2	New paint job requested for the common area (lounge).	Open	10	0	
6	4	1	1	Shower is dripping when not in use.	Problem confirmed. Plumber has been scheduled.	4	2	10/07/2019
7	2	2	1	Heating unit in the entrance smells like it's burning.	Service rep confirmed the issue to be dust in the heating unit. To be cleaned.	1	0	10/09/2019
8	9	1	2	Kitchen sink does not drain properly.	Problem confirmed. Plumber scheduled.	6	2	11/12/2019
9	12	6	2	New sofa requested.	Open	2	0	











FIGURE 1-8 Sample service request category

RESIDENTS





RESIDENT_ID	FIRST_NAME	SURNAME	PROPERTY_ID
1	Albie	O'Ryan	1
2	Tariq	Khan	1
3	Ismail	Salib	1
4	Callen	Beck	2
5	Milosz	Polansky	2
6	Ashanti	Lucas	2
7	Randy	Woodrue	2
8	Aislinn	Lawrence	3
9	Monique	French	3
10	Amara	Dejsuwan	4
12	Rosalie	Blackmore	4
13	Carina	Britton	4
14	Valentino	Ortega	5
15	Kaylem	Kent	5
16	Alessia	Wagner	6
17	Tyrone	Galvan	6
18	Constance	Fleming	6
19	Eamonn	Bain	6
20	Mishbah	Yacob	7
21	Gianluca	Esposito	7
22	Elinor	Lake	7
23	Ray	Rosas	8
24	Damon	Caldwell	8
25	Dawood	Busby	8
26	Dora	Harris	8
27	Leroy	Stokes	8
28	Tamia	Hess	9
29	Amelia	Sanders	9
30	Zarah	Byers	10
31	Sara	Farrow	10
32	Delilah	Roy	10
33	Dougie	McDaniel	11
34	Tahir	Halabi	11
35	Mila	Zhikin	12
36	Glenn	Donovan	12
37	Zayn	Fowler	12

FIGURE 1-9 Sample data for StayWell residents




1. List the owner number, last name, and first name of every property owner.

-  PA101: Patel, Makesh
-  AK102: Aksoy, Ceyda
-  CO103: Cole, Meerab
-  KO104: Kowalczyk, Jakub
-  SI105: Sims, Haydon
-  BU106: Burke, Ernest
-  RE107: Redman, Seth
-  LO108: Lopez, Janine
-  BI109: Bianchi, Nicole
-  JO110: Jones, Ammarah

3. List the property ID for each condo that is smaller than 1,600 square feet.

-  3: 9800 Sunbeam Ave., 1,005 square feet
-  5: 887 Vine Rd., 1,125 square feet
-  9: 891 Alton Dr., 1,300 square feet
-  11: 9531 Sherwood Rd., 1,075 square feet


5. List the last name, first name, and city of every owner with a property that has a monthly rent of less than \$1,400 per month.


-  Moore, Elle-May from Reno, NV
-  Aksoy, Ceyda from Seattle, WA
-  Bianchi, Nicole from New York, NY

7. How many properties have two floors?


There are 4 properties with two floors (Properties with IDs: 2, 6, 7, and 8).


9. List the owner's last and first names and property IDs for each property that has a scheduled or open service request.

 Sims, Haydon (Property ID: 5)

 Jones, Ammarah (Property ID: 12)

11. List the property ID and office number for all service requests for which the estimated number of hours is greater than 5.

 Property ID: 8, Office Number: 2

 Property ID: 12, Office Number: 2

Chapter 2 (A Guide to SQL) Use the Staywell student Accommodation database only.
Case Exercises: Odd Number Case Exercises, pg. 48-49.

OWNER						
OWNER_NUM	LAST_NAME	FIRST_NAME	ADDRESS	CITY	STATE	ZIP_CODE
MO100	Moore	Elle-May	8006 W. Newport Ave.	Reno	NV	89508
PA101	Patel	Mahesh	7337 Sheffield St.	Seattle	WA	98119
AK102	Aksoy	Ceyda	411 Griffin Rd.	Seattle	WA	98131
CO103	Cole	Moerab	9486 Circle Ave.	Olympia	WA	98506
RO104	Rowalczyk	Jakub	7431 S. Bishop St.	Bellingham	WA	98226
RI105	Rims	Haydon	527 Primrose Rd.	Portland	OR	97203
BU106	Burke	Ernest	613 Old Pleasant St.	Twin Falls	ID	83303
RE107	Redman	Seth	7681 Fordham St.	Seattle	WA	98119
LO108	Lopca	Janina	9856 Pumpkin Hill Ln.	Everett	WA	98213
BI109	Blanchi	Nicole	7990 Willow Dr.	New York	NY	10005
JO110	Jones	Ammarah	730 Military Ave.	Seattle	WA	98126

FIGURE 1-5 Sample data for the owners of StayWell properties

PROPERTY							
PROPERTY_ID	OFFICE_NUM	ADDRESS	SQR_FT	BDRMS	FLOORS	MONTHLY_RENT	OWNER_NUM
1	1	30 West Thomas Rd.	1,600	3	1	1,400	BU106
2	1	782 Queen Ln.	2,100	4	2	1,900	AK102
3	1	9809 Sunbeam Ave.	1,005	2	1	1,200	RI109
4	1	105 North Illinois Rd.	1,780	3	1	1,630	RO104
5	1	887 Vine Rd.	1,125	2	1	1,160	SI105
6	1	8 Laurel Dr.	2,125	4	2	2,080	MO100
7	2	447 Goldfield St.	1,675	3	2	1,700	CO103
8	2	394 Leatherwood Dr.	2,700	5	2	2,750	RO104
9	2	504 Winzor Ave.	700	2	1	1,050	PA101
10	2	891 Alton Dr.	1,300	3	1	1,690	LO108
11	2	9531 Silverwood Rd.	1,075	2	1	1,100	JO110
12	2	2 Rose Ridge Ave.	1,400	3	2	1,700	RE107

FIGURE 1-6 Sample data for StayWell properties

OFFICE						
OFFICE_NUM	OFFICE_NAME	ADDRESS	AREA	CITY	STATE	ZIP_CODE
1	StayWell-Columbia City	1135 N. Wells Avenue	Columbia City	Seattle	WA	98118
2	StayWell-Georgetown	986 S. Madison Rd.	Georgetown	Seattle	WA	98108

FIGURE 1-4 Sample data for StayWell offices

SERVICE_REQUEST								
SERVICE_ID	PROPERTY_ID	CATEGORY_NUMBER	OFFICE_NUM	DESCRIPTION	STATUS	EST_HOURS	SPENT_HOURS	NEXT_SERVICE_DATE
1	11	2	2	The second bedroom upstairs is not heating up at night.	Problem has been confirmed. Central heating engineer has been scheduled.	2	1	11/01/2019
2	1	4	1	A new strip light is needed for the kitchen.	Scheduled	1	0	10/02/2019
3	6	5	1	The bathroom door does not close properly.	Service rep has confirmed issue. Scheduled to be refitted.	3	1	11/09/2019
4	2	4	1	New outlet has been requested for the first upstairs bedroom. (There is currently no outlet).	Scheduled	1	0	10/02/2019
5	8	3	2	New paint job requested for the common area (lounge).	Open	10	0	
6	4	1	1	Shower is dripping when not in use.	Problem confirmed. Plumber has been scheduled.	4	2	10/07/2019
7	2	2	1	Heating unit in the entrance smells like it's burning.	Service rep confirmed the issue to be dust in the heating unit. To be cleaned.	1	0	10/09/2019
8	9	1	2	Kitchen sink does not drain properly.	Problem confirmed. Plumber scheduled.	6	2	11/12/2019
9	12	6	2	New sofa requested.	Open	2	0	

FIGURE 1-8 Sample service request category

SERVICE_CATEGORY	
CATEGORY_NUM	CATEGORY_DESCRIPTION
1	Plumbing
2	Heating
3	Painting
4	Electrical systems
5	Carpentry
6	Furniture replacement

FIGURE 1-7 Sample category data for StayWell maintenance services

RESIDENTS

RESIDENT_ID	FIRST_NAME	SURNAME	PROPERTY_ID
1	Albie	O'Ryan	1
2	Tariq	Khan	1
3	Ismail	Salib	1
4	Callen	Beck	2
5	Milosz	Polansky	2
6	Ashanti	Lucas	2
7	Randy	Woodrue	2
8	Aislinn	Lawrence	3
9	Monique	French	3
10	Amara	Dejsuwan	4
12	Rosalie	Blackmore	4
13	Carina	Britton	4
14	Valentino	Ortega	5
15	Kaylem	Kent	5
16	Alessia	Wagner	6
17	Tyrone	Galvan	6
18	Constance	Fleming	6
19	Eamonn	Bain	6
20	Misbah	Yacob	7
21	Gianluca	Esposito	7
22	Elinor	Lake	7
23	Ray	Rosas	8
24	Damon	Caldwell	8
25	Dawood	Busby	8
26	Dora	Harris	8
27	Leroy	Stokes	8
28	Tamia	Hess	9
29	Amelia	Sanders	9
30	Zarah	Byers	10
31	Sara	Farrow	10
32	Delilah	Roy	10
33	Dougjie	McDaniel	11
34	Tahir	Halabi	11
35	Mila	Zhikin	12
36	Glenn	Donovan	12
37	Zayn	Fowler	12

FIGURE 1-9 Sample data for StayWell residents

Answer each of the following questions using the StayWell Student Accommodation data shown in Figures 1-4 through 1-9 in Module 1. No computer work is required.

1. Determine the functional dependencies that exist in the following table and then convert this table to an equivalent collection of tables that are in third normal form.

OFFICE (OFFICE_NUM, OFFICE_NAME, (ADDRESS, SQR_FT, BDRMS, FLOORS, MONTHLY_RENT, OWNER_NUM))
--

1. OFFICE

✚ OFFICE_NUM (PK): Primary key, unique identifier for each office.

✚ ADDRESS: Address of the office.

✚ SQR_FT: Square footage of the office.

✚ BDRMS: Number of bedrooms in the office.

✚ FLOORS: Number of floors in the office.

✚ MONTHLY_RENT: Monthly rent price.

✚ OWNER_NUM (FK): Foreign key that links to the OWNER table.

2. OWNER

✚ OWNER_NUM (PK): Primary key, unique identifier for each owner.

✚ OWNER_NAME: Name of the owner.

3. Relationship

✚ Each OFFICE belongs to one OWNER, with the foreign key in OFFICE referencing the primary key in OWNER.

3. StayWell also rents out properties on a weekly basis to students attending summer school in the Seattle area. Design a database to meet the following requirements, using the shorthand representation and a diagram of your choice.

a. For each student renter, list his or her number, first name, middle initial, last name, address, city, state, postal code, telephone number, and e-mail address.

Student Renter:

- + Renter_ID (PK): Primary key.
- + First_Name
- + Middle_Initial
- + Last_Name
- + Address
- + City
- + State
- + Postal_Code
- + Telephone_Number
- + Email

b. For each property, list the office number, property address, city, state, postal code, square footage, number of bedrooms, number of floors, maximum number of persons that can sleep in the unit, and the base weekly rate.


Property:

- + Property_ID (PK): Primary key.
- + Office_Num (FK): Foreign key.
- + Address
- + City
- + State
- + Postal_Code
- + Sqr_Ft
- + Bedrooms
- + Floors
- + Max_Occupancy
- + Weekly_Rate

c. For each rental agreement, list the renter number, first name, middle initial, last name, address, city, state, postal code, telephone number, start date of the rental, end date of the rental, and the weekly rental amount. The rental period is one or more weeks.

Rental Agreement:

- + Rental_ID (PK): Primary key.
- + Renter_ID (FK): Foreign key.
- + Property_ID (FK): Foreign key.
- + Start_Date
- + End_Date
- + Weekly_Rental_Amount



For Chapters 3 and 4 please show the screen print out of the Oracle or MySQL (among others) output. Use the Staywell student Accommodation database only.

Chapter 3 (A Guide to SQL) Use the Staywell student Accommodation database only.

Review Questions: Odd Numbers: pgs. 92-93

1. How do you create a table using SQL?

To create a table using SQL, you use the CREATE TABLE command. Ex:

CREATE TABLE table_name (


column1 datatype,


column2 datatype,


...


);


3. What are common data types used to define columns using SQL?

 CHAR(n): Stores a fixed-length character string. Useful for columns containing letters, special characters, or numbers not used in calculations.

 VARCHAR(n): Stores a variable-length character string. More space-efficient than CHAR but slower in processing.

 DATE: Stores date data. The format varies by SQL implementation (e.g., 'YYYY-MM-DD' in MySQL and SQL Server).

 INT: Stores integers, which are numbers without a decimal part. Suitable for calculations.

 DECIMAL(p,q): Stores a decimal number with a specified number of digits. Useful for precise calculations involving decimal points.

5. Identify the following column names as valid or invalid in MySQL:

a. COMMISSIONRATE - Valid. It follows the rules for column names, which can include letters and numbers without spaces.

b. POSTAL_CODE_5CHAR - Valid. It uses underscores to separate words, which is acceptable in MySQL.

c. SHIP TO ADDRESS - Invalid. Column names cannot contain spaces. You could use underscores instead, like SHIP_TO_ADDRESS.

d. INVOICE-NUMBER - Invalid. Column names cannot contain hyphens. You could use underscores instead, like INVOICE_NUMBER.

7. Which SQL command do you use to add a row to a table?

To add a row to a table in SQL, you use the INSERT command. Ex:

INSERT INTO table_name (column1, column2, column3, ...)

VALUES (value1, value2, value3, ...);

9. Which SQL command do you use to change the value in a column in a table?

To change the value in a column in a table, you use the UPDATE command. Ex:

UPDATE table_name

SET column_name = new_value

WHERE condition;

11. How do you display the columns in a table and their characteristics in MySQL?

To display the columns in a table and their characteristics in MySQL, you can use the DESCRIBE command. Ex:

DESCRIBE table_name;

Case Exercises: Odd Numbers: pgs. 94-95.

OFFICE

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
OFFICE_NUM	DECIMAL	2	0	No	Office number (primary key)
OFFICE_NAME	CHAR	25			Office name
ADDRESS	CHAR	25			Office address
AREA	CHAR	25			Office area
CITY	CHAR	25			Office city
STATE	CHAR	2			Office state
ZIP_CODE	CHAR	5			Office zip code

OWNER

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
OWNER_NUM	CHAR	2		No	Office number (primary key)
LAST_NAME	CHAR	25			Owner last name
FIRST_NAME	CHAR	25			Owner first name
ADDRESS	CHAR	25			Owner street address
CITY	CHAR	25			Owner city
STATE	CHAR	2			Owner state
ZIP_CODE	CHAR	5			Owner zip code

PROPERTY

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
PROPERTY_ID	DECIMAL	2	0	No	Property ID (primary key)
OFFICE_NUM	DECIMAL	2	0		Number of office managing the property
ADDRESS	CHAR	25			Property address
SQR_FT	DECIMAL	5	0		Property size in square feet
BDRMS	DECIMAL	2	0		Number of bedrooms of the property
FLOORS	DECIMAL	2	0		Number of floors
MONTHLY_RENT	DECIMAL	6	2		Monthly property rent
OWNER_NUM	CHAR	5			Number of property owner

FIGURE 3-48 Table layouts for the StayWell Student Accommodation database

SERVICE_CATEGORY

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
CATEGORY_NUM	DECIMAL	2	0	No	Category number (primary key)
CATEGORY_DESCRIPTION	CHAR	35			Category description

SERVICE_REQUEST

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
SERVICE_ID	DECIMAL	2	0	No	Service ID (primary key)
PROPERTY_ID	DECIMAL	35			Property for which the service is requested
CATEGORY_NUMBER	DECIMAL	2			Category number of the service requested
OFFICE_ID	DECIMAL	2			Number of the office managing the property
DESCRIPTION	CHAR	255			Description of the specific service e required
STATUS	CHAR	255			Description of the status of the service request
EST_HOURS	DECIMAL	4			Estimated number of hours required to complete the service
SPENT_HOUSE	DECIMAL	4			Hours already spent on the service
NEXT_SERVICE_DATE	CHAR				Next scheduled date for work on this service (or null if no next service is required)

RESIDENTS

COLUMN	TYPE	LENGTH	DECIMAL PLACES	NULLS ALLOWED	DESCRIPTION
RESIDENT_ID	DECIMAL	2	0	No	ID of property resident (primary key)
FIRST_NAME	CHAR	25			First name of resident
SURNAME	CHAR	25			Last name of resident
PROPERTY_ID	DECIMAL	2			Property number

FIGURE 3-48 Table layouts for the StayWell Student Accommodation database (Continued)

StayWell Student Accommodation

Use SQL to complete the following exercises.

1. Create a table named **SUMMER_SCHOOL_RENTALS**. The table has the same structure as the **PROPERTY** table shown in Figure 3-48 except the **PROPERTY_ID** and **OFFICE_NUMBER** columns should use the **NUMBER** data type and the **MONTHLY_RENT** column should be changed to **WEEKLY_RENT**. Execute the command to describe the layout and characteristics of the **SUMMER_SCHOOL_RENTALS** table.

The screenshot shows the Oracle Application Express SQL Commands window. The SQL command entered is:

```
CREATE TABLE SUMMER_SCHOOL_RENTALS (  
  PROPERTY_ID NUMBER(2) NOT NULL,  
  OFFICE_NUM NUMBER(2) NOT NULL,  
  ADDRESS CHAR(25),  
  SQRT DECIMAL(5, 0),  
  BDRMS DECIMAL(2, 0),  
  FLOORS DECIMAL(2, 0),  
  WEEKLY_RENT DECIMAL(6, 2),  
  OWNER_NUM CHAR(5)  
);
```

The command has been executed successfully, as indicated by the "Results" tab showing "Table created." and a execution time of "0.05 seconds".

A yellow sticky note is overlaid on the right side of the SQL editor, containing the text:

Coral S. Schmidt Montilla
#148830

The interface also shows the "Autocommit" checkbox checked, the "Rows" dropdown set to 10, and the "Schema" dropdown set to CORAL.

SQL Commands

127.0.0.1:8080/...

ORACLE Application Express

Welcome CORAL (Logout)

Home

Application Builder

SQL Workshop

Team Development

Administration

Home > SQL Workshop > SQL Commands

Schema CORAL

☒ Autocommit

Rows 10

Save

Run

DESCRIBE SUMMER_SCHOOL_RENTALS;

Coral S. Schmidt Montilla
#148830

B *I* U

Results

Explain

Describe

Saved SQL

History

Object Type TABLE Object SUMMER_SCHOOL_RENTALS

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default
SUMMER_SCHOOL_RENTALS	PROPERTY_ID	NUMBER	-	2	0	-	-	-
	OFFICE_NUM	NUMBER	-	2	0	-	-	-
	ADDRESS	CHAR	25	-	-	-	✓	-
	SQR_FT	NUMBER	-	5	0	-	✓	-
	BDRMS	NUMBER	-	2	0	-	✓	-
	FLOORS	NUMBER	-	2	0	-	✓	-
	WEEKLY_RENT	NUMBER	-	6	2	-	✓	-
	OWNER_NUM	CHAR	5	-	-	-	✓	-

Workspace: CORAL User: CORAL

Language: en | Copyright

3. Delete the SUMMER_SCHOOL_RENTALS table.

The screenshot shows the Oracle Application Express interface. The browser address bar indicates the URL `127.0.0.1:8080/...`. The page title is "ORACLE Application Express" and the user is logged in as "CORAL". The navigation menu includes "Home", "Application Builder", "SQL Workshop", "Team Development", and "Administration". The breadcrumb trail shows "Home > SQL Workshop > SQL Commands". The "Schema" dropdown is set to "CORAL".

In the SQL Commands window, the "Autocommit" checkbox is checked, and the "Rows" limit is set to 10. The SQL command entered is `DROP TABLE SUMMER_SCHOOL_RENTALS;`. The "Run" button is highlighted in yellow.

A yellow sticky note is overlaid on the right side of the SQL Commands window, containing the text: "Coral S. Schmidt Montilla #148830".

The "Results" tab is selected, showing the output: "Table dropped." and "0.07 seconds".

The footer of the interface displays "Workspace: CORAL User: CORAL" and "Language: en | Copyright".

5. Confirm that you have created the tables correctly by describing each table and comparing the results to Figures 3-48.

The screenshot shows the Oracle Application Express SQL Workshop interface. The top navigation bar includes links for Home, Application Builder, SQL Workshop, Team Development, and Administration. The current page is SQL Workshop > SQL Commands. The command entered is `DESCRIBE OFFICE`. The results are displayed in a table format.

Object Type TABLE **Object** OFFICE

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
OFFICE	OFFICE_NUM	NUMBER	-	2	0	1	-	-	-
	OFFICE_NAME	CHAR	25	-	-	-	✓	-	-
	ADDRESS	CHAR	25	-	-	-	✓	-	-
	AREA	CHAR	25	-	-	-	✓	-	-
	CITY	CHAR	25	-	-	-	✓	-	-
	STATE	CHAR	2	-	-	-	✓	-	-
	ZIP_CODE	CHAR	5	-	-	-	✓	-	-

1 - 7

Workspace: CORAL User: CORAL

Application Express 4.0.2.00.04

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

A yellow sticky note is overlaid on the right side of the interface, containing the text: Coral S. Schmidt Montilla #148830.

SQL Commands

127.0.0.1:8080/a...

ORACLE® Application Express

Welcome CORAL (Logout)

Home

Application Builder

SQL Workshop

Team Development

Administration

Home > SQL Workshop > SQL Commands

Schema CORAL

Help

☒ Autocommit

Rows 10

Save

Run

DESCRIBE OWNER

Coral S. Schmidt Montilla
#148830

Results

Explain

Describe

Saved SQL

History

Object Type

TABLE

Object

OWNER

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
OWNER	OWNER_NUM	CHAR	2	-	-	1	-	-	-
	LAST_NAME	CHAR	25	-	-	-	✓	-	-
	FIRST_NAME	CHAR	25	-	-	-	✓	-	-
	ADDRESS	CHAR	25	-	-	-	✓	-	-
	CITY	CHAR	25	-	-	-	✓	-	-
	STATE	CHAR	2	-	-	-	✓	-	-
	ZIP_CODE	CHAR	5	-	-	-	✓	-	-
1 - 7									

Application Express 4.0.2.00.0

Workspace: CORAL User: CORAL

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved

SQL Commands

127.0.0.1:8080/a...

ORACLE® Application Express

Welcome CORAL (Logout)

Home

Application Builder

SQL Workshop

Team Development

Administration

Home > SQL Workshop > SQL Commands

Schema CORAL

Autocommit Rows 10 Save Run

DESCRIBE PROPERTY

+

...

×

Coral S. Schmidt Montilla
#148830

B

I

U

ab

≡

🖼️

Results

Explain

Describe

Saved SQL

History

Object Type TABLE Object PROPERTY

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
PROPERTY	PROPERTY_ID	NUMBER	-	2	0	1	-	-	-
	OFFICE_NUM	NUMBER	-	2	0	-	✓	-	-
	ADDRESS	CHAR	25	-	-	-	✓	-	-
	SQR_FT	NUMBER	-	5	0	-	✓	-	-
	BDRMS	NUMBER	-	2	0	-	✓	-	-
	FLOORS	NUMBER	-	2	0	-	✓	-	-
	MONTHLY_RENT	NUMBER	-	6	2	-	✓	-	-
	OWNER_NUM	CHAR	5	-	-	-	✓	-	-
1 - 8									

Application Express 4.0.2.00.0

Workspace: CORAL User: CORAL

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved

SQL Commands

127.0.0.1:8080/a...

ORACLE® Application Express

Welcome CORAL (Logout)

HomeApplication BuilderSQL WorkshopTeam DevelopmentAdministration

Home > SQL Workshop > SQL Commands

Schema CORAL

Autocommit Rows 10 Save Run

DESCRIBE SERVICE_CATEGORY

Coral S. Schmidt Montilla
#148830

B*I*U

ResultsExplainDescribeSaved SQLHistory

Object Type TABLE Object SERVICE_CATEGORY

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
SERVICE_CATEGORY	CATEGORY_NUM	NUMBER	-	2	0	1	-	-	-
	CATEGORY_DESCRIPTION	CHAR	35	-	-	-	✓	-	-
									1 - 2

Application Express 4.0.2.00.0!

Workspace: CORAL User: CORAL

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

SQL Commands

127.0.0.1:8080/a...

ORACLE Application Express

Welcome CORAL (Logout)

Home

Application Builder

SQL Workshop

Team Development

Administration

Home > SQL Workshop > SQL Commands

Schema CORAL

Autocommit Rows 10 Save Run

DESCRIBE SERVICE_REQUEST

+

Coral S. Schmidt Montilla
#148830

B

I

U

ab

Results

Explain

Describe

Saved SQL

History

Object Type TABLE Object SERVICE_REQUEST

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
SERVICE_REQUEST	SERVICE_ID	NUMBER	-	2	0	1	-	-	-
	PROPERTY_ID	NUMBER	-	35	0	-	✓	-	-
	CATEGORY_NUMBER	NUMBER	-	2	0	-	✓	-	-
	OFFICE_ID	NUMBER	-	2	0	-	✓	-	-
	DESCRIPTION	CHAR	255	-	-	-	✓	-	-
	STATUS	CHAR	255	-	-	-	✓	-	-
	EST_HOURS	NUMBER	-	4	0	-	✓	-	-
	SPENT_HOURS	NUMBER	-	4	0	-	✓	-	-
	NEXT_SERVICE_DATE	CHAR	25	-	-	-	✓	-	-
1 - 9									

Application Express 4.0.2.00.09

Workspace: CORAL User: CORAL

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

SQL Commands

127.0.0.1:8080/a...

ORACLE Application Express

Welcome CORAL (Logout)

HomeApplication BuilderSQL WorkshopTeam DevelopmentAdministration

Home > SQL Workshop > SQL Commands

Schema CORAL

Help

☒ AutocommitRows10SaveRun

DESCRIBE RESIDENTS

Coral S. Schmidt Montilla
#148830

B*I*Uab☰🖼️

ResultsExplainDescribeSaved SQLHistory

Object TypeTABLEObjectRESIDENTS

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
RESIDENTS	RESIDENT_ID	NUMBER	-	2	0	1	-	-	-
	FIRST_NAME	CHAR	25	-	-	-	✓	-	-
	SURNAME	CHAR	25	-	-	-	✓	-	-
	PROPERTY_ID	NUMBER	-	2	0	-	✓	-	-
1 - 4									

Application Express 4.0.2.00.04

Workspace: CORAL User: CORALLanguage: en | Copyright © 1999, 2010, Oracle. All rights reserved.

Chapter 4 (A Guide to SQL) Use the Staywell student Accommodation database only.

Review Questions: Odd Numbers: pgs. 101-102

1. Describe the basic form of the SQL SELECT command.

The basic form of the SQL SELECT command is SELECT-FROM-WHERE:12

✚ SELECT: Specify the columns you want to retrieve.

✚ FROM: Indicate the table containing these columns.

✚ WHERE: (Optional) List any conditions to filter the data.

Ex:

SELECT column1, column2

FROM table_name

WHERE condition;

3. How do you form a compound condition?

To form a compound condition in SQL, you connect two or more simple conditions using the AND, OR, and NOT operators:

✚ AND: All simple conditions must be true for the compound condition to be true.

✚ OR: The compound condition is true if any one of the simple conditions is true.

✚ NOT: Reverses the truth of the original condition.

Ex:

SELECT DESCRIPTION

FROM ITEM

WHERE (LOCATION = 'B') AND (ON_HAND > 15);

5. How do you use a computed column in SQL? How do you name the computed column?

Using a Computed Column in SQL:

✚ Performing Computations: You can perform computations using SQL queries.

A computed column does not exist in the database but can be computed using data in the existing columns. For example, to compute available credit, you can use the expression `CREDIT_LIMIT - BALANCE`.

Naming a Computed Column:

✚ Assigning a Name: You can assign a name, or alias, to a computed column by following the computation with the word `AS` and the desired name. For example, `CREDIT_LIMIT - BALANCE AS AVAILABLE_CREDIT`.

7. What wildcards are available in MySQL, and what do they represent?

In MySQL, there are two main wildcard characters used in SQL queries:

✚ Percent Sign (%): Represents any collection of characters. For example, `LIKE "%Rock%"` matches any string containing "Rock".

✚ Underscore (_): Represents any single character. For example, `LIKE "T_m"` matches "Tim", "Tom", or "T3m".

These wildcards are typically used with the `LIKE` operator to search for patterns within text columns.

9. How do you sort data?

To sort data in SQL, you use the ORDER BY clause. Here are the key points:

✚ Basic Sorting: Use ORDER BY column name to sort data in ascending order by default.

- ✚ Descending Order: Add DESC after the column name to sort in descending order, e.g., ORDER BY column_name DESC.
- ✚ Multiple Keys: List multiple columns separated by commas to sort by multiple keys, e.g., ORDER BY column1, column2 DESC.
- ✚ Major and Minor Keys: The first column listed is the major sort key, and the subsequent columns are minor sort keys.

11. How do you sort data in descending order?

To sort data in descending order in SQL, you use the ORDER BY clause followed by the column name and the DESC keyword. Ex:

```
SELECT column_name  
FROM table_name  
ORDER BY column_name DESC;
```

13. How do you avoid including duplicate values in a query's results?

To avoid including duplicate values in a query's results, you can use the DISTINCT operator in your SQL command. This operator ensures that only unique values are returned in the query results. Ex:

```
SELECT DISTINCT column_name  
FROM table_name;
```

15. How do you group data in an SQL query?

To group data in an SQL query, you use the GROUP BY clause. This clause allows you to group rows that have the same values in specified columns. Ex:

```
SELECT column_name, COUNT(*)  
FROM table_name
```

GROUP BY column_name;

17. How do you find rows in which a particular column contains a null value?

To find rows where a particular column contains a null value in SQL, you can use

the IS NULL operator in a WHERE clause. Ex:

SELECT column1, column2, ...

FROM table_name

WHERE column_name IS NULL;

Case Exercises: Odd Numbers: pgs. 133-134.

OFFICE

OFFICE_NUM	OFFICE_NAME	ADDRESS	AREA	CITY	STATE	ZIP_CODE
1	StayWell-Columbia City	1135 N. Wells Avenue	Columbia City	Seattle	WA	98118
2	StayWell-Georgetown	986 S. Madison Rd	Georgetown	Seattle	WA	98108

FIGURE 1-4 Sample data for StayWell offices

OWNER

OWNER_NUM	LAST_NAME	FIRST_NAME	ADDRESS	CITY	STATE	ZIP_CODE
MO100	Moore	Elle-May	8006 W. Newport Ave.	Reno	NV	89508
PA101	Patel	Makesh	7337 Sheffield St.	Seattle	WA	98119
AK102	Aksoy	Ceyda	411 Griffin Rd.	Seattle	WA	98131
CO103	Cole	Meerab	9486 Circle Ave.	Olympia	WA	98506
KO104	Kowalczyk	Jakub	7431 S. Bishop St.	Bellingham	WA	98226
SI105	Sims	Haydon	527 Primrose Rd.	Portland	OR	97203
BU106	Burke	Ernest	613 Old Pleasant St.	Twin Falls	ID	83303
RE107	Redman	Seth	7681 Fordham St.	Seattle	WA	98119
LO108	Lopez	Janine	9856 Pumpkin Hill Ln.	Everett	WA	98213
BI109	Bianchi	Nicole	7990 Willow Dr.	New York	NY	10005
JO110	Jones	Ammarah	730 Military Ave.	Seattle	WA	98126

FIGURE 1-5 Sample data for the owners of StayWell properties

PROPERTY

PROPERTY_ID	OFFICE_NUM	ADDRESS	SQR_FT	BDRMS	FLOORS	MONTHLY_RENT	OWNER_NUM
1	1	30 West Thomas Rd.	1,600	3	1	1,400	BU106
2	1	782 Queen Ln.	2,100	4	2	1,900	AK102
3	1	9800 Sunbeam Ave.	1,005	2	1	1,200	BI109
4	1	105 North Illinois Rd.	1,750	3	1	1,650	KO104
5	1	887 Vine Rd.	1,125	2	1	1,160	SI105
6	1	8 Laurel Dr.	2,125	4	2	2,050	MO100
7	2	447 Goldfield St.	1,675	3	2	1,700	CO103
8	2	594 Leatherwood Dr.	2,700	5	2	2,750	KO104
9	2	504 Windsor Ave.	700	2	1	1,050	PA101
10	2	891 Alton Dr.	1,300	3	1	1,600	LO108
11	2	9531 Sherwood Rd.	1,075	2	1	1,100	JO110
12	2	2 Bow Ridge Ave.	1,400	3	2	1,700	RE107

FIGURE 1-6 Sample data for StayWell properties

SERVICE_CATEGORY

CATEGORY_NUM	CATEGORY_DESCRIPTION
1	Plumbing
2	Heating
3	Painting
4	Electrical systems
5	Carpentry
6	Furniture replacement

FIGURE 1-7 Sample category data for StayWell maintenance services

RESIDENTS

RESIDENT_ID	FIRST_NAME	SURNAME	PROPERTY_ID
1	Albie	O'Ryan	1
2	Tariq	Khan	1
3	Ismail	Salib	1
4	Callen	Beck	2
5	Milosz	Polansky	2
6	Ashanti	Lucas	2
7	Randy	Woodrue	2
8	Aislinn	Lawrence	3
9	Monique	French	3
10	Amara	Dejsuwan	4
12	Rosalie	Blackmore	4
13	Carina	Britton	4
14	Valentino	Ortega	5
15	Kaylem	Kent	5
16	Alessia	Wagner	6
17	Tyrone	Galvan	6
18	Constance	Fleming	6
19	Eamonn	Bain	6
20	Misbah	Yacob	7
21	Gianluca	Esposito	7
22	Elinor	Lake	7
23	Ray	Rosas	8
24	Damon	Caldwell	8
25	Dawood	Busby	8
26	Dora	Harris	8
27	Leroy	Stokes	8
28	Tamia	Hess	9
29	Amelia	Sanders	9
30	Zarah	Byers	10
31	Sara	Farrow	10
32	Delilah	Roy	10
33	Dougie	McDaniel	11
34	Tahir	Halabi	11
35	Mila	Zhikin	12
36	Glenn	Donovan	12
37	Zayn	Fowler	12

FIGURE 1-9 Sample data for StayWell residents

SERVICE_REQUEST

SERVICE_ID	PROPERTY_ID	CATEGORY_NUMBER	OFFICE_NUM	DESCRIPTION	STATUS	EST_HOURS	SPENT_HOURS	NEXT_SERVICE_DATE
1	11	2	2	The second bedroom upstairs is not heating up at night.	Problem has been confirmed. Central heating engineer has been scheduled.	2	1	11/01/2019
2	1	4	1	A new strip light is needed for the kitchen.	Scheduled	1	0	10/02/2019
3	6	5	1	The bathroom door does not close properly.	Service rep has confirmed issue. Scheduled to be refitted.	3	1	11/09/2019
4	2	4	1	New outlet has been requested for the first upstairs bedroom. (There is currently no outlet).	Scheduled	1	0	10/02/2019
5	8	3	2	New paint job requested for the common area (lounge).	Open	10	0	
6	4	1	1	Shower is dripping when not in use.	Problem confirmed. Plumber has been scheduled.	4	2	10/07/2019
7	2	2	1	Heating unit in the entrance smells like it's burning.	Service rep confirmed the issue to be dust in the heating unit. To be cleaned.	1	0	10/09/2019
8	9	1	2	Kitchen sink does not drain properly.	Problem confirmed. Plumber scheduled.	6	2	11/12/2019
9	12	6	2	New sofa requested.	Open	2	0	

FIGURE 1-8 Sample service request category

Use SQL and the StayWell Student Accommodation database (Figures 1-4 through 1-9 in Module 1) to complete the following exercises. If directed to do so by your instructor, use the information provided with the Module 3 Exercises to print your output or save it to a document.

1. List the owner number, last name, and first name of every property owner.

The screenshot shows a web-based SQL interface. The top navigation bar includes 'Home', 'SQL Workshop', and 'SQL Commands'. The schema is set to 'CORAL'. The query editor contains the following SQL command:

```
SELECT OWNER_NUM, LAST_NAME, FIRST_NAME  
FROM OWNER;
```

Below the query editor, the 'Results' tab is active, displaying a table with the following data:

OWNER_NUM	LAST_NAME	FIRST_NAME
M0100	Moore	Elle-May
PA0101	Patel	Mekalah
AK0102	Aksay	Ceyda
CO0103	Cole	Meredith
K0104	Kowalczyk	Jakob
SI0105	Sinas	Haydon
BU0106	Burke	Ernest
RE0107	Redman	Seth
LO0108	Lopez	Janine
BH0109	Bianche	Nicole

Below the table, it states: 'More than 10 rows available. Increase rows selector to view more rows.' and '10 rows returned in 0.00 seconds'. A 'Download' link is also present. At the bottom, the workspace is identified as 'CORAL User: CORAL' and the language is 'en'.

A yellow sticky note is overlaid on the right side of the interface, containing the text: 'Coral S. Schmidt Montilla #148830'.

3. List the last name and first name of every owner who lives in Seattle.

The screenshot shows the SQL Workshop interface in a web browser. The browser's address bar shows the URL `127.0.0.1:8080/...`. The interface has a top navigation bar with tabs: Home, Application Builder, SQL Workshop (selected), Team Development, and Administration. Below this is a breadcrumb trail: Home > SQL Workshop > SQL Commands. On the right, the schema is identified as CORAL.

The main workspace contains a SQL editor with the following query:

```
SELECT LAST_NAME, FIRST_NAME
FROM OWNER
WHERE CITY = 'Seattle';
```

Below the editor are buttons for Autocommit (checked), Rows (set to 10), Save, and Run. A yellow tooltip is visible over the Run button, displaying the text: Coral S. Schmidt Montilla #148830.

Below the editor is the Results tab, which shows the following data:

LAST_NAME	FIRST_NAME
Aksay	Ceyda
Jones	Amannah

Below the table, it states "2 rows returned in 0.00 seconds" and provides a [Download](#) link.

The footer of the interface shows "Workspace: CORAL User: CORAL" and "Language: en | Copyright".

5. List the property ID and office number for every property whose square footage is equal to or less than 1,400 square feet.

The screenshot shows a web-based SQL Workshop interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', 'Team Development', and 'Administration'. The breadcrumb trail is 'Home > SQL Workshop > SQL Commands'. The schema is 'CORAL'. The interface has a toolbar with 'Autocommit' (checked), 'Rows' (set to 10), 'Save', and 'Run' buttons. The SQL command entered is: `SELECT PROPERTY_ID, OFFICE_NUM
FROM PROPERTY
WHERE SQR_FT <= 1400;`

A yellow sticky note is overlaid on the right side of the SQL editor, containing the text:
Coral S. Schmidt Montilla
#148830

Below the editor, the 'Results' tab is active, displaying a table with the following data:

PROPERTY_ID	OFFICE_NUM
3	1
5	1
9	2
10	1
11	2

Below the table, it states '5 rows returned in 0.01 seconds' and provides a 'Download' link. The footer shows 'Workspace: CORAL User: CORAL' and 'Language: en | Copyright'.

7. List the property ID for every property with two bedrooms that is managed by StayWell-Georgetown.

The screenshot shows the Oracle Application Express interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', 'Team Development', and 'Administration'. The breadcrumb trail is 'Home > SQL Workshop > SQL Commands'. The schema is set to 'CORAL'. The SQL command area contains the following query:

```
SELECT PROPERTY_ID
FROM PROPERTY
WHERE BDRMS = 2
AND OFFICE_NUM = (SELECT OFFICE_NUM FROM OFFICE WHERE OFFICE_NAME = 'StayWell-Georgetown');
```

The query has been executed, and the results are displayed in a table with the following structure:

PROPERTY_ID
11

Below the table, it states '1 rows returned in 0.01 seconds' and provides a 'Download' link. A yellow sticky note is overlaid on the right side of the screen, containing the text:

Coral S. Schmidt Montilla
#148830

The bottom status bar shows 'Workspace: CORAL User: CORAL' and 'Language: en | Copyright'.

9. List the property ID for every property managed by StayWell-Columbia City whose monthly rent is less than \$1,500.

The screenshot shows the Oracle Application Express interface. The browser address bar indicates the URL `127.0.0.1:8080/...`. The page title is "ORACLE Application Express" and the user is logged in as "CORAL". The navigation menu includes "Home", "Application Builder", "SQL Workshop", "Team Development", and "Administration". The breadcrumb trail shows "Home > SQL Workshop > SQL Commands". The schema is set to "CORAL".

The SQL command area contains the following query:

```
SELECT PROPERTY_ID
FROM PROPERTY
WHERE MONTHLY_RENT < 1500
AND OFFICE_NUM = (SELECT OFFICE_NUM FROM OFFICE WHERE OFFICE_NAME = 'StayWell-Columbia City');
```

The query has been executed, and the results are displayed in a table with the following data:

PROPERTY_ID
1
3
5

Below the table, it states "3 rows returned in 0.00 seconds" and provides a "Download" link. A yellow sticky note is overlaid on the right side of the screen, containing the text "Coral S. Schmidt Montilla #148830".

The footer of the page shows "Workspace: CORAL User: CORAL" and "Language: en | Copyright".

11. List the owner number and last name for all owners who live in Nevada (NV), Oregon (OR), or Idaho (ID).

The screenshot shows the Oracle Application Express interface. The browser address bar indicates the URL `127.0.0.1:8080/...`. The page title is "ORACLE Application Express" with a "Welcome CORAL (Logout)" message. The navigation menu includes "Home", "Application Builder", "SQL Workshop", "Team Development", and "Administration". The breadcrumb trail shows "Home > SQL Workshop > SQL Commands". The "Schema" dropdown is set to "CORAL".

In the SQL Commands area, the "Autocommit" checkbox is checked, and the "Rows" limit is set to 10. The SQL query entered is:

```
SELECT OWNER_NUM, LAST_NAME
FROM OWNER
WHERE STATE IN ('NV', 'OR', 'ID');
```

A yellow sticky note is overlaid on the right side of the SQL editor, containing the text:

```
Coral S. Schmidt Montilla
#148830
```

Below the SQL editor, the "Results" tab is selected, displaying the query results in a table:

OWNER_NUM	LAST_NAME
M0100	Moore
SI0105	Sinas
BU0106	Burke

Below the table, it states "3 rows returned in 0.01 seconds" and provides a "Download" link. The footer of the interface shows "Workspace: CORAL User: CORAL" and "Language: en | Copyright".

13. How many three-bedroom properties are managed by each office?

The screenshot shows the Oracle Application Express interface. The top navigation bar includes 'Home', 'Application Builder', 'SQL Workshop', 'Team Development', and 'Administration'. The breadcrumb trail is 'Home > SQL Workshop > SQL Commands'. The schema is set to 'CORAL'. The SQL editor contains the following query:

```
SELECT OFFICE_NUM, COUNT(*) AS THREE_BEDROOM_PROPERTIES
FROM PROPERTY
WHERE BDRMS = 3
GROUP BY OFFICE_NUM;
```

The query has been executed, and the results are displayed in a table with two columns: 'OFFICE_NUM' and 'THREE_BEDROOM_PROPERTIES'. The results show two rows, both with a count of 2.

OFFICE_NUM	THREE_BEDROOM_PROPERTIES
1	2
2	2

Below the table, it states '2 rows returned in 0.00 seconds' with a 'Download' link. A yellow sticky note is overlaid on the right side of the screen, containing the text 'Coral S. Schmidt Montilla #148830'. The bottom status bar shows 'Workspace: CORAL User: CORAL' and 'Language: en | Copyright'.