

MIU-B24C-2

24,000 BTU 4-Way Cassette Indoor Unit

Job Name:	
Reference:	Date:



Item	Unit	Specification
Performance Data		
Cooling Capacity	Btu/hr	23400
Heating Capacity	Btu/hr	25000
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	3/8" (9.52mm)
Gas Side	inch(mm)	5/8" (15.9mm)
Drain Pipe Size	inch(mm)	1" (25mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)

Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3
Indoor Fan Motor Model	-	ZKFN-45-8-1
Indoor Fan Motor Output	W	45
Indoor Fan Motor RLA	A	1
Indoor Fan Motor Speed (Hi/Mi/Lo)	r/min	624 / 568 / 426

Air Flow & Noise Level		
Indoor Air Flow (H/M/L) (CFM)	CFM	765 / 706 / 636 / 547 / 547
Indoor Noise Flow (H/M/L) (dB(A))	dB(A)	49 / 45 / 43 / 34 / 34
Dimension (W×D×H)	inch	32-5/8 × 32-5/8 × 8-1/8
	mm	(830 × 830 × 205)
Package (W×D×H)	inch	35-7/8 × 35-7/8 × 9-7/8
	mm	(910 × 910 × 250)
Net Weight / Gross Weight	lbs	47 / 59
	kg	21.4 / 26.8

Indoor Unit Dimensions

