

MOU-5B36H-2

36,000 BTU Multi-Zone Hyper Heat Outdoor Unit

Job Name:	
Reference:	Date:



EFFICIENCY			
Cooling		Heating	
SEER2	21.5	HSPF2-4	11.3
EER2	12.2	COP	3.9

PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	36000
Min/Max Capacity	9000~42000
Moisture Removal(L/h)	2.7
Standard Operating Range(°F/°C)	-22~122/(-30 ~ 50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	36000
1. @ 47°F Min/Max Capacity	10000~44000
2. @ 17°F Rated(H32)	36600
3. @ 5°F Rated: Capacity / COP(H42)	37000/1.9
3. @ 5°F Max: Capacity	37000
Standard Operating Range(°F/°C)	-22~75/(-30 ~ 24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

OUTDOOR SPECIFICATION		
Compressor Type	TWIN-ROTARY	
Compressor Model	ETPQ420D1UMUA	
Refrigerant	R454B	
Refrigerant Oil Charge(mL)	1460	
Refrigerant Oil	VG75	
Outdoor Air Flow (Max) (CFM)	3037.0	
Outdoor Noise Level (dBA)	65	
Dimension (W×D×H)	inch	38-5/8 × 16-3/8 × 38-7/16
	mm	(980 × 415 × 975)
Package (W×D×H)	inch	45-1/8 × 19-11/16 × 42-9/16
	mm	(1145 × 500 × 1080)
Net/Gross Weight	lbs	212 / 245
	kg	(97 / 111)

ELECTRICAL	
Power Supply	208/230V,60Hz,1Ph
System MCA	37
Connection Wiring	AWG 14-4
System MOCP	40
Compressor RLA	20.5
Outdoor Fan Motor RLA	2.6
Outdoor Fan Motor W	250
Indoor Fan Motor RLA	/
Indoor Fan Motor W	/
System Power Input @ Cooling (W)	2950 (600 ~ 4050)
System Power Input @ Heating (W)	2705 (600 ~ 5000)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING	
Liquid Size	5 × 1/4in (5 × 6.35mm)
Gas Size	3 × 3/8in + 2 × 1/2in (3 × 9.52mm + 2 × 12.7mm)
Max. Piping Length for all rooms(ft/m)	262.4 (80)
Max. Piping Length for one IDU(ft/m)	114.8 (35)
Max. Height Difference of IDU and ODU(ft/m)	49.2 (15)
Refrigerant Pre-charged Amount(oz/kg)	134.04 (3.8)
Refrigerant Precharge Length(ft/m)	24.6 (7.5)x5
Additional Charge of Refrigerant (Φ6.35 (1/4") liquid pipe) ((oz/ft)/(g/m))	0.16 (15)
Additional Charge of Refrigerant (Φ9.52 (3/8") liquid pipe) ((oz/ft)/(g/m))	0.32 (30)
Connection Method	Flared

Outdoor Unit Dimension

