

MOU-6B60G-2

60,000 BTU Multi-Zone Outdoor Unit

Job Name:

Reference:

Date:



EFFICIENCY

Cooling		Heating	
SEER2	18.0	HSPF2-4	9.2
EER2	10	COP	3.7

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	60000
Min/Max Capacity	19000~61000
Moisture Removal(L/h)	3.1
Standard Operating Range(°F/°C)	-13~122/(-25 ~ 50)
Rated Cooling Conditions:	
Indoor: 80°F DB/67°F WB	
Outdoor: 95°F DB/75°F WB	

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	60000
1. @ 47°F Min/Max Capacity	20000~61000
2. @ 17°F Rated(H32)	39000
3. @ 5°F Rated: Capacity / COP(H42)	40000/2.1
3. @ 5°F Max: Capacity	40000
Standard Operating Range(°F/°C)	-13~75/(-25 ~ 24)
1. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 47°F DB/43°F WB	
2. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 17°F DB/15°F WB	
3. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 5°F DB/5°F WB	

OUTDOOR SPECIFICATION

Compressor Type		ROTARY
Compressor Model		KTQ420D1UMU
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1400
Refrigerant Oil		V74
Outdoor Air Flow (Max) (CFM)		4503.0
Outdoor Noise Level (dBA)		64
Dimension (W×D×H)	inch	37-1/2 × 16-3/8 × 52-1/2
	mm	(952 × 415 × 1333)
Package (W×D×H)	inch	43-1/8 × 19-1/2 × 58-5/16
	mm	(1095 × 495 × 1480)
Net/Gross Weight	lbs	238 / 271
	kg	(108 / 123)

ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	40
Connection Wiring	AWG 14-4
System MOCP	45
Compressor RLA	25
Outdoor Fan Motor RLA	2.5
Outdoor Fan Motor W	85
Indoor Fan Motor RLA	/
Indoor Fan Motor W	/
System Power Input @ Cooling (W)	6000 (1200 ~ 6360)
System Power Input @ Heating (W)	4753 (1200 ~ 5200)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Liquid Size	6 × 1/4in (6 × 6.35mm)
Gas Size	4×3/8in + 2×1/2in (4×9.52mm + 2×12.7mm)
Max. Piping Length for all rooms(ft/m)	80 (262.4)
Max. Piping Length for one IDU(ft/m)	35 (114.8)
Max. Height Difference of IDU and ODU(ft/m)	15 (49.2)
Refrigerant Pre-charged Amount(oz/kg)	4.3 (151.68)
Refrigerant Precharge Length(ft/m)	7.5 (24.6)x6
Additional Charge of Refrigerant (Φ6.35 (1/4") liquid pipe) ((oz/ft)/(g/m))	0.16 (15)
Additional Charge of Refrigerant (Φ9.52 (3/8") liquid pipe) ((oz/ft)/(g/m))	0.32 (30)
Connection Method	Flared

Outdoor Unit Dimension

