

MOU-B36L-2&MIU-B36LF-2

36,000 BTU Floor Mounted Indoor/Outdoor Unit

Job Name:	
Reference:	Date:



INDOOR SPECIFICATION		
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)		1224.3 / 1088.9 / 988.8 / 765.2 / 653.3
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)		50.5 / 49 / 44.5 / 37 / 33
Dimension (W×D×H)	inch	65 × 26-5/8 × 9-1/4
	mm	(1650 × 675 × 235)
Package (W×D×H)	inch	67-15/16 × 29-3/4 × 12-9/16
	mm	(1725 × 755 × 318)
Net/Gross Weight	lbs	89 / 105
	kg	(41 / 48)

OUTDOOR SPECIFICATION		
Compressor Type		ROTARY
Compressor Model		KTF310D43UMT
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1000
Refrigerant Oil		VG74
Outdoor Air Flow (Max) (CFM)		2413.3
Outdoor Noise Level (dBA)		64
Dimension (W×D×H)	inch	37-1/4 × 16-3/16 × 31-15/16
	mm	(946 × 410 × 810)
Package (W×D×H)	inch	42-15/16 × 19-11/16 × 34-7/8
	mm	(1090 × 500 × 885)
Net/Gross Weight	lbs	153 / 163
	kg	(70 / 74)

EFFICIENCY			
Cooling		Heating	
SEER2	20.0	HSPF2-4	10.0
EER2	10.1	COP	3.34


PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	36000
Min/Max Capacity	7300~39500
Moisture Removal(L/h)	3.23
Standard Operating Range(°F/°C)	-13~122(-25 ~ 50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	38000
1. @ 47°F Min/Max Capacity	14100~40400
2. @ 17°F Rated	26400
3. @ 5°F Rated: Capacity / COP	26000/2.17
3. @ 5°F Max: Capacity	26000
Standard Operating Range(°F/°C)	-13~75(-25 ~ 24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

ELECTRICAL	
Power Supply	208/230V,60Hz,1Ph
System MCA	33
Connection Wiring	14/4
System MOC	35
Compressor RLA	21.5
Outdoor Fan Motor RLA	0
Outdoor Fan Motor W	120
Indoor Fan Motor RLA	1
Indoor Fan Motor W	90
System Power Input @ Cooling (W)	3529 (560 ~ 4180)
System Power Input @ Heating (W)	3334 (855 ~ 3500)
MCA: Min. circuit amps (A)	MOC: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)


PIPING	
Throttle type(Indoor)	N/A
Throttle type(Outdoor)	EXV+Throttle valve
Liquid Size	3/8in (9.52mm)
Gas Size	3/4in (19mm)
Max. Piping Length(ft/m)	75 (246.00)
Max. Height Difference(ft/m)	30 (98.40)
Max. Pre-charged Length(ft/m)	7.5 (24.6)
Refrigerant Pre-charged Amount(oz/g)	2.60 (91.71)
Additional Refrigerant Charge(oz/ft)/(g/m)	30 (0.32)
Connection Method	Flared

Indoor Unit Dimension



Model	A	B	C	D
18K/24K	42in(1068mm)	26-1/2in(675mm)	9-1/4in(235mm)	38-3/4in(983mm)
36K/48K/60K	65in(1650mm)	26-1/2in(675mm)	9-1/4in(235mm)	61-5/8in(1565mm)

Outdoor Unit Dimension



General Features

GENERAL FEATURES

- 2 Style Installation
- 3D Airflow
- Refrigerant leakage detection sensor
- Humidity sensor
- 88" display tube
- 1~100% fan speed setting
- WiFi capability: through WiFi dongle or wired controller with built-in WiFi
- OTA(by using WiFi dongle)
- 2-pin connector(HA/HB) for programmable wired controller

MULTIPLE CONTROL OPTIONS AVAILABLE:

- Two way communication wired controller:120N(X6)
- Two way communication wired controller with built-in WiFi:120N(X6W)
- Infrared wired controller: 120L
- Wireless remote controller
- Third-Party 24V Thermostat

*24V interface is required.