

MIU-B16F-2

16,000 BTU Floor Mounted Indoor Unit

Job Name:	
Reference:	Date:



Item	Unit	Specification
Performance Data		
Cooling Capacity	Btu/hr	16000
Heating Capacity	Btu/hr	17000
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	1/4" (6.35mm)
Gas Side	inch(mm)	1/2" (12.7mm)
Drain Pipe Size	inch(mm)	5/8" (16mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)

Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3
Indoor Fan Motor Model	-	ZKFP-13-8-104
Indoor Fan Motor Output	W	13
Indoor Fan Motor RLA	A	1
Indoor Fan Motor Speed (Hi/Mi/Lo)	r/min	1100 / 1000 / 900

Air Flow & Noise Level		
Indoor Air Flow (H/M/L) (CFM)	CFM	500 / 441 / 383 / 324 / 206
Indoor Noise Flow (H/M/L) (dB(A))	dB(A)	47 / 44 / 41 / 31 / 26
Dimension (W×D×H)	inch	31-1/4 × 7-7/8 × 24-1/2
	mm	(794 × 200 × 621)
Package (W×D×H)	inch	34 × 11 × 28-1/4
	mm	(865 × 280 × 719)
Net Weight / Gross Weight	lbs	33 / 42
	kg	14.9 / 19.0

Indoor Unit Dimensions

