

MOU-6B48G-2

48,000 BTU Multi-Zone Outdoor Unit

Job Name:

Reference:

Date:



OUTDOOR SPECIFICATION

Compressor Type		ROTARY
Compressor Model		KTQ420D1UMU
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1400
Refrigerant Oil		V74
Outdoor Air Flow (Max) (CFM)		4503.0
Outdoor Noise Level (dBA)		63
Dimension (W×D×H)	inch	37-1/2 × 16-3/8 × 52-1/2
	mm	(952 × 415 × 1333)
Package (W×D×H)	inch	43-1/8 × 19-1/2 × 58-5/16
	mm	(1095 × 495 × 1480)
Net/Gross Weight	lbs	222 / 255
	kg	(101 / 116)

ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	40
Connection Wiring	AWG 14-4
System MOCP	45
Compressor RLA	24
Outdoor Fan Motor RLA	2.5
Outdoor Fan Motor W	85
Indoor Fan Motor RLA	/
Indoor Fan Motor W	/
System Power Input @ Cooling (W)	3740 (800 ~ 6000)
System Power Input @ Heating (W)	3532 (800 ~ 5200)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

EFFICIENCY

Cooling		Heating	
SEER2	20.4	HSPF2-4	10.6
EER2	12	COP	3.9

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	45000
Min/Max Capacity	12000~52000
Moisture Removal(L/h)	2.5
Standard Operating Range(°F/°C)	-13~122/(-25 ~ 50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	47000
1. @ 47°F Min/Max Capacity	13000~53000
2. @ 17°F Rated(H32)	37000
3. @ 5°F Rated: Capacity / COP(H42)	38000/2.1
3. @ 5°F Max: Capacity	38000
Standard Operating Range(°F/°C)	-13~75/(-25 ~ 24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

PIPING

Liquid Size	6 × 1/4in (6 × 6.35mm)
Gas Size	4×3/8in + 2×1/2in (4×9.52mm + 2×12.7mm)
Max. Piping Length for all rooms(ft/m)	262.4 (80)
Max. Piping Length for one IDU(ft/m)	114.8 (35)
Max. Height Difference of IDU and ODU(ft/m)	49.2 (15)
Refrigerant Pre-charged Amount(oz/kg)	148.15 (4.2)
Refrigerant Precharge Length(ft/m)	24.6 (7.5)x6
Additional Charge of Refrigerant (Φ6.35 (1/4") liquid pipe) ((oz/ft)/(g/m))	0.16 (15)
Additional Charge of Refrigerant (Φ9.52 (3/8") liquid pipe) ((oz/ft)/(g/m))	0.32 (30)
Connection Method	Flared

Outdoor Unit Dimension

Technical drawing of the outdoor unit showing front, side, and top views with dimensions in inches and millimeters.

Front View Dimensions:

- Overall Width: 37-1/2 (952)
- Overall Height: 52-1/2 (1333)
- Top Section Width: 41-1/8 (1045)
- Bottom Section Width: 41-3/4 (1060)

Side View Dimensions:

- Overall Height: 16-3/4 (425)
- Top Section Height: 3-3/8 (85)
- Bottom Section Height: 5-7/8 (149)
- Base Width: 3-3/8 (85)
- Base Height: 3 (76.4)
- Base Width (Detail A): 2-7/8 (73.5)

Top View Dimensions:

- Overall Width: 25 (634) A
- Overall Depth: 17-5/8 (448)
- Front Panel Depth: 16-5/16 (415)
- Right Side Depth: 15-15/16 (404)

DETAIL A SCALE 1:2

Ø1/2 (Ø 12)