

MIU-B09CO-2

9,000 BTU 1-Way Cassette Indoor Unit

Job Name:	
Reference:	Date:



Item	Unit	Specification
Performance Data		
Cooling Capacity	Btu/hr	9000
Heating Capacity	Btu/hr	10900
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	1/4" (6.35mm)
Gas Side	inch(mm)	3/8" (9.52mm)
Drain Pipe Size	inch(mm)	1" (25mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)

Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3
Indoor Fan Motor Model	-	ZKFN-30-8-43
Indoor Fan Motor Output	W	30
Indoor Fan Motor RLA	A	0.8
Indoor Fan Motor Speed (Hi/Mi/Lo)	r/min	1104 / 994 / 784

Air Flow & Noise Level		
Indoor Air Flow (H/M/L) (CFM)	CFM	341 / 294 / 259 / 235 / 235
Indoor Noise Flow (H/M/L) (dB(A))	dB(A)	38 / 38 / 36 / 33 / 24
Dimension (W×D×H)	inch	50-1/4 × 13-1/4 × 9
	mm	(1278 × 335 × 228)
Package (W×D×H)	inch	57-5/8 × 22-1/2 × 22-5/8
	mm	(1463 × 571 × 575)
Net Weight / Gross Weight	lbs	45 / 82
	kg	20.5 / 37.4

Indoor Unit Dimensions

