

MIU-B18D-2

18,000 BTU Ducted Indoor Unit

Job Name:

Reference:

Date:




Item	Unit	Specification
Performance Data		
Cooling Capacity	Btu/hr	17500
Heating Capacity	Btu/hr	19500
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	1/4" (6.35mm)
Gas Side	inch(mm)	1/2" (12.7mm)
Drain Pipe Size	inch(mm)	1" (25mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)

Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3
Indoor Fan Motor Model	-	ZKFN-165-10-1L
Indoor Fan Motor Output	W	165
Indoor Fan Motor RLA	A	1.8
Indoor Fan Motor Speed (Hi/Mi/Lo)	r/min	820 / 760 / 700

Air Flow & Noise Level		
Indoor Air Flow (H/M/L) (CFM)	CFM	706 / 618 / 530 / 441 / 441
Indoor Noise Flow (H/M/L) (dB(A))	dB(A)	36 / 36 / 34 / 32 / 28
Dimension (W×D×H)	inch	39-3/8 × 29-1/2 × 9-5/8
	mm	(1000 × 750 × 245)
Package (W×D×H)	inch	48-1/4 × 33-7/8 × 12
	mm	(1225 × 860 × 304)
Net Weight / Gross Weight	lbs	80 / 91
	kg	36.2 / 41.4

Indoor Unit Dimensions



inch(mm)				
MODEL	A	B	C	D
9~12K	27-1/2(700)	9-5/8(245)	29-1/2(750)	31-1/4(795)
18K~24K	39-3/8(1000)	9-5/8(245)	29-1/2(750)	31-1/4(795)
36K~48K	47-1/8(1200)	11-7/8(300)	29-1/2(750)	31-1/4(795)
60K	55-1/8(1400)	15(380)	31-1/2(800)	33-1/4(845)