

MAC-B4821

48,000 BTU A Coil Indoor Unit

Job Name:	
Reference:	Date:



Item	Unit	Specification
Performance Data		
Rated Capacity	Btu/hr	47000
Min/Max Capacity	Btu/hr	15,500~47,000
Moisture Removal	L/h	4
Standard Operating Range	°F/°C	-13~122 (-25 ~ 50)
Throttle type	-	TXV
Liquid Size	inch(mm)	3/8" (9.52mm)
Gas Size	inch(mm)	3/4" (19mm)
Max. Piping Length	ft/m	246 (75)
Max. Height Difference(ft/m)	ft/m	98.4 (30)
Max. Pre-charged Length(ft/m)	ft/m	25 (7.5)
Refrigerant Pre-charged Amount(oz/kg)	oz/kg	134 (3.8)
Additional Charge of Refrigerant((oz/ft)/(g/m))	oz/ft/(g/m)	0.7 (65)
Connection Method	-	Flared

Electrical		
Power Supply	V, Ph, Hz	24V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	V	/
Indoor MOP	-	/
Communication Wiring	-	AWG 20-2
Indoor Fan Motor RLA	A	/
Indoor Fan Motor W	W	/

Air Flow & Noise Level		
Dimension (W×D×H)	inch	21-5/8 x 21-1/2 x 27-3/4
	mm	549 x 546 x 706
Package (W×D×H)	inch	31-1/8 x 25 x 25-5/8
	mm	790 x 635 x 650
Net Weight / Gross Weight	lbs	97 / 115
	kg	43.9 / 52.2

Indoor Unit Dimensions

Unit: inch(mm)

