

MIU-B12C-2

12,000 BTU 4-Way Cassette Indoor Unit

Job Name:

Reference:

Date:



Item	Unit	Specification
Performance Data		
Cooling Capacity	Btu/hr	12000
Heating Capacity	Btu/hr	12000
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	1/4" (6.35mm)
Gas Side	inch(mm)	3/8" (9.52mm)
Drain Pipe Size	inch(mm)	1" (25mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)

Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3
Indoor Fan Motor Model	-	ZKFN-45-8-2
Indoor Fan Motor Output	W	45
Indoor Fan Motor RLA	A	0.9
Indoor Fan Motor Speed (Hi/Mi/Lo)	r/min	700 / 600 / 400

Air Flow & Noise Level		
Indoor Air Flow (H/M/L) (CFM)	CFM	418 / 365 / 306 / 194 / 147
Indoor Noise Flow (H/M/L) (dB(A))	dB(A)	46 / 44 / 41 / 28 / 26
Dimension (W×D×H)	inch	22-1/2 × 22-1/2 × 9-5/8
	mm	(570 × 570 × 245)
Package (W×D×H)	inch	28-1/8 × 25-1/4 × 11-5/8
	mm	(715 × 640 × 295)
Net Weight / Gross Weight	lbs	35 / 42
	kg	16 / 19

Indoor Unit Dimensions

Liquid side Gas side

Body

