

MOU-6B55H-2

55,000 BTU Multi-Zone Hyper Heat Outdoor Unit

Job Name:

Reference:

Date:



EFFICIENCY

Cooling		Heating	
SEER2	21.4	HSPF2-4	10.6
EER2	12	COP	3.4

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	51000
Min/Max Capacity	19000~58000
Moisture Removal(L/h)	4
Standard Operating Range(°F/°C)	-22~122/(-30 ~ 50)
Rated Cooling Conditions:	
Indoor: 80°F DB/67°F WB	
Outdoor: 95°F DB/75°F WB	

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	55000
1. @ 47°F Min/Max Capacity	20000~56000
2. @ 17°F Rated(H32)	45000
3. @ 5°F Rated: Capacity / COP(H42)	48000/2
3. @ 5°F Max: Capacity	48000
Standard Operating Range(°F/°C)	-22~75/(-30 ~ 24)
1. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 47°F DB/43°F WB	
2. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 17°F DB/15°F WB	
3. Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 5°F DB/5°F WB	

OUTDOOR SPECIFICATION

Compressor Type		TWIN-ROTARY
Compressor Model		ETPQ440D1UMUB
Refrigerant		R454B
Refrigerant Oil Charge(mL)		1300
Refrigerant Oil		VG75
Outdoor Air Flow (Max) (CFM)		4503.0
Outdoor Noise Level (dBA)		65
Dimension (W×D×H)	inch	37-1/2 × 16-3/8 × 52-1/2
	mm	(952 × 415 × 1333)
Package (W×D×H)	inch	43-1/8 × 19-1/2 × 58-5/16
	mm	(1095 × 495 × 1480)
Net/Gross Weight	lbs	247 / 277
	kg	(112 / 126)

ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	43
Connection Wiring	AWG 14-4
System MOCP	45
Compressor RLA	28
Outdoor Fan Motor RLA	2.5
Outdoor Fan Motor W	85
Indoor Fan Motor RLA	/
Indoor Fan Motor W	/
System Power Input @ Cooling (W)	4250 (1200 ~ 5600)
System Power Input @ Heating (W)	4741 (1200 ~ 5400)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Liquid Size	6 × 1/4in (6 × 6.35mm)
Gas Size	4×3/8in + 2×1/2in (4×9.52mm + 2×12.7mm)
Max. Piping Length for all rooms(ft/m)	262.4 (80)
Max. Piping Length for one IDU(ft/m)	114.8 (35)
Max. Height Difference of IDU and ODU(ft/m)	49.2 (15)
Refrigerant Pre-charged Amount(oz/kg)	151.68 (4.3)
Refrigerant Precharge Length(ft/m)	24.6 (7.5)x6
Additional Charge of Refrigerant (Φ6.35 (1/4") liquid pipe) ((oz/ft)/(g/m))	0.16 (15)
Additional Charge of Refrigerant (Φ9.52 (3/8") liquid pipe) ((oz/ft)/(g/m))	0.32 (30)
Connection Method	Flared

Outdoor Unit Dimension

