



## Github URL


### W04-P1: add 3 images of my meals to menu array



## W04-P2: show all data in array menu into html (section-center)



## W04-P3: show all filter buttons into html (section-center)including (all, breakfast, lunch, dinner, shakes)



```
JS app_xx.js > displayMenuItems > displayMenu > menu.map() callback
1 > const menu = [ ...
57 ];
58
59 > const btn = [ ...
68 ];
69
70
71 const sectionCenter = document.querySelector('.section-center')
72 const btnContainer = document.querySelector('btn-container')
73
74 const displayMenuItems = (menu) => {
75   let displayMenu = menu.map( (item) => {
76     return `
77     <article class="menu-item">
78       
80         <header>
81           <h4>${item.title}</h4>
82           <h4 class="price">${item.price}</h4>
83         </header>
84         <p class="item-text">
85           ${item.desc}
86         </p>
87       </div>
88     </article>`
89   });
90   console.log('displayMenu', displayMenu);
91   displayMenu = displayMenu.join('');
92   console.log('displayMenu after join', displayMenu);
93   sectionCenter.innerHTML = displayMenu;
94 }
95
96
97 window.addEventListener('DOMContentLoaded', () => {
98   displayMenuItems(menu);
99 });
100
101
```

```
JS app_xx.js M > displayMenuItems > displayMenu > menu.map() callback
1 const menu = [
2 {
3   id: 1,
4   title: "buttermilk pancakes",
5   category: "breakfast",
6   price: 15.59,
7   img: './images/item-1.jpeg',
8   remote_img: '',
9   desc: 'Lorem ipsum dolor sit amet consectetur, adipisc
10 },
11 ]
```

```
index.html M > JS app_xx.js M
34 </div>
35
36 <!-- menu items -->
37 <div class="section-center">
38   single item
39
40 <!-- <article class="menu-item">
41   
43     <header>
44       <h4>buttermilk pancakes</h4>
45       <h4 class="price">$15.99</h4>
46     </header>
47     <p class="item-text">
48       I'm baby woke mlkshk wolf bitters live-edge blue bo
49       freegan copper mug whatever cold-pressed
50     </p>
51   </div>
52 </article> -->
53 </div>
54 <section>
55   -- javascript -->
56   <script src="app_xx.js"></script>
57 </div>
```

# W04-P3: show all filter buttons into html (section-center)including (all, breakfast, lunch, dinner, shakes)

Our Menu - 207410290


All

Breakfast

Lunch

Shakes


Dinner



Buttermilk Pancakes

15.59


Lorem ipsum dolor sit amet consectetur, adipisicing elit. Sapiente dolore ullam ipsam suscipit!



Dinner Double

25.69

Lorem ipsum dolor sit amet consectetur, adipisicing elit. Sapiente dolore ullam ipsam suscipit!



Elements

Console

Sources

Network

Filter

Default levels

1 Issue: 1

displayButtons before join

app\_xx.js:97

(5) [ ' <button type="button" class="filter-btn" data-id="all">\n all\n </button>', ' <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button>', ' <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button>', ' <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button>', ' <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>' ]

0: " <button type="button" class="filter-btn" data-id="all">\n all\n </button>"

1: " <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button>"

2: " <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button>"

3: " <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button>"

4: " <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>"

length: 5

[[Prototype]]: Array(0)

displayMenuButtons after join

app\_xx.js:99

<button type="button" class="filter-btn" data-id="all">\n all\n </button> <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button> <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button> <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button> <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>

Uncaught TypeError: Cannot set properties of null (setting 'innerHTML')

app\_xx.js:100

at displayMenuButtons (app\_xx.js:100:26)

at app\_xx.js:105:3

```
const categories = ['all', 'breakfast', 'lunch', 'dinner', 'shakes'];
const btnContainer = document.querySelector('btn-container');
const displayMenuButtons = () => {
  let menuButtons = categories.map((category) => {
    return `<button type="button" class="filter-btn" data-id="${category}">
      ${category}
    </button>`;
  })
  console.log('displayButtons before join', menuButtons);
  menuButtons = menuButtons.join('');
  console.log('displayMenuButtons after join\n', menuButtons);
  btnContainer.innerHTML = menuButtons;
}

window.addEventListener('DOMContentLoaded', () => {
  displayMenuItems(menu);
  displayMenuButtons();
});
```

# W03-P4: implement prev button and show the sequence in console.log

Our Menu - 207410290


All

Breakfast

Lunch

Shakes


Dinner



Buttermilk Pancakes

15.59


Lorem ipsum dolor sit amet consectetur, adipisicing elit. Sapiente dolore ullam ipsam suscipit!



Dinner Double

25.69

Lorem ipsum dolor sit amet consectetur, adipisicing elit. Sapiente dolore ullam ipsam suscipit!



Elements

Console

Sources

Network

Filter

Default levels

1 Issue: 1

displayButtons before join

app\_xx.js:97

(5) [ ' <button type="button" class="filter-btn" data-id="all">\n all\n </button>', ' <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button>', ' <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button>', ' <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button>', ' <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>' ]

0: " <button type="button" class="filter-btn" data-id="all">\n all\n </button>"

1: " <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button>"

2: " <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button>"

3: " <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button>"

4: " <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>"

length: 5

[[Prototype]]: Array(0)

displayMenuButtons after join

app\_xx.js:99

<button type="button" class="filter-btn" data-id="all">\n all\n </button> <button type="button" class="filter-btn" data-id="breakfast">\n breakfast\n </button> <button type="button" class="filter-btn" data-id="lunch">\n lunch\n </button> <button type="button" class="filter-btn" data-id="dinner">\n dinner\n </button> <button type="button" class="filter-btn" data-id="shakes">\n shakes\n </button>

Uncaught TypeError: Cannot set properties of null (setting 'innerHTML')

app\_xx.js:100

at displayMenuButtons (app\_xx.js:100:26)

at app\_xx.js:105:3

app\_xx.js - 1112-1N-js-demo-207410290 - Visual Studio Code

w04\_90.md JS app\_xx.js M X index.html

```
JS app_xx.js > ...
76     </p>
77     </div>
78   </article>`
79
80   });
81   // console.log('displayMenu', displayMenu);
82   displayMenu = displayMenu.join('');
83   // console.log('displayMenu after join', displayMenu);
84   sectionCenter.innerHTML = displayMenu;
85 }
86
87
88
89 // const categories = ['all', 'breakfast', 'lunch', 'dinner',
90 // 'shakes'];
91 const categories = ['all', ...new Set(menu.map((item) => item.
category))];
92
93 const btnContainer = document.querySelector('btn-container');
94 const displayMenuButtons = () => {
95   let menuButtons = categories.map((category) => {
96     return `<button type="button" class="filter-btn" data-id="$
{category}">
97     ${category}
98   </button>`;
99   })
100   console.log('displayButtons before join', menuButtons);
101   menuButtons = menuButtons.join('');
102   console.log('displayMenuButtons after join\n', menuButtons);
103   btnContainer.innerHTML = menuButtons;
104 }
105 window.addEventListener('DOMContentLoaded', () => {
106   displayMenuItems(menu);
107   displayMenuButtons();
108 });
109
110
111
112
```

啟用 Windows  
移至 [設定] 以啟用 Windows。

main\* 0 0 Spaces: 2 UTF-8 CRLF {} JavaScript Port: 5500 Prettier

16°C 晴時多雲 上午 12:00 2023/3/11

```
git log --pretty=format:"%h%x09%an%x09%ad%x09%s" --after="2023-3-08"
```

```
$ git log --pretty=format:"%h%x09%an%x09%ad%x09%s" --after="2023-3-08"
a0adea6 Sky001 Fri Mar 10 23:52:08 2023 +0800 W04-P3: show all filter buttons into html (section-center)including (all, breakfast, lunch, dinner, shakes)
c4f0a10 Sky001 Thu Mar 9 21:23:51 2023 +0800 upload files
80bf8ad Sky001 Thu Mar 9 20:25:41 2023 +0800 W04-P2: show all data in array menu into html (section-center)
86a4d3a Sky001 Thu Mar 9 19:15:14 2023 +0800 W04-P1: add 3 images of my meals to menu array
```