

DJI Matrice M600 + GS Pro

System Architecture · 7-Layer Model

◀ System Components ▶

Interface Protocol

LAYER 1 — GROUND CONTROL STATION

- DJI Remote Controller
- Mobile Device (iPad / Tablet)
- GS Pro Application

Protocol: 802.11 Wi-Fi / USB

LAYER 2 — COMMUNICATION LINK

- Lightbridge 2 Data Link
- Uplink: Commands, Waypoints
- Downlink: Telemetry, Video Feed

Protocol: 2.4 / 5.8 GHz RF · Proprietary DJI · MAVLink-like

LAYER 3 — FLIGHT CONTROLLER

A3 Pro Flight Controller

IMU (Triple Redundant)

GPS Module (Dual)

Barometer & Compass

Protocol: CAN Bus · I²C · UART · SPI

LAYER 4 — POWER SYSTEM

- 6× TB47S / TB48S Battery Packs
- Power Management Unit (PMU)
- Electronic Speed Controllers (ESC)

Protocol: SMBus · PWM

LAYER 5 — PROPULSION SYSTEM

- 6× DJI 6010 Brushless Motors
- 6× Bi-directional ESCs
- 6× 21" Carbon Fibre Propellers

Protocol: PWM Signal (50 Hz / Digital)

LAYER 6 — PAYLOAD INTERFACE

- Ronin-MX Gimbal Stabiliser
- Zenmuse X5 / X7 Camera
- Expansion / SDK Port

Protocol: UART · CAN · OSDK / SDK API

LAYER 7 — POSITIONING SYSTEM

- GPS L1/L2 (Primary)
- GLONASS (Secondary)
- Triple-redundant Compass

Protocol: NMEA 0183 · UBX Binary