Step-by-step: Run the starter

1. Download and unzip the package

Download the package:

CG Assignment 1 — Babylon.js 2D Rasterisation

Unzip it somewhere convenient, for example:

```
Documents/
└── CG_Assignment1_BabylonJS_2D_Rasterisation/
    ├── starter/
    └── docs/
```

2. Open a terminal

- Open Terminal (macOS) or PowerShell (Windows).
- Type `cd` followed by the path to the `starter` folder.

For example, if it is in Documents:

```
cd ~/Documents/CG_Assignment1_BabylonJS_2D_Rasterisation/starter
```

You can verify that you are in the correct directory with:

```
ls
```

You should see:

```
index.html
src
```

and:

```
ls src
```

should show:

```
main.js
rasterization.js
style.css
```

3. Start a local web server

The easiest option is Python.

Check that Python is installed:

```
 python --version (Windows)
 python3 --version (macOS)
```

You should get something similar to:

```
Python 3.x.x
```

Then run:

```
python -m http.server 8000 (Windows)
python3 -m http.server 8000 (macOS)
```

You should see something like:

```
Serving HTTP on 0.0.0.0 port 8000 ...
```

Leave this terminal window open and running in the background (minimizing it is fine)

---

4. Open the application

Open Chrome, Safari, Firefox, or another browser and go to:


http://localhost:8000

You should see the Babylon.js application.

---

5. The Result

You should see an empty drawing area with the toolbar/buttons at the top, as in the screenshot below. Once you complete the assignment code, running it should render the house drawing on screen.



Note: Browsers can cache your JS files, so changes may not always appear on a normal refresh. Use a hard refresh (Ctrl+Shift+R / Cmd+Shift+R) or open the page in a new private/incognito window to guarantee you're seeing your latest code.