

# CS172: COMPUTER SYSTEMS II

## Lecture 20

# Functions

- *classifying*


James Power



# Domain, codomain and image: definition


# Domain, codomain and image: definition

Suppose we are given some sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ .



## Domain, codomain and image: definition

Suppose we are given some sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ .




- The set  $X$  is called the **domain** of the function  $f$

Image from [Wikipedia](#)

## Domain, codomain and image: definition

Suppose we are given some sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ .




- The set  $X$  is called the **domain** of the function  $f$
- The set  $Y$  is called the **codomain** (or range) of the function  $f$

Image from [Wikipedia](#)

## Domain, codomain and image: definition

Suppose we are given some sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ .



- The set  $X$  is called the **domain** of the function  $f$
- The set  $Y$  is called the **codomain** (or range) of the function  $f$
- The subset of the codomain  $Y$  containing elements mapped-to by  $f$  is called the **image** of the function  $f$

Image from [Wikipedia](#)

# Domain, codomain and image: example

For example, consider the two functions  $sq, db \subseteq \mathbb{Z} \times \mathbb{Z}$  defined as

- $sq \triangleq (\lambda x \in \mathbb{Z} . x^2)$
- $db \triangleq (\lambda x \in \mathbb{Z} . 2 * x)$

# Domain, codomain and image: example

For example, consider the two functions  $sq, db \subseteq \mathbb{Z} \times \mathbb{Z}$  defined as

- $sq \triangleq (\lambda x \in \mathbb{Z} . x^2)$
- $db \triangleq (\lambda x \in \mathbb{Z} . 2 * x)$

In each case the domain and codomain is the set  $\mathbb{Z}$ , but

- The image of  $sq$  is the set  $\{n \in \mathbb{N} \mid n^2\}$   
 $= \{0, 1, 4, 9, 16, \dots\}$
- The image of  $db$  is the set  $\{n \in \mathbb{Z} \mid 2 * n\}$   
 $= \{\dots, -6, -4, -2, 0, 2, 4, 6, \dots\}$



# Injective and Surjective Functions

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$

Thus the *inverse* of an injective function is always a function (from the image to the domain).

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$

- **surjective** (onto) if each element in the codomain is mapped to by *at least one* element in the domain; that is, if

$$(\forall z \cdot z \in Y \rightarrow (\exists x \cdot x \in X \wedge f(x) = z))$$

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$

- **surjective** (onto) if each element in the codomain is mapped to by *at least one* element in the domain; that is, if

$$(\forall z \cdot z \in Y \rightarrow (\exists x \cdot x \in X \wedge f(x) = z))$$

For a surjective function the image is the *whole* codomain.

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$

- **surjective** (onto) if each element in the codomain is mapped to by *at least one* element in the domain; that is, if

$$(\forall z \cdot z \in Y \rightarrow (\exists x \cdot x \in X \wedge f(x) = z))$$

- **bijective** if it is both injective and surjective.

# Injective and Surjective Functions

For any sets  $X$  and  $Y$  and a function  $f \subseteq X \times Y$ , we say that the function  $f$  is:

- **injective** (one-to-one) if each element in the image is mapped to by *just one* element in the domain; that is, if

$$(\forall x, y \cdot (x \in X \wedge y \in X \wedge f(x) = f(y)) \rightarrow x = y)$$


- **surjective** (onto) if each element in the codomain is mapped to by *at least one* element in the domain; that is, if

$$(\forall z \cdot z \in Y \rightarrow (\exists x \cdot x \in X \wedge f(x) = z))$$

- **bijective** if it is both injective and surjective.

Thus if there is a bijection between two sets, then those sets have the same number of elements.

# Example: Surjective but not injective






Injective? ✗

Surjective? ✓




## Example: Injective but not surjective




Injective?   
Surjective? 

# Example: Neither injective nor surjective



Injective? **×**  
Surjective? **×**

# Example: Both injective and surjective (so, bijective)



Injective?



Surjective?



# Injective and Surjective: Java example 1

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = new Person("Harry");
```

# Injective and Surjective: Java example 1

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = new Person("Harry");
```

- There is a bijective function from the variable names  $\{a, b, c\}$  to the three objects on the heap.

## Injective and Surjective: Java example 2

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = b;
```

## Injective and Surjective: Java example 2

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = b;
```

- There is now a surjective (but not injective) function from the variable names  $\{a, b, c\}$  to the *two* objects on the heap.

## Injective and Surjective: Java example 3

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = new Person("Harry");  
c = new Person("Fred");
```



## Injective and Surjective: Java example 3

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = new Person("Harry");  
c = new Person("Fred");
```

- There is an injective (but not surjective) function from the variable names  $\{a, b, c\}$  to the *four* objects on the heap.

## Injective and Surjective: Java example 3

Consider the function from the variable names  $\{a, b, c\}$  to the objects on the heap created by the following Java code:

```
Person a = new Person("Tom");  
Person b = new Person("Dick");  
Person c = new Person("Harry");  
c = new Person("Fred");
```

- There is an injective (but not surjective) function from the variable names  $\{a, b, c\}$  to the *four* objects on the heap.
- Calling the *garbage collector* would make this function surjective again.

# Injective: Hash Tables Example

- **Hash tables** are a data structure used to map keys to values.
- Like an array, except the index (key) can be of any type.  
Sometimes called an *associative array* (or, if the keys are strings, a *dictionary*).
- To implement this, you need a **hash function** that maps the key type to an integer.




Image from [Wikipedia](#)

# Injective: Hash Tables Example

- **Hash tables** are a data structure used to map keys to values.
- Like an array, except the index (key) can be of any type.  
Sometimes called an *associative array* (or, if the keys are strings, a *dictionary*).
- To implement this, you need a **hash function** that maps the key type to an integer.




Image from [Wikipedia](#)

- Ideally, the hash function would be *injective*.
- When it's not injective, you get collisions.

# Total vs. Partial Functions

# Total vs. Partial Functions

- Typically in mathematics we assume that a function maps *all* the elements in the domain to an element in the codomain.

# Total vs. Partial Functions

- Typically in mathematics we assume that a function maps *all* the elements in the domain to an element in the codomain.
- In certain cases we may want to allow *some* elements not to be mapped: this is known as a **partial function**. For example:

$$\textit{reciprocal} \triangleq (\lambda a \in \mathbb{Z} \mid a \neq 0 \cdot 1/a)$$

- We can always make a partial function into a **total function** by restricting the domain to just those elements that are mapped from.

$$(\lambda a \in (\mathbb{Z} \setminus \{0\})) \cdot 1/a)$$

# Total vs. Partial Functions

- Typically in mathematics we assume that a function maps *all* the elements in the domain to an element in the codomain.
- In certain cases we may want to allow *some* elements not to be mapped: this is known as a **partial function**. For example:

$$\textit{reciprocal} \triangleq (\lambda a \in \mathbb{Z} \mid a \neq 0 \cdot 1/a)$$

- We can always make a partial function into a **total function** by restricting the domain to just those elements that are mapped from.

$$(\lambda a \in (\mathbb{Z} \setminus \{0\}) \cdot 1/a)$$

- assuming we have some way of deciding which elements of the domain it won't work for...



# Partial functions in CS

- *Partial* functions are interesting in Computer Science where we might have to allow for a method to be non-halting (e.g. because of an infinite loop).

```
int fact(int n) {  
    if (n==0) return 1;  
    else return n * fact(n-1);  
}
```

- What is `fact(-1)` ?

# Partial functions in CS

- *Partial* functions are interesting in Computer Science where we might have to allow for a method to be non-halting (e.g. because of an infinite loop).

```
int fact(int n) {  
    if (n==0) return 1;  
    else return n * fact(n-1);  
}
```

- What is  $\text{fact}(-1)$  ?



Theorem: It is not possible to write a code-analyser that will detect in advance whether *any* function is total or partial (i.e. whether it will halt or not).

- *Halting Problem*, Alan Turing, 1936

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

There are 16 possible *subsets* of this set,  
thus 16 possible relations whose domain and codomain are the set  $\{0, 1\}$ .

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

There are 16 possible *subsets* of this set,  
thus 16 possible relations whose domain and codomain are the set  $\{0, 1\}$ .

- 1 relation of size 0
- 4 relations of size 1
- 6 relations of size 2
- 4 relations of size 3
- 1 relation of size 4

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

There are 16 possible *subsets* of this set,  
thus 16 possible relations whose domain and codomain are the set  $\{0, 1\}$ .

- 1 relation of size 0 - is a (partial) function
- 4 relations of size 1 - all are (partial) functions
- 6 relations of size 2
- 4 relations of size 3
- 1 relation of size 4

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

There are 16 possible *subsets* of this set,  
thus 16 possible relations whose domain and codomain are the set  $\{0, 1\}$ .

- 1 relation of size 0 - is a (partial) function
- 4 relations of size 1 - all are (partial) functions
- 6 relations of size 2
- 4 relations of size 3 - none are functions
- 1 relation of size 4 - not a function

## Example: classifying functions

Consider the set

$$\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$$

There are 16 possible *subsets* of this set,  
thus 16 possible relations whose domain and codomain are the set  $\{0, 1\}$ .

- 1 relation of size 0 - is a (partial) function
- 4 relations of size 1 - all are (partial) functions
- 6 relations of size 2 - only 4 are functions
- 4 relations of size 3 - none are functions
- 1 relation of size 4 - not a function



## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$				
$\{(0, 0)\}$				
$\{(0, 1)\}$				
$\{(1, 0)\}$				
$\{(1, 1)\}$				
$\{(0, 0), (1, 0)\}$				
$\{(0, 0), (1, 1)\}$				
$\{(0, 1), (1, 0)\}$				
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$				
$\{(0, 1)\}$				
$\{(1, 0)\}$				
$\{(1, 1)\}$				
$\{(0, 0), (1, 0)\}$				
$\{(0, 0), (1, 1)\}$				
$\{(0, 1), (1, 0)\}$				
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$	✗	✓	✗	✗
$\{(0, 1)\}$	✗	✓	✗	✗
$\{(1, 0)\}$	✗	✓	✗	✗
$\{(1, 1)\}$	✗	✓	✗	✗
$\{(0, 0), (1, 0)\}$				
$\{(0, 0), (1, 1)\}$				
$\{(0, 1), (1, 0)\}$				
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$	✗	✓	✗	✗
$\{(0, 1)\}$	✗	✓	✗	✗
$\{(1, 0)\}$	✗	✓	✗	✗
$\{(1, 1)\}$	✗	✓	✗	✗
$\{(0, 0), (1, 0)\}$	✓	✗	✗	✗
$\{(0, 0), (1, 1)\}$				
$\{(0, 1), (1, 0)\}$				
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$	✗	✓	✗	✗
$\{(0, 1)\}$	✗	✓	✗	✗
$\{(1, 0)\}$	✗	✓	✗	✗
$\{(1, 1)\}$	✗	✓	✗	✗
$\{(0, 0), (1, 0)\}$	✓	✗	✗	✗
$\{(0, 0), (1, 1)\}$	✓	✓	✓	✓
$\{(0, 1), (1, 0)\}$				
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$	✗	✓	✗	✗
$\{(0, 1)\}$	✗	✓	✗	✗
$\{(1, 0)\}$	✗	✓	✗	✗
$\{(1, 1)\}$	✗	✓	✗	✗
$\{(0, 0), (1, 0)\}$	✓	✗	✗	✗
$\{(0, 0), (1, 1)\}$	✓	✓	✓	✓
$\{(0, 1), (1, 0)\}$	✓	✓	✓	✓
$\{(0, 1), (1, 1)\}$				

## Example: classifying functions (continued)

Consider the set  $\{0, 1\} \times \{0, 1\} = \{(0, 0), (0, 1), (1, 0), (1, 1)\}$ .

There are 9 *functions* whose domain and codomain are the set  $\{0, 1\}$ .

Function	Total	Injective	Surjective	Bijjective
$\{\}$	✗	✓	✗	✗
$\{(0, 0)\}$	✗	✓	✗	✗
$\{(0, 1)\}$	✗	✓	✗	✗
$\{(1, 0)\}$	✗	✓	✗	✗
$\{(1, 1)\}$	✗	✓	✗	✗
$\{(0, 0), (1, 0)\}$	✓	✗	✗	✗
$\{(0, 0), (1, 1)\}$	✓	✓	✓	✓
$\{(0, 1), (1, 0)\}$	✓	✓	✓	✓
$\{(0, 1), (1, 1)\}$	✓	✗	✗	✗

# Sets, bags, and sequences

- A set is a collection of objects.

We can only ask: is  $x \in S$ ?

We cannot ask:

- *how many times* does  $x$  occur in  $S$ ?
- *where* does  $x$  occur in  $S$ ?



# Sets, bags, and sequences

- A set is a collection of objects.

We can only ask: is  $x \in S$ ?

We cannot ask:

- *how many times* does  $x$  occur in  $S$ ?
  - *where* does  $x$  occur in  $S$ ?
- 
- A **bag** is like a set, but we also remember *how many times* an object occurs.
  - A **sequence** is like a set, but we also remember *where* an object occurs.

## Bags: basic definition

- A **bag** (or **multiset**) is like a set except that members are allowed to occur many times.

## Bags: basic definition

- A **bag** (or **multiset**) is like a set except that members are allowed to occur many times.
- The number of times an element occurs in a bag is called the **multiplicity** of that element.
- We typically use a special kind of bracket to indicate that we care about multiplicity;

For example:  $\llbracket a, a, b, b, b, c \rrbracket$  is the bag where  $a$  occurs twice,  $b$  occurs thrice and  $c$  occurs once.

# Bags: basic definition

- A **bag** (or **multiset**) is like a set except that members are allowed to occur many times.
- The number of times an element occurs in a bag is called the **multiplicity** of that element.
- We typically use a special kind of bracket to indicate that we care about multiplicity;

For example:  $\llbracket a, a, b, b, b, c \rrbracket$  is the bag where  $a$  occurs twice,  $b$  occurs thrice and  $c$  occurs once.

- Notes:
  - The notation  $\llbracket \cdot \cdot \cdot \rrbracket$  is not very standard.
  - The *order* of elements in a bag doesn't matter.

## Bags: set-based definition

- A bag is really a special kind of **function**.
- For any set  $S$ , a “bag of  $S$ ” is a function from  $S$  to  $\mathbb{N}$ , giving the multiplicity of each element.

## Bags: set-based definition

- A bag is really a special kind of **function**.
- For any set  $S$ , a “bag of  $S$ ” is a function from  $S$  to  $\mathbb{N}$ , giving the multiplicity of each element.
- Thus  $\llbracket a, a, b, b, b, c \rrbracket$  is just a shorthand for  $\{(a, 2), (b, 3), (c, 1)\}$

## Bags: set-based definition

- A bag is really a special kind of **function**.
- For any set  $S$ , a “bag of  $S$ ” is a function from  $S$  to  $\mathbb{N}$ , giving the multiplicity of each element.
- Thus  $\llbracket a, a, b, b, b, c \rrbracket$  is just a shorthand for  $\{(a, 2), (b, 3), (c, 1)\}$
- For example, given some set  $F \triangleq \{apple, orange, pear\}$ , given the bag

$$myShopping \triangleq \llbracket apple, apple, pear, pear, pear \rrbracket$$

# Bags: set-based definition

- A bag is really a special kind of **function**.
- For any set  $S$ , a “bag of  $S$ ” is a function from  $S$  to  $\mathbb{N}$ , giving the multiplicity of each element.
- Thus  $\llbracket a, a, b, b, b, c \rrbracket$  is just a shorthand for  $\{(a, 2), (b, 3), (c, 1)\}$
- For example, given some set  $F \triangleq \{apple, orange, pear\}$ , given the bag

$$myShopping \triangleq \llbracket apple, apple, pear, pear, pear \rrbracket$$

we can say

$$myShopping = \{(apple, 2), (orange, 0), (pear, 3)\}$$



## Operations on Bags (inherited)

- Since bags are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.

## Operations on Bags (inherited)

- Since bags are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\llbracket a, a, b, b, b, c \rrbracket \cup \llbracket a, b, b, c, c \rrbracket$$

## Operations on Bags (inherited)

- Since bags are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned} & \llbracket a, a, b, b, b, c \rrbracket \cup \llbracket a, b, b, c, c \rrbracket \\ &= \{(a, 2), (b, 3), (c, 1)\} \cup \{(a, 1), (b, 2), (c, 2)\} \end{aligned}$$

# Operations on Bags (inherited)

- Since bags are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned}
 & \llbracket a, a, b, b, b, c \rrbracket \cup \llbracket a, b, b, c, c \rrbracket \\
 = & \{(a, 2), (b, 3), (c, 1)\} \cup \{(a, 1), (b, 2), (c, 2)\} \\
 = & \{(a, 2), (b, 3), (c, 1), (a, 1), (b, 2), (c, 2)\}
 \end{aligned}$$

# Operations on Bags (inherited)

- Since bags are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned}
 & \llbracket a, a, b, b, b, c \rrbracket \cup \llbracket a, b, b, c, c \rrbracket \\
 = & \{(a, 2), (b, 3), (c, 1)\} \cup \{(a, 1), (b, 2), (c, 2)\} \\
 = & \{(a, 2), (b, 3), (c, 1), (a, 1), (b, 2), (c, 2)\}
 \end{aligned}$$

- This is a relation, but not a function (and thus not a bag)  
- probably not what we intended to happen...

# Operations on Bags (new)

- We can define a special union operator just for bags, so that e.g.

$$\llbracket a, a, b, b, b, c \rrbracket \uplus \llbracket a, b, b, c, c \rrbracket = \llbracket a, a, a, b, b, b, b, b, c, c, c \rrbracket$$

# Operations on Bags (new)

- We can define a special union operator just for bags, so that e.g.

$$\llbracket a, a, b, b, b, c \rrbracket \uplus \llbracket a, b, b, c, c \rrbracket = \llbracket a, a, a, b, b, b, b, b, c, c, c \rrbracket$$

- Definition: for any two bags  $A$  and  $B$ ,

$$A \uplus B = (\lambda x \cdot A(x) + B(x))$$

# Operations on Bags (new)

- We can define a special union operator just for bags, so that e.g.

$$\llbracket a, a, b, b, b, c \rrbracket \uplus \llbracket a, b, b, c, c \rrbracket = \llbracket a, a, a, b, b, b, b, b, c, c, c \rrbracket$$

- Definition: for any two bags  $A$  and  $B$ ,

$$A \uplus B = (\lambda x \cdot A(x) + B(x))$$

- Notes:
  - Since any bag is a function,  $B(x)$  is just the multiplicity of element  $x$  in bag  $B$ .
  - Can you define bag versions of intersection and difference?
  - Can you define the relation *is-a-subbag-of*?



## Sequence: basic definition

- A **sequence** is like a set except that we remember the order in which members occur.

## Sequence: basic definition

- A **sequence** is like a set except that we remember the order in which members occur.
- The place where an element occurs in a sequence is called the **position** of that element.
- We typically use a special kind of bracket to indicate that we care about ordering;

For example:  $\langle a, b, c, b, a, a \rangle$  is the sequence where  $a$  occurs at positions 1, 5 and 6,  $b$  occurs at positions 2 and 4, and  $c$  occurs at position 3.

## Sequence: basic definition

- A **sequence** is like a set except that we remember the order in which members occur.
- The place where an element occurs in a sequence is called the **position** of that element.
- We typically use a special kind of bracket to indicate that we care about ordering;

For example:  $\langle a, b, c, b, a, a \rangle$  is the sequence where  $a$  occurs at positions 1, 5 and 6,  $b$  occurs at positions 2 and 4, and  $c$  occurs at position 3.

- Notes:
  - The notation  $\langle \dots \rangle$  is not very standard.
  - We usually start counting position at 1 (unlike arrays)

## Sequences: set-based definition

- A sequence is really a special kind of **function**.
- For any set  $S$ , a sequence of  $S$  is a (partial) function from  $\mathbb{N}$  to  $S$ , giving the element at each position.

## Sequences: set-based definition

- A sequence is really a special kind of **function**.
- For any set  $S$ , a sequence of  $S$  is a (partial) function from  $\mathbb{N}$  to  $S$ , giving the element at each position.
- Thus  $\langle a, b, c, b, a \rangle$  is just a shorthand for
$$\{(1, a), (2, b), (3, c), (4, b), (5, a)\}$$

# Sequences: set-based definition

- A sequence is really a special kind of **function**.
- For any set  $S$ , a sequence of  $S$  is a (partial) function from  $\mathbb{N}$  to  $S$ , giving the element at each position.
- Thus  $\langle a, b, c, b, a \rangle$  is just a shorthand for
$$\{(1, a), (2, b), (3, c), (4, b), (5, a)\}$$
- For example, given some set  $F \triangleq \{apple, orange, pear\}$ , given the sequence

$$myEating \triangleq \langle apple, pear, apple, pear, apple \rangle$$

## Sequences: set-based definition

- A sequence is really a special kind of **function**.
- For any set  $S$ , a sequence of  $S$  is a (partial) function from  $\mathbb{N}$  to  $S$ , giving the element at each position.
- Thus  $\langle a, b, c, b, a \rangle$  is just a shorthand for
$$\{(1, a), (2, b), (3, c), (4, b), (5, a)\}$$
- For example, given some set  $F \triangleq \{apple, orange, pear\}$ , given the sequence

$$myEating \triangleq \langle apple, pear, apple, pear, apple \rangle$$

we can say

$$myEating = \{(1, apple), (2, pear), (3, apple), (4, pear), (5, apple)\}$$

## Operations on Sequences (inherited)

- Since sequences are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.



# Operations on Sequences (inherited)

- Since sequences are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\langle a, a, b \rangle \cup \langle a, b \rangle$$

## Operations on Sequences (inherited)

- Since sequences are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned} & \langle a, a, b \rangle \cup \langle a, b \rangle \\ &= \{(1, a), (2, a), (3, b)\} \cup \{(1, a), (2, b)\} \end{aligned}$$

## Operations on Sequences (inherited)

- Since sequences are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned} & \langle a, a, b \rangle \cup \langle a, b \rangle \\ = & \{(1, a), (2, a), (3, b)\} \cup \{(1, a), (2, b)\} \\ = & \{(1, a), (2, a), (2, b), (3, b)\} \end{aligned}$$

## Operations on Sequences (inherited)

- Since sequences are a special kind of function/relation/set, we can use all the function/relation/set operations with them.
- But note: the union (or intersection) of two functions is a relation, but not necessarily a function.
- Example:

$$\begin{aligned} & \langle a, a, b \rangle \cup \langle a, b \rangle \\ &= \{(1, a), (2, a), (3, b)\} \cup \{(1, a), (2, b)\} \\ &= \{(1, a), (2, a), (2, b), (3, b)\} \end{aligned}$$

- This is a relation, but not a function (and thus not a sequence)
  - probably not what we intended to happen...

# Operations on Sequences (inherited)

- One useful inherited operation is *cardinality*:
  - The **cardinality** of a finite set is the number of elements it contains.
  - **Notation:** If  $S$  is a finite set, we write  $\#S$  to denote the cardinality of  $S$ .
- Since a sequence is a set of tuples, the cardinality of a sequence is also its *length*.

Example:

$$\# \langle a, b, c, b, a \rangle = 5$$

# Operations on Sequences (inherited)

- One useful inherited operation is *cardinality*:
  - The **cardinality** of a finite set is the number of elements it contains.
  - **Notation:** If  $S$  is a finite set, we write  $\#S$  to denote the cardinality of  $S$ .
- Since a sequence is a set of tuples, the cardinality of a sequence is also its *length*.

Example:

$$\#\langle a, b, c, b, a \rangle = 5$$

- The **empty set**  $\emptyset$  is also a sequence; when we want to refer to it as a sequence we usually write  $\langle \rangle$

Naturally,  $\#\langle \rangle = 0$

# Operations on Sequences (new)

- One of the most important sequence-specific operations is **concatenation**.
- This just appends two sequences together, in order:

$$\langle a, b, c \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a \rangle$$

$$\langle a, b, c \rangle \frown \langle b, a \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a, b, a \rangle$$

# Operations on Sequences (new)

- One of the most important sequence-specific operations is **concatenation**.
- This just appends two sequences together, in order:

$$\langle a, b, c \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a \rangle$$

$$\langle a, b, c \rangle \frown \langle b, a \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a, b, a \rangle$$

- Definition: for any two sequences  $s$  and  $t$ ,

$$s \frown t = \lambda n \in \mathbb{N}. \begin{cases} s(n) & \text{if } 1 \leq n \leq \#s \\ t(n - \#s) & \text{if } (\#s + 1) \leq n \leq (\#s + \#t) \end{cases}$$



# Operations on Sequences (new)

- One of the most important sequence-specific operations is **concatenation**.
- This just appends two sequences together, in order:

$$\langle a, b, c \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a \rangle$$


$$\langle a, b, c \rangle \frown \langle b, a \rangle \frown \langle b, a \rangle = \langle a, b, c, b, a, b, a \rangle$$

- Definition: for any two sequences  $s$  and  $t$ ,

$$s \frown t = \lambda n \in \mathbb{N} . \begin{cases} s(n) & \text{if } 1 \leq n \leq \#s \\ t(n - \#s) & \text{if } (\#s + 1) \leq n \leq (\#s + \#t) \end{cases}$$


- Notes:
  - Since any sequence is a function,  $s(n)$  is just the element at position  $n$  in sequence  $s$ .
  - Notation: sometimes we write  $s.t$  for the concatenation of  $s$  and  $t$ .

# Sets: the full “class hierarchy”




# Sets: the full “class hierarchy”

- We took *sets* as the basic concept because they fit well with logic.




# Sets: the full “class hierarchy”

- We took *sets* as the basic concept because they fit well with logic.
- Database theory takes *relations* as the basic concept (Codd’s relational algebra).



# Sets: the full “class hierarchy”

- We took *sets* as the basic concept because they fit well with logic.
- Database theory takes *relations* as the basic concept (Codd’s relational algebra).
- The theory of computation takes *functions* as the basic concept (Church’s  $\lambda$ -calculus).



# Sets: the full “class hierarchy”

- We took *sets* as the basic concept because they fit well with logic.
- Database theory takes *relations* as the basic concept (Codd’s relational algebra).
- The theory of computation takes *functions* as the basic concept (Church’s  $\lambda$ -calculus).
- Language theory takes *sequences* as the basic concept (Kleene’s regular expressions, Chomsky’s grammars etc.).

