



Activity 3




Complete Activity 3 now. Fill in the blanks using words from the word banks provided.




Activity 3, Question 1

Clock




The *clock* pulses at a constant rate and is used to synchronize the internal operations of the CPU with other system components



- ▶ *Clock cycle*: time between consecutive falling edges
- ▶ 1 GHz = 1,000,000,000 cycles per second, so each cycle is $\frac{1}{1,000,000,000}$ s = $\frac{1}{10^9}$ s = 10-9 s = 1 ns (one nanosecond)

Clock



Question:

If a clock oscillates at 2.2 GHz, what is the duration of one clock cycle in nanoseconds?

Answer:


 $2.2 \text{ GHz} = 2.2 \cdot 10^9 \text{ Hz}$, so one clock cycle is $\frac{1}{2.2 \cdot 10^9}$ seconds. To convert to nanoseconds (recall that 1 ns = 10^{-9} s), solve:

$$\frac{1}{2.2 \cdot 10^9} = x \cdot 10^{-9}$$

$$10^9 \cdot \frac{1}{2.2 \cdot 10^9} = x \cdot 10^{-9} \cdot 10^9$$


$$\frac{1}{2.2} = x = \frac{5}{11}$$

So one clock cycle is $\frac{5}{11} \approx 0.4545$ ns.




Activity 3, Question 2


CPU



- The *central processing unit (CPU)* contains circuitry to carry out the instructions of a computer program, performing basic arithmetic, logical, and I/O operations. It contains:
 - ▶ *ALU* contains circuitry to perform arithmetic, comparison, and logical operations
 - Control unit contains circuitry to fetch an instruction, decode it, and direct the ALU to carry out the appropriate operation
 - Registers memory locations located inside the CPU that hold intermediate values for computations and are accessed much faster than conventional memory


Memory Storage Unit







- Memory storage unit ("memory") stores both
 - ▶ **Instructions** the machine language code for every all of the programs you have open
 - ▶ **Data** strings, arrays, etc. used by those programs
- You can think of your computer's memory as a giant array of bytes
 - On a 32-bit processor, the bytes are numbered from 00000000h to FFFFFFFFh
 - This number is the *memory address* of that particular byte
- Q. How much memory can be addressed if a processor uses 32-bit memory addresses?

Instruction Pointer







- Remember: Machine language instructions are stored in memory
- The processor has a special register called the *instruction pointer* or *program counter*
 - In x86 processors, this register is named EIP
- This contains the memory address of the next machine language instruction to execute
- ▶ So how does the processor actually run a program? Suppose EIP contains 401010h...




Section 2.1.5, Questions 4-5




- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. Fetch
 - 2. Decode
 - 3. Fetch operands (memory access instructions only)
 - 4. Execute
 - 5. Store output (memory access instructions only)




- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. **Fetch** control unit retrieves the next instruction (i.e., byte(s) of machine code) from memory and increments the *instruction pointer/program counter*
 - 2. Decode
 - 3. Fetch operands (memory access instructions only)
 - 4. Execute
 - 5. Store output (memory access instructions only)




- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. Fetch
 - 2. **Decode** control unit determines what those bytes mean, passes operands to the ALU, sends signals to the ALU indicating what action to take
 - 3. Fetch operands (memory access instructions only)
 - 4. Execute
 - 5. Store output (memory access instructions only)




- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. Fetch
 - 2. Decode
 - 3. **Fetch operands** (memory access instructions only) control unit copies operands from memory into internal registers
 - Internal registers cannot be accessed by user programs
 - 4. Execute
 - 5. Store output (memory access instructions only)



- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. Fetch
 - 2. Decode
 - 3. Fetch operands (memory access instructions only)
 - 4. **Execute** ALU performs the operation and sets *flags* (in a special *flags* register) indicating whether certain conditions occurred (overflow, carry, etc.)
 - 5. Store output (memory access instructions only)




- A CPU executes a program by repeating the fetch-decode-execute (FDX) cycle:
 - 1. Fetch
 - 2. Decode
 - 3. Fetch operands (memory access instructions only)
 - 4. Execute
 - 5. **Store output** (memory access instructions only) control unit copies result from register to memory



▶ The FDX cycle in pseudocode:


```
while (true) {
    Fetch next instruction
    Advance instruction pointer (IP)
    Decode instruction
    If memory operand needed, read value from memory
    Execute instruction
    If output operand is a memory operand, write to memory
}
```

- When the CPU is started/reset, the instruction pointer is set to a predefined value
 - E.g., the Intel 8086 processor begins executing instructions at memory address FFFF0h. The machine code at this address is in read-only memory (ROM) and begins the computer's boot sequence.
 - Yes, FFFF0h is a 20-bit memory address, not 32-bit (what?!). Wait for Section 2.3.





Activity 3, Question 3 Section 2.1.5, Question 2


Buses



- A bus is a group of parallel wires that transfer data from one part of the computer to another
- The CPU is connected to the rest of the computer system using four buses:
 - Address bus
 - Data bus
 - Control bus
 - ▶ I/O bus









Activity 3, Question 4


Reading from Memory




- 1. CPU places an address on the address bus
- 2. CPU's control unit signals the memory storage unit that a read operation should be performed
- 3. Memory storage unit reads the data from memory and places the data on the data bus
- 4. CPU's control unit reads the data from the bus and stores it in an internal register in the CPU

Reading from Memory






Cache Memory




- Accessing conventional memory is *slow*, so...
- When memory is accessed the first time, it is copied into a high-speed cache memory
 - Cache memory is faster than conventional memory
 - ▶ But it is much smaller: it only contains a copy of a few recently-accessed portions of main memory
- Memory accesses look in the cache first, then access main memory only if necessary
 - Cache hit: data found in cache
 - Cache miss: data not in cache




Activity 3, Questions 5-6

Operating Systems



- ▶ An operating system (OS)
 - Manages hardware resources
 - Provides services to application programs, e.g.,
 - ▶ Input/output remember what *device drivers* do? (assigned reading, §1.1)
 - Read/write/delete files
 - Allocate memory
 - Run another program
 - The operating system's *application programming interface (API)* provides functions that you can call from C/C++ or assembly language programs to perform these tasks. Example from the Win32 API: <a href="https://www.wienes.com/wind-com/w
- The part of the OS the user interacts with (e.g., to start programs) is the *shell*

Homework



- ▶ For next class (Friday, August 29):
 - ▶ Lab 1 (from Monday) is due <u>on paper</u> at the beginning of class
 - ▶ Read **Section 2.2** from the <u>6th edition</u> (pp. 36–42) PDF in Canvas
 - Be prepared to verbally answer review questions 1, 2, 3, 6, and 12 from Section 2.2.5