


# AVL Trees

COMP 2210 – Dr. Hendrix




## Shapes and height

height 

Many tree algorithms are dependent to some extent on the tree's height.


### best-case BST



### worst-case BST




### balanced BST



COMP 2210 • Dr. Hendrix • 2

## AVL Trees


An AVL tree is a **binary search tree** in which the heights of the left and right subtree of *every* node differ by at most 1.




COMP 2210 • Dr. Hendrix • 3

## Structural possibilities


### Equal heights



### Right is 1 level taller



### Left is 1 level taller



COMP 2210 • Dr. Hendrix • 4

## Balance factors

Every node in an AVL tree has a **balance factor**.

$$bf_N = h_R - h_L$$




Remember to subtract heights, not balance factors.



The text counts path lengths differently from me.




Balance factors are sometimes computed as  $h_L - h_R$




## Balance factor example

**NOT** an AVL Tree



But it could have been one ...




## Participation question



Q. In the AVL tree below, what is the balance factor of the shaded node?

- A. -2
- B. -1
- C. 0
- D. 1
- E. 2




## Rebalancing


A bf of  $\pm 2$  means that the subtree rooted at that node is out of balance.

Balance will be restored by subtree rotations.

All rotations will occur in the context of a 3-node neighborhood.




## Rebalancing operations




COMP 2210 • Dr. Hendrix • 9

## Subtree displacement




COMP 2210 • Dr. Hendrix • 10

## Coding rotations



COMP 2210 • Dr. Hendrix • 11


## Inserting a new element



COMP 2210 • Dr. Hendrix • 12

## Building an AVL tree

Insert: 10, 85, 15, 70, 20, 60, 30, 50, 65, 80, 90, 40, 5, 55







COMP 2210 • Dr. Hendrix • 13

## Participation question



Q. Which AVL tree would result from inserting the following values in the order they are written?

14, 12, 10, 8, 6, 4, 2



COMP 2210 • Dr. Hendrix • 14


## Deleting an element

Use the standard BST deletion algorithm to delete the element. Ex: 40

Beginning at the *point of deletion*, walk the reverse path back toward the root, recalculating balance factors.

Stop at the first (lowest) node that has a balance factor of  $\pm 2$ . This node roots the 3-node neighborhood that will be rotated.


**Multiple rebalancing operations may be required per deletion, so the reverse walk must go to the root each time.**



COMP 2210 • Dr. Hendrix • 15


## Example deletion

**Delete 60:**  
(use successor)



COMP 2210 • Dr. Hendrix • 16


### Example deletion



COMP 2210 • Dr. Hendrix • 17


### Example deletion

Delete 80:



COMP 2210 • Dr. Hendrix • 18


### Example deletion



COMP 2210 • Dr. Hendrix • 19


### Example deletion

Delete 20:




COMP 2210 • Dr. Hendrix • 20

## Example deletion



COMP 2210 • Dr. Hendrix • 21

## Example deletion



COMP 2210 • Dr. Hendrix • 22

## Remind me: what's the point of all this?

### Performance analysis of lists ...

Performance analysis

	Unordered List		Non-Ordered List		Self-Ordered List	
method	Array	Nodes	Array	Nodes	Array	Nodes
add(element)	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$
remove(element)	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$
search(element)	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$
add(element)	$O(1)$	$O(1)$	$O(1)$	$O(1)$	$O(1)$	$O(1)$
add(element, element)	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$
get(index)	$O(1)$	$O(N)$	$O(1)$	$O(N)$	$O(1)$	$O(N)$
index(element)	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$	$O(N)$

Tell me why... ☐ Tell me how... ☐

If we could use binary search on a node-based structure, then add() and remove() would be  $O(\log N)$  – a huge improvement!

Stay tuned... this is exactly where we're headed.

Balanced binary search trees are like a structural implementation of the binary search algorithm.

So, now we can use binary search on a structure built with linked nodes.

**AVL trees offer guaranteed  $O(\log N)$  performance on all three major collection operations: add, remove, and search.**

	Self-Ordered Lists		
	Array	Linked List	AVL Tree
add(element)	$O(N)$	$O(N)$	$O(\log N)$
remove(element)	$O(N)$	$O(N)$	$O(\log N)$
search(element)	$O(\log N)$	$O(N)$	$O(\log N)$

COMP 2210 • Dr. Hendrix • 23