

Object-Oriented Programming

Outline



- Why Object-Oriented Programming?
 - Procedural Programming
 - Object-Oriented Programming
- Classes and Objects
 - Defining a class: attributes and methods (private vs. public)
 - Encapsulation (data hiding)
 - Creating (constructing) an object (instance) from a class
- Universal Modeling Language (UML)

Procedural (Functional) Programming





- Focus
 - On creating functions (procedures) for solving specific tasks
- Advantages
 - Modularized design of a larger program (top-down approach)
 - More natural way of breaking the problem down (decomposition)
 - Better suited for step-by-step sequential types of problems
 - Relatively fast execution compared to OOP approach
- Disadvantages
 - Less well suited for user-driven problems with unpredictable execution paths
 - Limited code reuse, copy/paste modify approach
 - Complex code operating on unprotected data separated from functionality
 - Increasingly complex programs very difficult to manage
 - A change request may require checking and rewriting a significant portion of the code


- **Focus**
 - On creating objects -> software constructs containing both data and procedures (functions)
- **Advantages**
 - Data are integrated and hidden parts of objects, exposed when needed
 - Internal data structure could be changed, the interaction with the data through methods stays the same
 - Object focused and more appropriate for user-driven problems with non-sequential execution paths
 - Significant code reuse, higher reliability and extensibility
 - Improved development productivity, maintainability, speed, lower cost and higher quality
- **Disadvantages**
 - Generally slower execution compared to functional approach
 - Relatively steep learning curve with complex designs

Defining a Class (Conceptual)

- A template (blueprint) for creating objects
 - Provides a list of attributes (data)
 - Implements methods (actions/behaviors)
- Classes: nouns
 - Dog (an abstraction)
- Attributes: adjectives
 - Color, height, weight
- Methods: verbs
 - Sit, come
- Object
 - An instance of a dog class (ayne object)



Examples of Objects




- Student
 - Attributes: name, SSN, midterm and final exam grades
 - Methods: **calc_sem_grade** – calculate semester grade
- Textbook
 - Attributes: name, author, quantity in stock, wholesale price
 - Method: **calc_retail_price** – calculate selling price
- Loan
 - Attributes: interest rate, term, amount borrowed
 - Method: **calc_mth_pmt** – calculate monthly payment

Defining a Class (Technical)

- Class – a template from which objects created
 - Specifies attributes and methods in common to all objects
- ```
class Car:
```
- `__init__` initializer method defining `color`, `make`, `speed`, `direction`, `mph`, ... attributes for `self` reference

```
self.color = 'Green'
```
  - Functions defining `drive`, `turn`, `park`, `break`, ... methods

```
def turn(self, dir):
 self.direction = dir
```



# Using Attributes and Methods

- Object – an instance of a class

```
audi = Car()
```

- An object created in memory
- `__init__` method automatically executed and `self` parameter automatically references the object just created

- Reassign different value to a public attribute (writing)

```
audi.color = 'Red'
```


- Retrieve value of a public attribute (reading)

```
mph = audi.mph
```

- Carry out a method (initiate behavior)

- No need for `self` parameter when a method is called

```
audi.turn(dir)
```







# Loan Class: Attributes & Methods

- Class attributes (data, properties, characteristics,
  - Interest rate, term, amount borrowed (hard-coded)
  - Default object constructor: `__init__(self)`
    - Automatically called when object is instantiated (created)
- Class methods (actions, behaviors, functionality)
  - Calculate monthly payment (\$2,026.74)

```
def calc_mth_pmt(self):
```

- **Lect10\_Loan\_Objects.py**

```
my_mortg = Loan()
```

# Loan Class: Data Encapsulation

- Store class definitions in a separate module (**loan.py**)
- Data Encapsulation – Hiding Attributes
  - Stored as private attributes starting with `__` (2 underscores)
  - Cannot be accessed directly from the code
  - Indirect access through **Accessor** and **Mutator** methods
- Accessor methods
  - Gets the value of the attribute (read-only)
  - Provides safe way to access data from outside the class
- Mutator methods
  - Sets the value of the attribute (write-only)
  - Additional code validates data before assigning it to attribute

# Loan Class: Object Constructors

- Non-default object constructors: special initializer method

- `__init__(self, other parameters)`
- Typically used to initialize the default values for attributes

- Object instantiation and use

```
my_loan = loan.Loan(rate, years, amt, l_type)
```

```
meth_pmt = my_loan.calc_mth_pmt()
```

- \$400,000 for 30 years at 4.5% has \$2,026.74 monthly payment
- Refinance \$300,000 for 15 year at 4% to get \$2,219.74 payment

- **loan1.py**

- Additional attribute: current payment period (180, half-way through)
- Additional methods: calculating remaining balance (\$264,935.82) and interest savings (\$99,877.60)



# Universal Modeling Language (UML)

- Designing complex object-oriented systems
  - Beyond the scope of this class
  - Represent classes with UML diagrams
- Identify all the needed classes
  - Loan, Credit, Borrower, ...
- See section 10.4
  - Define problem domain
  - Identify all the nouns as potential classes
  - Refine / reduce list to relevant nouns
  - Identify class responsibilities
    - Things class is responsible for knowing: data attributes
    - Things class is responsible for doing: actions (methods)

## Loan

```
__int_rate
__term
__amount
__loan_type
__period
```

```
__init__(rate, ...)
get_int_rate()
...
set_int_rate(rate)
...
calc_mth_pmt()
calc_remain_balance(per)
calc_interest_savings(per)
```

# Summary



- Defined the concept of classes as object templates with attributes and methods
- Explained the pros and cons of both procedural and object-oriented programming approaches
- Defined Loan class with attributes and methods
  - Extended the class with additional attributes and methods
- Defined Credit class that contains Loan class
  - A loan object of Loan class is an attribute of the Credit class
- Defined Borrower class also containing Loan class
  - A dictionary of loan objects of Loan class is an attribute of Borrower class
- A list of Borrower objects
  - Each element in the list is an object of Borrower class
- Brief mention of Universal Modeling Language (UML)