


- Object (sprite) code,
- palette,
- position and
- attributes

- Individual object character (tiles) color code,
- Palette values
- object character address

1. SCLR (OSCANCLR) starts the object scanning process.
2. OSCN is activated when each of the four words to be scanned are to be read. The 007783 increments the address.

The 007786 uses an OKI 79V000 gate cell array with 3289 unit cells.







Sheet: /
File: 007785.kicad_sch

Size: A3	Date: 2023-12-22
KiCad E.D.A. kicad-cli 7.0.10-7.0.10-ubuntu20.04.1	

Rev:
Id: 1/7








Sheet: /Frame Buffer Address Counters/
File: frame_buffer_address_counters.kicad_sch


Title:		
Size: A3	Date: 2023-12-22	Rev:
KiCad E.D.A. kicad-cli 7.0.10-7.0.10-ubuntu20.04.1	Id: 4/7	

Object Character Select Address

Object (Sprite) tiles are called characters on the twin16 platform.



VSIZE1	VSIZE0	VSIZE	HSIZE1	HSIZE0	HSIZE	OCAS2	OCAS1	OCAS0			
0	0	16	0	0	16	0	0	0	0	16H16V	256
0	0	16	0	1	32	0	0	1	1	32H16V	512
0	0	16	1	0	64	0	1	0	2	64H16V	1024
0	0	16	1	1	128	0	1	1	3	128H16V	2048
0	1	32	0	0	16	1	0	0	4	16H32V	512
0	1	32	0	1	32	1	0	1	5	32H32V	1024
0	1	32	1	0	64	0	1	0	2	64H32V	2048
0	1	32	1	1	128	0	1	1	3	128H32V	4096
1	0	64	0	0	16	0	1	0	2	16H64V	1024
1	0	64	0	1	32	0	1	1	3	32H64V	2048
1	0	64	1	0	64	1	1	0	6	64H64V	4096
1	0	64	1	1	128	1	1	1	7	128H64V	8192
1	1	128	0	0	16	1	1	0	6	16H128V	2048
1	1	128	0	1	32	1	1	1	7	32H128V	4096
1	1	128	1	0	64	1	1	0	6	64H128V	8192
1	1	128	1	1	128	1	1	1	7	128H128V	16384



CODE[5..0]D

