Статистики за мечеви на играч (победени, изгубени, одиграни)

Input
- id_igrach (1)

Output
- odigrani, pobedi, zagubi

Опис:
- Со овој прашалник добиваме статистика за историјата на играчот во турнири и во лиги (сите мечеви кои ги има играно)
- View: igrach_stats

odigrani
- Целта на овој подпрашалник е да ги изброи одиграните мечеви за даден играч

pobedi
- Целта на овој подпрашалник е да ги изброи победените мечеви за даден играч

zagubeni
- Целта на овој подпрашалник е да ги изброи изгубените мечеви за даден играч

main query
- Ги комбинира резултатите од подпрашалниците

```
-- odigrani
select 1 as igrach, count(*) as odigrani from igrachi as i
inner join mechevi as m on m.id_lice_igrach_domakjin=i.id_lice_igrach or
m.id_lice_igrach_gostin=i.id_lice_igrach
```

```sql
        where i.id_lice_igrach=1


-- pobedi
select 1 as igrach, sum(stats.pobedi) as pobedi from (
        (
                select count(*) as pobedi from mechevi as m
                where m.id_lice_igrach_domakjin=1 and m.dobieni_setovi_domakjin >
m.dobieni_setovi_gostin
        )
        union
        (
                select count(*) as pobedi from mechevi as m
                where m.id_lice_igrach_gostin=1 and m.dobieni_setovi_domakjin <
m.dobieni_setovi_gostin
        )
) as stats


-- zagubeni
select 1 as igrach, sum(stats.zagubi) as zagubeni from (
        (
                select count(*) as zagubi from mechevi as m
                where m.id_lice_igrach_domakjin=1 and m.dobieni_setovi_domakjin <
m.dobieni_setovi_gostin
        )
        union
        (
                select count(*) as zagubi from mechevi as m
                where m.id_lice_igrach_gostin=1 and m.dobieni_setovi_domakjin >
m.dobieni_setovi_gostin
        )
) as stats



--main query
select odigrani, pobedi, zagubeni from odigrani as o
inner join pobedi as p on o.igrach=p.igrach
inner join zagubeni as z on z.igrach=p.igrach
```

Целосен прашалник:

```sql
select odigrani, pobedi, zagubeni from (
        select 1 as igrach, count(*) as odigrani from igrachi as i
        inner join mechevi as m on m.id_lice_igrach_domakjin=i.id_lice or
        m.id_lice_igrach_gostin=i.id_lice
        where i.id_lice=1
) as o
inner join (
        select 1 as igrach, sum(stats.pobedi) as pobedi from (
                (
                        select count(*) as pobedi from mechevi as m
                        where m.id_lice_igrach_domakjin=1 and m.dobieni_setovi_domakjin >
m.dobieni_setovi_gostin
                )
                union
                (
                        select count(*) as pobedi from mechevi as m
                        where m.id_lice_igrach_gostin=1 and m.dobieni_setovi_domakjin <
m.dobieni_setovi_gostin
                )
        ) as stats
) as p on o.igrach=p.igrach
inner join (
        select 1 as igrach, sum(stats.zagubi) as zagubeni from (
                (
                        select count(*) as zagubi from mechevi as m
                        where m.id_lice_igrach_domakjin=1 and m.dobieni_setovi_domakjin <
m.dobieni_setovi_gostin
                )
                union
                (
                        select count(*) as zagubi from mechevi as m
                        where m.id_lice_igrach_gostin=1 and m.dobieni_setovi_domakjin >
m.dobieni_setovi_gostin
                )
        ) as stats
) as i on i.igrach=p.igrach
```