

More Exercise: Arrays

Problems for exercise and homework for the ["JS Fundamentals" Course @ SoftUni.](#)

Submit your solutions in the SoftUni judge system at: <https://judge.softuni.bg/Contests/1272>

1. Print N-th Element

Write a function that collect each element of an array, on a given **step**.

The **input** comes as **array of strings**. The last element is **N - the step**.

The **collections** are every element on the **N-th** step **starting** from the **first one**. If the step is "**3**", you need to print the **1-st**, the **4-th**, the **7-th** ... and so on, until you reach the end of the array. Then, print elements in a row, **separated** by single space.

Examples

Input	Output
['5', '20', '31', '4', '20', '2']	5 31 20
['dsa', 'asd', 'test', 'test', '2']	dsa test
['1', '2', '3', '4', '5', '6']	1

2. Add and Remove

Write a function that **adds** and **removes** numbers **to/from** an array. You will receive a command which can either be "**add**" or "**remove**".

The **initial number** is **1**. Each input command should **increase that number**, regardless of what it is.

- Upon receiving an "**add**" command you should add the current number to your array.
- Upon receiving the "**remove**" command you should remove the **last** entered number, currently existent in the array.

Input

The **input** comes as array of strings. Each element holds a **command**.

Output

Print elements in a row, separated by single space. In case of an empty array, just print "**Empty**".

Examples

Input	Output
['add', 'add', 'add', 'add']	1 2 3 4
['add', 'add', 'remove', 'add', 'add']	1 4 5

['remove', 'remove', 'remove']	Empty
--------------------------------	-------

3. Rotate Array

Write a function that rotates an array. The array should be rotated to the **right** side, meaning that the **last** element should become the **first**, upon rotation.

The **input** comes as **array** of strings. The **last element** of the array is the amount of rotation you need to perform.

The **output** is the **resulted** array after the rotations. The elements should be printed on one **line**, **separated** by a **single space**.

Examples

Input	Output
['1', '2', '3', '4', '2']	3 4 1 2
['Banana', 'Orange', 'Coconut', 'Apple', '15']	Orange Coconut Apple Banana

Hints

- Check if there is a **built-in function** for inserting elements **at the start** of the array.

4. Non-Decreasing Subsequence

Write a function that extracts only those numbers that form a **non-decreasing subsequence**. In other words, you start from the **first element** and continue to **the end** of the given array of numbers. Any number which is **LESS THAN** the **current biggest one** is **ignored**, alternatively if it's equal or higher than the **current biggest one** you set it as the **current biggest one** and you continue to the next number.

Input

The **input** comes as array of numbers.

Output

The **output** is the processed array after the filtration, which should be a non-decreasing subsequence. The elements should be printed on one line, separated by a **single space**.

Examples

Input	Output
[1, 3, 8, 4, 10, 12, 3, 2, 24]	1 3 8 10 12 24
[1, 2, 3, 4]	1 2 3 4
[20, 3, 2, 15, 6, 1]	20

Hints

- The **Array.filter()** built-in function might help you a lot with this problem.

5. Tseam Account

As a gamer, Peter has Tseam Account. He loves to buy new games. You are given Peter's account with all of his games-> **strings, separated** by space. Until you receive "**Play!**" you will be receiving commands which Peter does with his account.`

You may receive the following commands:

- **Install {game}**
- **Uninstall {game}**
- **Update {game}**
- **Expansion {game}-{expansion}**

If you receive **Install command**, you should **add** the game at **last** position in the account, but only if it **isn't** installed already.

If you receive **Uninstall command**, **delete** the game if it **exists**.

If you receive **Update command**, you should **update** the game **if it exists** and place it on **last position**.

If you receive **Expansion command**, you should check if the game exists and **insert** after it the expansion in the following format: "{game}:{expansion}";

Input

- On the **first input line** you will receive Peter`s **account** - **sequence** of game names, **separated** by space.
- Until you receive "**Play!**" you will be receiving **commands**.

Output

- As output you must print Peter`s Tseam **account**.

Constraints

- The **command will always be valid**.
- The **game** and **expansion** will be strings and will contain any character, except '- '.
- Allowed working **time / memory: 100ms / 16MB**.

Examples

Input	Output	Comments
['CS WoW Diablo', 'Install LoL', 'Uninstall WoW', 'Update Diablo', 'Expansion CS-Go', 'Play!']	CS CS:Go LoL Diablo	We receive the account => CS, WoW, Diablo We Install LoL => CS, WoW, Diablo, LoL Uninstall WoW => CS, Diablo, LoL Update Diablo => CS, LoL, Diablo We add expansion => CS, CS:Go, LoL, Diablo We print the account.

['CS WoW Diablo', 'Uninstall XCOM', 'Update PeshoGame', 'Update WoW', 'Expansion Civ-V', 'Play!']	CS Diablo WoW	
--	---------------	--

Multidimensional Arrays

We will mainly work with 2-dimensional arrays. The concept is as simple as working with a simple 1-dimensional array. It is just an array of arrays.

6. Magic Matrices

Write a function that checks if a given **matrix** of numbers is magical. A matrix is magical if the **sums of the cells** of every row and every column are equal.

Input

The input comes as an array of arrays, containing numbers (number 2D matrix). The input numbers will **always be positive**.

Output

The **output** is a **Boolean** result indicating whether the matrix is magical or not.

Examples

Input	Output
[[4, 5, 6], [6, 5, 4], [5, 5, 5]]	true

Input	Output
[[11, 32, 45], [21, 0, 1], [21, 1, 1]]	false

Input	Output
[[1, 0, 0], [0, 0, 1], [0, 1, 0]]	true

Hints

- You can read more about the magic square [here](#).

7. Spiral Matrix

Write a function that generates a **Spirally filled** matrix with numbers, with given dimensions.

Input

The input comes as 2 numbers that represent the **dimension of the matrix**.

Output

The output is the matrix filled spirally starting from **1**. You need to print **every row on a new line**, with the cells **separated by a space**. Check the examples below.

Examples

Input	Output
5, 5	1 2 3 4 5 16 17 18 19 6 15 24 25 20 7 14 23 22 21 8 13 12 11 10 9

Input	Output
3, 3	1 2 3 8 9 4 7 6 5

8. Diagonal Attack

Write a function that reads a given matrix of numbers, and checks if both main diagonals have **equal sum**. If they do, set every element that is **NOT** part of **the main diagonals** to that sum, alternatively just print the matrix unchanged.

Input

The input comes as array of strings. Each element represents a **string of numbers**, with **spaces** between them. Parse it into a **matrix of numbers**, so you can work with it.

Output

The **output** is either the new matrix, with all cells not belonging to a main diagonal changed to the diagonal sum or the original matrix, if the two diagonals have different sums. You need to print **every row on a new line**, with cells **separated by a space**. Check the examples below.

Examples

Input	Output
['5 3 12 3 1', '11 4 23 2 5', '101 12 3 21 10', '1 4 5 2 2', '5 22 33 11 1']	5 15 15 15 1 15 4 15 2 15 15 15 3 15 15 15 4 15 2 15 5 15 15 15 1

Input	Output
['1 1 1', '1 1 1', '1 1 0']	1 1 1 1 1 1 1 1 0

9. Orbit

You will be given an empty rectangular space of cells. Then you will be given the position of a star. You need to build the orbits around it.

You will be given a coordinate of a cell, which will **always be inside the matrix**, on which you will put the value - **1**. Then you must set the values of the cells **directly surrounding that cell**, including the **diagonals**, to **2**. After which you must set the values of the next surrounding cells to 3 and so on. Check the pictures for more info.

For example, we are given a matrix which has 5 rows and 5 columns and the star is at coordinates - **0**, **0**. Then the following should happen:

1				

1	2			
2	2			

1	2	3	4	5
2	2	3	4	5

3	3	3	4	5
4	4	4	4	5
5	5	5	5	5

If the coordinates of the star are somewhere in the middle of the matrix for example - 2, 2, then it should look like this:

		1		

	2	2	2	
	2	1	2	
	2	2	2	

3	3	3	3	3
3	2	2	2	3
3	2	1	2	3
3	2	2	2	3
3	3	3	3	3

Input

The input comes as an array of 4 numbers [width, height, x, y] which represents the **dimensions** of the matrix and the **coordinates** of the star.

Output

The output is the filled matrix, with the cells **separated by a space**, each **row on a new line**.

Examples

Input	Output
[4, 4, 0, 0]	1 2 3 4 2 2 3 4 3 3 3 4 4 4 4 4

Input	Output
[5, 5, 2, 2]	3 3 3 3 3 3 2 2 2 3 3 2 1 2 3 3 2 2 2 3 3 3 3 3 3

Input	Output
[3, 3, 2, 2]	3 3 3 3 2 2 3 2 1

Hints

- Check if there is some **dependency** or **relation** between the **position of the numbers** and the **rows** and **columns** of those positions.