

Powerful and Swift Printing

FOR GREATER RESULTS

Start every workday with confidence. The LBP325x monochrome laser printer makes high volume printing effortless. Small in footprint, easy to maintain and scalable for greater productivity, the LBP325x is ready whenever the business gears up for growth.



Add up to three 550-sheet cassettes for a huge paper input capacity of 2,300 sheets, reducing the frequency of paper reloads.



single-sided and double-sided prints respectively, boost your print productivity rate with LBP325x.



MINIMAL MAINTENANCE

Experience effortless replacement with the All-in-One Cartridge and the Auto Toner Seal



uniFLOW COMPATIBLE

Track print usage with uniFLOW print



EASE OF USE

Experience friendly navigation of settings

SPECIFICATIONS

PRINT				
Printing Method		Monochrome Laser Beam Printing		
Printing Speed	A4	43 ppm		
	Letter	45 ppm		
	2-sided	36 ppm (A4) / 37 ppm (Letter)		
Print Resolution		600 x 600dpi		
Print Quality with Image Refinement Technology		1,200 (eq.) x 1,200dpi (eq.)		
Warm up Time (From Power On)		30 sec or less		
First Printout Time (FPOT)	A4	Approx. 5.7 sec		
	Letter	Approx. 5.7 sec		
Recovery Time (From Sleep Mode)		3.0 sec or less		
Print Language		UFR II, PCL 6 , PostScript 3™		
Auto Duplex Print		Standard		
Available Paper Size for Auto Duplex Print		A4, Letter, Legal, Foolscap, Indian Legal		
Print Margins		5mm - top, bottom, left and right (Envelope: 10mm)		
Printinalgins		Poster, Booklet, Watermark, Page Composer,		
Print Features		Toner Saver		
LICE Divert Driet		Supported		
USB Direct Print				
Supported File Format for USB Direct Print Supported File Format: JPEG, TIFF, PDF				
PAPER HANDLING	6. 1.10	550.1		
Paper Input	Standard Cassette	550 sheets		
(Based on 80g/m²)	Multi-Purpose Tray	100 sheets		
	Optional Paper Feeder	550 sheets (x3)		
Maximum Paper Input Capacity		2,300 sheets		
Paper Output		250 sheets		
	Cassette /	A4, B5, A5, A6, Letter, Legal, Statement, Executive,		
	Optional Paper Feeder	Foolscap, Indian Legal, Custom		
		(Min. 105.0 x 148.0mm to Max. 216.0 x 355.6mm)		
Paper Sizes	Multi-Purpose Tray	A4, B5, A5, A6, Letter, Legal, Statement, Executive,		
		Foolscap, Indian Legal, Index Card		
		Envelope: COM10, Monarch, C5, DL, Custom		
		(Min. 76.2 x 127.0mm to Max. 216.0 x 355.6mm)		
Paper Types		Plain, Heavy, Recycled, Label, Index Card,		
		Postcard, Envelope		
Paper Weight	Cassette /	60 to 120g/m ²		
	Optional Paper Feeder	, , , , , , , , , , , , , , , , , , ,		
	Multi-Purpose Tray	60 to 199g/m ²		
CONNECTIVITY & SOFTWARE				
Standard Interfaces	Wired	USB 2.0 High Speed, 10Base-T/100Base-TX		
		/1000Base-T		
	Wireless	-		
Network Protocol	Print	LPD, RAW, WSD-Print (IPv4,IPv6)		
	TCP/IP Application	Bonjour(mDNS), HTTP, HTTPS, POP before SMTP		
	Services	(IPv4,IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4),		
	36141663	DHCPv6 (IPv6)		
	Management	SNMPv1, SNMPv3 (IPv4,IPv6)		

Windows® 10, Windows® 81, Windows® 7, Windows® 7, Windows® 8erver® 2016, Windows Server® 2016, Windows Server® 2016, Windows Server® 2012, Windows Server® 2012, Windows Server® 2020, Windows Server® 20208, Mac® OS X 10.9.5 & up 110, Linux 110 Printer driver, Toner Status GENERAL Device Memory			
Network Security	Network Security	NA/Superal	IP/Mac address filtering, HTTPS, SNMPv3,
Other Features Department ID, Secure Print Mobile Solution Canon PRINT Business, Canon Print Service, Google Cloud Print", Apple® AirPrint®, Mopria® Print Service Windows® 10, Windows® 81, Windows® 7, Windows Server® 2019, Windows Server® 2018, Windows Server® 2016, Windows Server® 2018, Printer driver, Toner Status GENERAL Device Memory 1 GB LCD Display Vari-Angle 5-line LCD Dimensions (W x D x H) 4 prox 11.5 kg (without cartridge) Meight Approx 11.5 kg (without cartridge) Power Consumption Maximum 1,380 W or less Operation (average) Approx. 10.1 W Standby (average) Approx. 500 W Standby (average) Approx. 1.9 W (USB) / Approx. 12 (LAN) Noise Levels (2) Sound Pressure Level: 54dB Sound Power Level: 6.9 B Sound Pressure Level: 26dB Sound Power Level: 3.9 B Operating Environment Imperature 10 – 30°C Hundity 20% - 80% RH (no condensation) Cartridge 056:10,000 pages (bundled: 5,100 pages)		vviied	IEEE802.1x, IPSEC
Canon PRINT Business, Canon Print Service, Google Cloud Print*, Apple® AirPrint*, Mopria® Print Service Windows® 10, Windows® 11, Windows® 21, Windows® 21, Windows® 21, Windows® 21, Windows® 21, Windows® 21, Windows Server® 2012, R2, Windows Server® 2012, Windows Server® 2012, Windows Server® 2012, Windows Server® 2018, R2, Windows Server® 2018, Mac® OS X 10.9.5 & up f™, Linux f™ Printer driver, Toner Status		Wireless	-
Cloud Print*", Apple® Air Print*, Mopria® Print Service Windows® 10, Windows® 8.1, Windows® 2016, Windows® 8.1, Windows® 2016, Windows Server® 2016, Windows Server® 2016 R2, Windows Server® 2012 R2, Windows Server® 2012 R2, Windows Server® 2018 R2, Windows Server® 2008, Mac® OSX 10.9.5 & up ("), Linux (")	Other Features		Department ID, Secure Print
Cloud Print**, Apple* AirPrint*, Mopria* Print Service Windows 10, Windows 27, Windows 27, Windows Server* 2019, Windows Server* 2019, Windows Server* 2016, Windows Server* 2018, Windows Server* 2018, Windows Server* 2012, Windows Server* 2018, Windows Server*	Mobile Solution		Canon PRINT Business, Canon Print Service, Google
Windows Server® 2019, Windows Server® 2016, Windows Server® 2018, Windows Server® 2008, Mac® OS X 10.95 & up (**), Linux (**) Software Included			Cloud Print™, Apple® AirPrint®, Mopria® Print Service
Compatible Operating Systems			
Windows Server® 2008 R2, Windows Server® 2008, Mac® OS X 10.9.5 & up 1 Linux 1 Device Memory			
Mac® OS X 10.9.5 & up 11, Linux 11			
Software Included			
Device Memory			
Device Memory	Software Included		Printer driver, Toner Status
Vari-Angle 5-line LCD	GENERAL		
Dimensions (W x D x H)	Device Memory		1 GB
Maximum	LCD Display		Vari-Angle 5-line LCD
Maximum	Dimensions (W x D x H)		417 x 376 x 275 mm
Operation (average)	Weight		Approx. 11.5 kg (without cartridge)
Standby (average) Approx. 10.1 W	Power Consumption	Maximum	1,380 W or less
Standby (average) Approx. 10.1 W		Operation (average)	Approx. 600 W
Operation Sound Pressure Level: 54dB Sound Power Level: 6.9B Noise Levels (*2) Standby Sound Pressure Level: 26dB Sound Power Level: 26dB Sound Power Level: 3.9B Operating Environment Temperature 10 - 30°C Humidity 20% - 80% RH (no condensation) Power Requirements AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz) Standard Cartridge 056: 10,000 pages (bundled: 5,100 pages)		Standby (average)	Approx. 10.1 W
Operation Sound Power Level: 6.9B Standby Sound Pressure Level: 26dB Sound Power Level: 3.9B Operating Environment Temperature 10 - 30°C Humidity 20% - 80% RH (no condensation) Power Requirements AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz) Standard Cartridge 056: 10,000 pages (bundled: 5,100 pages)		Sleep (average)	Approx. 1.9W (USB)/ Approx. 1.2 (LAN)
Sound Power Level: 6.19		Operation	Sound Pressure Level: 54dB
Standby Sound Pressure Level: 26dB Sound Pressure Level: 26dB Sound Power Level: 3.9B Operating Environment Temperature 10 - 30 °C Humidity 20% - 80% RH (no condensation) Power Requirements AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz) Standard Cartridge 056: 10,000 pages (bundled: 5,100 pages)	Noise Levels (*2)		Sound Power Level: 6.9B
Sound Power Level: 3.78 Operating Environment		Standby	Sound Pressure Level: 26dB
Operating Environment Humidity 20% - 80% RH (no condensation) Power Requirements AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz) Standard Cartridge 056: 10,000 pages (bundled: 5,100 pages)			Sound Power Level: 3.9B
Humidity	Operating Environment	Temperature	10 - 30°C
Standard Cartridge 056: 10,000 pages (bundled: 5,100 pages)		Humidity	20% - 80% RH (no condensation)
and the second s	Power Requirements		AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz)
Toner Cartridge (*3) Low Cartridge 056L: 5.100 pages	Toner Cartridge (*3)	Standard	Cartridge 056: 10,000 pages (bundled: 5,100 pages)
		Low	Cartridge 056L: 5,100 pages
High Cartridge 056H: 21,000 pages		High	Cartridge 056H: 21,000 pages
Monthly Duty Cycle (*4) 150,000 pages	Monthly Duty Cycle (*4)		150,000 pages
OPTIONAL ACCESSORIES			
Paper Feeder PF-C1 (550 sheets)	Paper Feeder		Paper Feeder PF-C1 (550 sheets)
Barcode Printing Barcode Printing Kit-F1	Barcode Printing		Barcode Printing Kit-F1
SD Card SD Card - C1	SD Card		SD Card - C1

Canon

Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd. 1 Fusionopolis Place, #15-10, Galaxis Singapore 138522 Tel: 65-6799 8888 Fax: 65-6799 8888 https://asia.canop

CANON OFFICES

PPINES n Marketing (Philippines), Inc : 632-884 9090 : 632-556 1456

AND Marketing (Thailand)

CANON BUSINESS PARTNERS

r rrading Company (Pvt.) Limited (92-21)38704830-41, 35170851-54 (92-21)-35170860 stc@stc.atlas.pk

Dealer's Stamp

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. We and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed a diversarily. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to respective owners.