

imageRUNNER ADVANCE DX 6780i/6765i 6755i

imageRUNNER ADVANCE DX 6700 Series

Print up to 80 ppm (BW)

Scan up to 270/270 ipm (300 dpi) (BW/color, duplex)

Print up to 11" × 17"

8,020-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.





## WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with predefined settings such as number of copies and finishing requirements.



## **SECURITY**

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\*.<sup>2</sup> systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control<sup>3</sup> utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>4</sup>



# QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

<sup>\*</sup> Security Information and Event Management



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.

## **CONFIGURATION OPTIONS**



### STAPLE FINISHER-AC1

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Supports Staple-free\* Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



#### **BOOKLET FINISHER-AC1**

- · 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



#### DOCUMENT INSERTION/ FOLDING UNIT-J1

- Insert pre-printed sheets
- Up to 11" × 17"
- 1-tray, 100-sheet capacity
- Z-fold, C-fold



#### DOCUMENT INSERTION UNIT-P1

- Insert pre-printed sheets
- Up to 11" × 17"
- 1-tray, 100-sheet capacity



## imagePASS-Y3 v1.1

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



UPRIGHT CONTROL PANEL-J1

**UTILITY TRAY-B1** 



#### PAPER DECK UNIT-E1

- 3,660-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports LTR

## **SPECIFICATIONS**

#### Main Unit

Type

Monochrome Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store

Optional: Fax

Processor

1.75GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Color Flat Touch-panel Standard: Optional 10.4" TFT LCD SVGA Color Upright Touch-panel

Memory 3.0 GB RAM

Hard Disk Drive 250 GB Standard: Maximum: 1TB

Interface Connection

Network

1000Base-T/100Base-TX/10Base-T Standard: Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy

Others

Optional:

Standard USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Copy Control Interface Paper Capacity (LTR. 20 lb. Bond)

4.360 Sheets Standard: Maximum: 8.020 Sheets

Paper Sources (LTR, 20 lb. Bond) Dual 1,560-sheet Paper Drawers, Dual Standard:

570-sheet Paper Cassettes, 100-sheet

Multipurpose Tray 3,660-sheet Paper Deck

(Paper Deck Unit-E1 or POD Deck Lite-C1)

Paper Output Capacity (LTR, 20 lb. Bond)

With Copy Tray: 250 Sheets

With External 3,500 Sheets (with Staple Finisher-AC1 or

Booklet Finisher-AC1) Finishers:

Finishing Capabilities

With External Collate, Group, Offset, Staple, Saddle-Stitch, Hole Punch, Eco Staple, Finishers:

Staple On Demand, Document Insertion, Z-fold, C-fold

Supported Media Types

Paper Cassettes: Thin, Plain, Recycled, Color, Heavy, Bond,

Pre-punched, Letterhead, Tab<sup>5</sup>

Thin, Plain, Recycled, Color, Heavy, Tracing,6 Multipurpose Bond, Transparency, Label, Pre-punched, Tray:

Letterhead, Tab

Paper Decks: Thin, Plain, Recycled, Color, Heavy,

Pre-punched, Letterhead, Bond, Transparency, Labels, Tab

Supported Media Sizes

Multipurpose 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size/Free Size (4" x 5-7/8" to 11-3/4" x 19-1/4") Tray:

Paper Decks: Letter

Paper Cassettes: 11"x17", Legal, Letter, Letter-R, Executive, Statement-R, Custom size (5-1/2" x 7-1/8" to

11-3/4" x 19-1/4")

Supported Media Weights

Paper Decks: 14 lb. Bond to 80 lb. Cover (52 to 220 g/ $m^2$ ) Paper Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) Multipurpose Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²) Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed

Up to 80 ppm (Letter) 6780i: Up to 61 ppm (Letter-R)

Up to 48 ppm (Legal) Up to 40 ppm (11" x 17") Up to 65 ppm (Letter)

Up to 50 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17") Up to 55 ppm (Letter) Up to 43 ppm (Letter-R)

Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")

Warm-up Time

Approx. 30 Seconds<sup>7</sup> From Power On: Approx. 30 Seconds8 From Sleep

Mode: Quick Startup

Approx. 4 Seconds9

Mode:

6765i:

6755i:

Dimensions (W x D x H)

26-3/8" x 30-3/8" x 46-5/8" (670 x 770 x 1,185 mm)

Installation Space (W x D)

60-3/8" x 53-1/4" (1,533 mm x 1,353 mm) Basic:

(with Multi-purpose Tray/upper-right cover open + front cover open + Copy Tray) 95-7/8" x 53-1/4" (2,436 mm x 1,353 mm) (with POD Deck Lite-C1 + Document

Insertion/Folding Unit-J1 + Booklet Finisher-AC1/Staple Finisher-AC1 + Main unit front

cover open )

Weight

Fully

Configured:

Approx. 491.6 lb (223 kg)10

**Print Specifications** 

Print Resolution (dpi)

1200 x 1200

Standard Page Description Languages

UFR II, PCL® 6, Adobe® PS® 3

Supported File Types

PDF, TIFF, JPEG, EPS," XPS

Printing from Mobile and Cloud

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for

further information.

**Fonts** 

DS.

PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),12

Barcode Fonts<sup>13</sup> 136 Roman

Operating System<sup>14</sup>

UFRII/PS: Windows® 7/8.1/10/Server 2008/Server

2008 R2/Server 2012/Server 2012 R2/ Server 2016/Server 2019, MAC OS X

(10.10 or later)

Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/

Server 2016/Server 2019

Windows® 7/8.1/10, MAC OS X (10.9 or later) PPD:

Copy Specifications

First-Copy-Out Time (Letter)

6780i: As fast as 3.1 seconds 6765i/6755i: As fast as 3.3 seconds

Copy Resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999 Copies

Magnification

25%-400% (1% Increments)

Preset Reductions/Enlargements

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

Scan Specifications

Single-pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** 

Up to 200 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,

Custom size: 2-3/4" x 5-1/2" to 12" x 17"

Document Feeder Supported Media Weights

Single-sided/Double-sided scanning

13.3 lb Bond to 80 lb. Cover (50 to 220 gsm)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

Max. Platen

Scanning Size: Up to 11-3/4" x 17" (297 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10

Server 2008/Server 2008 R2/Server 2012/

Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600 Scan for Copy:

(Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), Scan for Send:

(Pull) 600 x 600

Scan for Fax:  $600 \times 600$ 

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning

BW/Color: 135 (300 dpi)/80 (600 dpi)

Double-sided Scanning

BW/Color: 270 (300 dpi)/160 (600 dpi)

**Send Specifications** 

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box,

Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Up to 600 x 600 Push: Up to 600 x 600 Pull:

Communication Protocol FTP, SMB v3.0, WebDAV File:

SMTP, POP3 Email:

File Format

TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

(Optional)

Modem Speed

Super G3: 33.6 Kbps 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dni)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement-R to 11" x 17

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

**Store Specifications** 

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV Windows (Windows 8.1/10) Supported

Client PC:

Concurrent Connections (Max.): SMR-

WebDAV: 3 (Active Sessions) Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD); 480 GB (With Optional 1 TB HDD) Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW

Online Express, 15 User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access

Management System

Optional: uniFLŎW

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Verify System at Startup,3

McAfee Embedded Control<sup>3</sup>

Hard Disk Drive Mirroring, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Optional:

Encrypted Secure Print, IP/Mac Standard:

Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Adobe

LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature,

User Signature

**Environmental Specifications** 

**Operating Environment** 

Temperature: 50 to 86 °F

20 to 80 % RH (Relative Humidity) Humidity:

Power Requirements 110-127 V AC, 60 Hz, 16 A

**Power Consumption** 

Maximum: Approx. 2,032 W Approx. 278 W<sup>16</sup> Standby:

Sleep Mode: 0.9 W17

Typical Electricity Consumption (TEC) Rating<sup>18</sup>

6780i: 1.65 kWh

Standards

ENERGY STAR Certified: 6780i Rated EPEAT Gold: 6780i

Consumables

Toner

GPR-38 Black Toner

Toner Yield (Estimated @ 6% Coverage)

56,000 Pages

Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.

Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.

This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on. Requires additional option.

5 Tab Feeding Attachment-B1 is required.

<sup>6</sup> Some types of tracing paper cannot be used.

Time from device power-on until copy ready (not print reservation).

<sup>8</sup> Time from exiting Sleep mode to when printing is operational.

<sup>9</sup> Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display.

Including ADF, optional Upright Touch Panel and the toner bottle.

EPS can be printed directly only from the Remote User

Interface.
Requires the optional PCL International Font Set-Al.

Requires the optional Barcode Printer Kit-D1.

Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix, may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

No charge for this solution; however, activation is required.

Standby Reference Value: measured one unit.

O.9 W Sleep mode not available in all circumstances due to

certain settings.
Based on ENERGY STAR Product Specification for Imaging





















