



SPECIFICATIONS LBP664Cx

PRINT		
Printing Method		Colour Laser Beam Printing
Printing Speed	A4	27 ppm / 27 ppm (mono / colour)
	Letter	28 ppm / 28 ppm (mono / colour)
	2-sided (A4)	21 ppm / 21 ppm (mono / colour)
Print Resolution		21 ppm (mone y corodi)
Print Resolution Print Quality with Image Refinement Technology		·
		1,200 × 1,200 dpi (equivalent)
Warm-up Time (From power on)		13 sec or less
First Print Out Time (FPOT)	A4	Approx. 7.7 / 8.6 sec (mono / colour)
	Letter	Approx. 7.5 / 8.5 sec (mono / colour)
Recovery Time (From Sleep	Mode)	6.1 sec or less
Print Language		UFR II, PCL 6, Adobe® PostScript® 3™
Auto Duplex Printing		Standard Standard
Available Paper Size for Auto Duplex Print		AA, Letter, Legal, Foolscap, Indian Legal
Print Margins		5mm - fop, bottom, left and right (Envelope: 10mm)
Print Features		Poster, Booklet, Watermark, Page Composer, Toner Saver
Supported File Format for USB Direct Print		
	ISB Direct Print	JPEG. TIFF, PDF
PAPER HANDLING		
Paper Input (Based on 80 g/m²)	Standard Cassette	250 sheets
	Multi-Purpose Tray	50 sheets
	Optional Paper Feeder	550 sheets
Maximum Paper Capacity (Based on 80 g/m²)		850 sheets
Paper Output		150 sheets
Paper Size	Standard Cassette /	A4, 85, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal
	Optional Paper Feeder	Custom (Min. 98.0 x 148.0mm to Max. 216.0 x 355.6mm)
	Multi-Purpose Tray	A4, B5, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal, Index Card, Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127.0mm to Max. 216.0 x 355.6mm)
Paper Weight	Standard Cassette / Optional Paper Feeder	60 to 200g/m²
	Multi-Purpose Tray	40 to 200m (m²
	Mulli-Purpose Iray	60 to 200g/m²
Paper Type		Plain, Thick, Coated, Recycled, Colour, Label, Postcard, Envelope
CONNECTIVITY AND SOF	TWARE	
	Wired	USB 2.0 High Speed, 10Base-T/100Base-TX/1000Base-T
Standard Interface		
NEO	Wireless	Wi-Fi 802.11b/g/n (Infrastructure mode, WPS easy Setup, Direct Connection)
NFC Network Protocol		Yes (Passive) Print: LPD, RAW, WSD-Print (IPv4,IPv6) TCP / IP Application Services: Bonjour(mDNS), HTTP. HTTPS, POP before SMTP (IPv4,IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6) Management: SNMPv1, SNMPv3 (IPv4,IPv6)
Network Security	Wired	IP/Mac address filtering, HTTPS, SNMPv3, IEEE802.1x, IPSEC
	Wireless	WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)
Mobile Solution	Wileless	· , , , ,
		Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple® AirPrint®, Mopria® Print Service
Other Features Compatible Operating Systems		Department ID, Secure Print, Application Library Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008 R2,
		Windows Server® 2008,Mac® OS X 10.9.5 & up (*1), Linux (*1)
Software Included		Printer driver, Toner Status
GENERAL		
Device Memory		1 GB
LCD Display		WVGA Colour LCD 5.0" Touch Screen Display
Dimensions (W × D × H)		476 x 469 x 379 mm
Weight		19.0 kg
	Maximum	1,360 W or less
Power Consumption Noise Level(*2)		
	During Operation (Avg.)	Approx. 470 W
	During Standby (Avg.)	Approx.17.0 W
	During Sleep (Avg.)	Approx. 0.6 W (USB / LAN / Wi-Fi)
	During Operation	Sound Pressure Level: 49 dB, Sound Power Level: 70.5 dB
	During Standby	Sound Pressure Level: 28 dB, Sound Power Level: 43 dB
Operating Environment		Temperature: 10 - 30°C, Humidity: 20% - 80% RH (no condensation)
Power Requirement		AC 220 - 240 V (±10%), 50 / 60 Hz (±2 Hz)
	Standard	Cartridge 055 BK: 2,300 pages (bundled: 1,200 pages), Cartridge 055 C/M/Y: 2,100 pages (bundled: 1,200 pages)
Toner Cartridge(*3)		
	High	Cartridge 055H BK: 7,600 pages, Cartridge 055H C/M/Y: 5,900 pages
Monthly Duty Cycle ^(*4)		50,000 pages
OPTIONAL ACCESSORIES		
Paper Feeder		Cassette Feeding Unit-AF1 (550 Sheets)
Barcode ROM		Barcode Printing Kit-E1
MICard Attachment		Mi-Card Attachment Kit-B1

- *1 The latest drivers for Mac OS and Linux can be downloaded from the https://asia.canon website when available.
- *2 Tested in accordance to ISO 7779 and declared per ISO 9
 *3 Toner cartridge yield is in accordance with ISO/IEC 19798.

*4 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

Canon

Delighting You Always

South & Southeast Asia **Regional Headquarters**

Canon Singapore Pte. Ltd. 1 Fusionopolis Place, Singapore 138522 Tel: 65-6799 8888 Fax: 65-6799 8<u>882</u>

CANON OFFICES

INDIA Canon India Pvt Ltd. Tel: 91-124 416 0000 Fax: 91-124 416 0011 https://in.canon

MALAYSIA Canon Marketing (Malaysia) Sdn. Bhd. Tel: 60-3 7844 6000 Fox: 60-3 7845 0505 https://my.canon

PHILIPPINES Canon Marketing (Philippines), Inc. Tel: 632-884 9090 Fax: 632-556 1456 https://ph.canon

SINGAPORE Canon Singapore Pte. Ltd. Tel: 65-6799 8888 Fax: 65-6799 8882 https://sg.canon

THALLAND
Canon Marketing (Thailand) Co. Ltd.
Tel: 66-2 344 9999
Fox: 66-2 344 9960
https://th.canon

VIETNAM
Canon Marketing Vietnam Co. Ltd.
Tel: 84-8 3820 0466
Fax: 84-8 3820 0477
https://vn.canon

CANON BUSINESS PARTNERS

International Electronics
Concern (P) Ltd.
Tel: 977-1 4421991
Fax: 977-1 4421909
www.iec.com.np

PAKISTAN
Shirazi Trading Company
(Pvt.) Limited
Tet: (92-21)38704830-41,
35170851-54
Fax: (92-21)-35170860
Email: sto@stc.atlas.pk
www.stc.atlas.pk

Megaplus Pakistan Tel: 111 00 33 55 Fax: 92 51 222 8430 www.megaplus.com.pk

SRI LANKA
Metropolitan Office (Pvt) Ltd.
Tel: 94-11 470 0200
Fax: 94-11 470 0267
www.metropolitan.lk

Dealer's Stamp

0217W186 © 2019 Canon Singapore Pte. Ltd. All rights reserved.

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document.