

C3 – Assignment #3 – Web-based Data Analysis

The `ea-thesaurus-lower.json` word associations file (discussed in class) contains a dictionary of word associations for 8,210 individual words (as a single JSON file). When a word in the word associations dictionary is looked up, the associations are returned as a list of individual dictionaries which themselves associate another word with a score.

You are to build a webapp which allows its users to upload any file of textual data for analysis. Upon receiving the text file, your webapp processes the file as follows:

- The text in the file is converted to lowercase.
- Each individual word (i.e., token) in the text is looked-up in the word associations file.
- For each unique word found, the top three scoring associations are to be remembered.
- If a word is **not** found in the word associations file, this fact is to be remembered, too.
- For every word found (or not found), a frequency count for the word is to be provided.

Once an analysis is complete, your webapp needs to provide a mechanism which allows a user to look up any previous analyses results. It is not enough to provide the results of the most-recent analysis: you must provide a lookup mechanism which allows the user of your webapp to lookup the results of any previous analysis. Additionally, your system is to only preform an analysis on a text file when required: if a text file has already been processed by your webapp, its remembered results are to be looked-up and displayed (i.e., the analysis is **not** to be needlessly repeated). See overleaf for an example analysis (input and output).

Assignment Specification & Notes

1. Use Python 3 as your programming language on your web server (built with Flask), and use MongoDB as your backend database system. You are not required to store the word associations JSON file in MongoDB (unless you want to).
2. You are **not** required to host your solution on the cloud (on your computer is fine).
3. Be sure to test your solution.
4. E-mail your solution code (as a ZIP file) to `paul.barry@itcarlow.ie` by the due date/time.
5. This CA and is worth 15% of your final mark. While this CA is active, no new material will be presented in class. (Up to) 5 marks are for performing the analysis; 5 marks are for building the webapp to host the analysis; 5 marks are for providing the lookup service.
6. You may be required to demonstrate your system running on your computer (so be ready).
7. Due date: **Tuesday, February 7th 2017**. Due time: 5:00pm.
8. This is an **individual** assignment, which you are expected to work on, and submit, as an individual. If you decide to collaborate with a classmate, you **must** declare this when submitting your assignment (and the marks assigned to collaborators will be adjusted accordingly).

Example Analysis

Given the following text in a file:

```
There are examples, and there is The Correct Way to do something.
```

Start by converting the text to lowercase:

```
there are examples, and there is the correct way to do something.
```

Gotcha: how are you going to handle that comma and full-stop? How are you going to handle punctuation in general?

Convert the text to a list of tokens:

```
['there', 'are', 'examples,', 'and', 'there', 'is', 'the',  
'correct', 'way', 'to', 'do', 'something.']
```

Lookup each token in the word associations JSON dictionary and pull out the top three scores, noting any words which aren't found (note the frequency counts for each word provided in parentheses):

```
and (1) -> [{'but': '32'}, {'or': '15'}, {'so': '7'}]  
are (1) -> [{'you': '27'}, {'is': '15'}, {'not': '13'}]  
correct (1) -> [{'right': '38'}, {'wrong': '14'}, {'incorrect': '11'}]  
do (1) -> [{"don't": '22'}, {'not': '18'}, {'you': '6'}]  
is (1) -> [{'not': '25'}, {'was': '18'}, {'are': '8'}]  
something (1) -> [{'nothing': '28'}, {'else': '9'}, {'good': '8'}]  
the (1) -> [{'a': '16'}, {'end': '15'}, {'cat': '4'}]  
there (2) -> [{'here': '48'}, {'where': '11'}, {'then': '7'}]  
to (1) -> [{'from': '17'}, {'go': '12'}, {'be': '7'}]  
way (1) -> [{'out': '27'}, {'path': '14'}, {'road': '11'}]
```

```
examples (1) was not found in the associations list
```

Hints:

- Be sure to check the Flask documentation for how to upload a text file to a web server.
- Don't forget about the Counter module in the collections library.
- If you have a dictionary (or a Counter) called data, you can process an ordered version of it using `for k, v in sorted(data.items()): print(k, v)`
- The PyMongo documentation (especially the tutorial) is **required reading**.
- Advanced (and optional): the more adventurous of you may wish to consider using some of the facilities provided by NLTK (nltk.org).