

**CALL:** 1.800.296.4321

**EMAIL:** SERVICE@FOLDERS.COM

## **Sending Art Files:**



Check that artwork & layout matches specs quoted.

• Follow pre-design checklist

For files with attachments, compress into a .zip file format before sending.



Contact us for any questions,

• Call: 1.800.296.4321

• Email: Service@folders.com

# PRE-DESIGN CHECKLIST

#### Create Layout Files with the Following Programs (Mac or PC):

• InDesign • Illustrator • Photoshop • Corel Draw (convert type to curves)

Please note we cannot accept files created with: • Microsoft Publisher • Powerpoint • Word • PageMaker

#### **Send ALL Required Files & Art Elements:**

$\square$ Use "package" function in program to collect all elements used in file, including: fonts, graphics, logos, scans, etc.
☐ Vector art: convert type to outlines save as .EPS
<ul> <li>Images (photos): 300 dpi high-res for CMYK &amp; grayscale</li> <li>Save as .PSD or .TIF</li> <li>RGB low resolution (72 dpi) web graphics are not acceptable</li> </ul>
Scans: 1200 dpi, bitmap format save as .PSD or .TIF
If Sending a .PDF File as Artwork: Wrong template, missing bleed, low-quality graphics will be rejected  Spot color PMS (Pantone®) printing: use SPOT/PMS colors
☐ Four color process (full color) printing: use CMYK - NOT RGB ☐ For large black areas (not type), we suggest the following rich-black mix (C:60% M:40% Y:40% K:100%) ☐ Avoid "Blues that look Purple" See Pantone® Formula Guide or Pantone® Color Bridge (www.Pantone.com)
☐ Choose a blue formula with 30% more cyan than magenta
Foil Stamp & Emboss:
☐ Supply one color vector (.EPS) art: convert type to outlines
<b>Emboss:</b> thick, bold copy is better. Recommended minimum line thickness is 2 PT. Increase point size/line weight accordingly. Certain copy will not emboss well and should be avoided: serif/thick-thin type, screens, fine lines and copy with intricate detail.

### **Avoid Errors & Job Delays:**

Proofread & test print your files: print color separations; print a reduced copy, cut-out & fold up...does copy fall on correct panels? Additional charges apply if we need to modify your files. **We are not responsible for errors in supplied files.** 

**Foil Stamp:** For most type styles, minimum point size is 8 PT. Increase size for serif/thick-thin styles. To avoid loss of detail and plugging do not use ultra-light type styles, screens, thin lines and copy with intricate detail and gaps no closer than 1 pt.