

FEATURE DEMO • DEBUG OVERLAY

See the boxes your layout is made of.

Set `debug: on` in the front matter and every preview — Playground, Drawing Board,

Studio — outlines each box by its **layout mode**; **hover** one to read its label.

It travels with the deck, and it is **stripped from every export**, so a boardroom PDF is byte-identical whether debug is on or off.

Read the grid at a glance.

At rest you see only the outlines — each box colored by how it lays its children out: **grid** (blue), **flex** (vermillion), **flow** (gray). **Hover** any box to reveal its label (and its containers') in full detail. Want the whole map pinned on at once instead? Use `debug: always`.

Tool A • Chorus

- ✓ Speed
- ✗ Auditability
- ✓ Adoption
- ✗ Calibration

Strong call recording and summarization. No decision logging or calibration loop.

Tool B • Productboard

- ✗ Speed
- ✓ Auditability
- ✓ Adoption
- ✗ Calibration

Solid intake and prioritization. Decision logging is manual and rarely used.

Tool C • Notion

- ✓ Speed
- ✓ Auditability
- ✗ Adoption
- ✗ Calibration

Flexible enough to build the whole system — but the result is fragile to maintain.

Tool D • Sprig + Decision Log

- ✓ Speed
- ✓ Auditability
- ✓ Adoption
- ✓ Calibration

Meets all four criteria within the weekly budget. Recommended.



Pull every lever on one slide.

`<!-- _debug: all -->` turns on the full set — `identity · layout · size · class · box` — for **this slide only**. The deck-wide `debug: on` stays the default everywhere else; a spot directive just overrides the box it sits on.

Sizes are the **intrinsic** pixel box, read straight off the layout — not the scaled-down thumbnail you see in the filmstrip.

`class` shows the raw CSS classes; `box` shows padding + gap. Both are opt-in, because on a dense slide they are more than you usually want to read.

Mute a slide you have already checked.

`←!— _debug: off →` silences the overlay on one slide even while the deck is debugging — handy once a layout is settled and the boxes are just noise.

Because labels are summoned by default, a busy grid never becomes a wall of chips: you pull detail in only where you look — **hover** on desktop, **tap** on touch — one box (and its containers) at a time.

Debug in the preview. Ship it clean.

`debug: on` is an authoring aid, not a deck style — the engine strips it from the PDF, PPTX, and HTML exports, so it can never end up in front of a board.