

STATEMENT • PANEL • STRUCTURE

wifi

A network join card: readable Wi-Fi credentials beside a QR a phone scans to connect in one tap.

ROOM WI-FI

Join the room.



• SCAN TO CONNECT

NETWORK

Offsite-Guest

PASSWORD

boardroom2026

SECURITY

WPA2 · type it if you prefer

ROOM WI-FI

Join the room.



• SCAN TO CONNECT

NETWORK

Offsite-Guest

PASSWORD

boardroom2026

SECURITY

WPA2 · type it if you prefer

ROOM WI-FI

Join the room.



• SCAN TO CONNECT

NETWORK

Offsite-Guest

PASSWORD

boardroom2026

SECURITY

WPA2 · type it if you prefer

ROOM WI-FI

Join the room.



• SCAN TO CONNECT

NETWORK

Offsite-Guest

PASSWORD

boardroom2026

SECURITY

WPA2 · type it if you prefer

When NOT to reach for wifi.

Not for secrets that outlive the room.

A rendered deck is persistent and shareable. Use it for guest/offsite networks, not for credentials that must not leak.

Don't bold the field values.

The value leads and the key is a trailing inline-code tag —

```
- Offsite-Guest ssid`. Don't write
```

```
- **SSID:** Offsite-Guest
```

; the transform reads the postfix key, not a bold label.

RELATED COMPONENTS

See also.

`contact` — the card is a person's identity rather than a network