

14. Array Minimum swaps required bring elements less equal K together

```
class Solution{
```

```
public:
```

```
    int minSwap(vector<int> &arr, int k) {
```

```
        int n = arr.size();
```

```
        // Count elements <= k
```

```
        int count_good = 0;
```

```
        for(int i = 0; i < n; i++){
```

```
            if(arr[i] <= k)
```

```
                count_good++;
```

```
        }
```

```
        if(count_good == 0) return 0;
```

```
        // Count bad elements in first window
```

```
        int bad = 0;
```

```
        for(int i = 0; i < count_good; i++){
```

```
            if(arr[i] > k)
```

```
                bad++;
```

```
        }
```

```
        int ans = bad; // Sliding window
```

```
        for(int i = 1, j = count_good; j < n; i++, j++){ if(arr[i-1] > k) bad--; if(arr[j] > k) bad++  
ans = min(ans, bad);    } return ans;    };
```

```
1- class Solution{  
2- public:  
3-     int minSwap(vector<int> &arr, int k) {  
4-  
5-         int n = arr.size();  
6-  
7-         // Count elements <= k  
8-         int count_good = 0;  
9-         for(int i = 0; i < n; i++){  
10-             if(arr[i] <= k)  
11-                 count_good++;  
12-         }  
13-  
14-         if(count_good == 0) return 0;  
15-  
16-         // Count bad elements in first window  
17-         int bad = 0;  
18-         for(int i = 0; i < count_good; i++){  
19-             if(arr[i] > k)  
20-                 bad++;  
21-         }  
22-  
23-         int ans = bad;  
24-  
25-         // Sliding window  
26-         for(int i = 1, j = count_good; j < n; i++, j++){  
27-             if(arr[i-1] > k) bad--;  
28-             if(arr[j] > k) bad++;  
29-             ans = min(ans, bad);  
30-         }  
31-  
32-         return ans;  
33-     }  
34- };
```