

24. Row with max 1s

```
class Solution {
public:
    int rowWithMax1s(vector<vector<int>> &arr) {
        int n = arr.size();
        if (n == 0) return -1;
        int m = arr[0].size();
        if (m == 0) return -1;
        int bestRow = -1;
        int row = 0, col = m - 1;
        while (row < n && col >= 0) {
            if (arr[row][col] == 1) {
                // This row has a 1 at 'col', so it has (m - col) ones.
                bestRow = row; // latest row that reaches further left with a 1
                col--; // try to find an earlier 1 in same row
            } else {
                // arr[row][col] == 0 -> this row can't have 1s at any index <= col
                row++; // move to next row
            }
        }
        return bestRow;
    }
};
```

The screenshot displays a C++ IDE interface. On the left, the 'Output Window' shows 'Compilation Results' for 'Y.O.G.I. (AI Bot)'. It indicates 'Problem Solved Successfully' with 11/11 test cases passed, 1/1 attempts correct, 100% accuracy, 4/4 points scored, and a time taken of 0.09 seconds. The 'Solve Next' section lists 'Max sum in the configuration', 'Boolean Matrix', and 'Row with Minimum 1s'. On the right, the C++ code for the 'rowWithMax1s' function is shown, matching the code provided in the text above. The code uses a while loop to traverse the matrix from the bottom-right towards the top-left, updating the best row whenever a 1 is found.