3D Data Science with Python

Sergio Peral · ML Engineer, Teqyard



3D used to mean C++. Not anymore

C++ with PCL

```
using Cloud =
    pcl::PointCloud<pcl::PointXYZ>;
Cloud::Ptr cloud(new Cloud);
Cloud down;
if (pcl::io::loadPCDFile(
    "crop.pcd", *cloud)) return 1;
pcl::VoxelGrid<pcl::PointXYZ> vg;
vg.setInputCloud(cloud);
vg.setLeafSize(0.5f, 0.5f, 0.5f);
vg.filter(down);
std::cout << cloud->size()
  << " -> " << down.size() << "\n";


# output
722961 -> 230519
```

Python with Open3D

```
pcd = o3d.io.read_point_cloud(path)
down = pcd.voxel_down_sample(0.5)
print(len(pcd.points), "->",
      len(down.points))



# output
722961 -> 232180
```

The Python 3D ecosystem at a glance



Blue outline: used in today's pipeline. Logos belong to their owners; no endorsement implied. 119 libraries checked on PyPI and GitHub: docs/ECOSYSTEM.md in the repo.

Today's case: the Jaarbeurs hall, from a plane



The data set

Area	200 m × 200 m
Points	722 961
Density	about 18 per m²
Source	AHN5, ahn.nl
Flown	April 2023, night
File	LAZ, 4.3 MB
Coordinates	RD New + NAP
Licence	CC BY 4.0


Goal: ground, buildings, vegetation, street furniture; scored against AHN.

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

A point cloud is just an N×3 array

```
>>> import laspy
>>> las = laspy.read("crop.laz")
>>> las.xyz.shape
(722961, 3)
>>> las.classification[:5]
array([6, 6, 6, 6, 6], dtype=uint8)
```

Plus one column per attribute:
intensity, returns, class.



Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

Four rules of thumb for 3D data

1 Think in arrays, not points

A point cloud is an N×3 table plus attribute columns.

2 Look before you compute

Render it; check units, coordinates and classes.

3 Make it small first

Crop, tile and downsample; scale up last.

4 Let compiled code loop

One call per array or tile, never per point.

No single library does the whole job

Load	Voxel downsampling	Ground removal	Clustering	Labelling	Visualisation
laspy LAS/LAZ in and out	**Open3D** downsampling, planes, DBSCAN				**PyVista** off-screen renders
			SciPy KDTree batch neighbour queries		
NumPy the arrays every step passes on					


Not in this pipeline

trimesh
meshes, hulls, oriented boxes

PyTorch3D
differentiable 3D for training


laspy loads, Open3D computes, PyVista draws


laspy → **NumPy** → **Open3D** → **PyVista**



```
     x      y     z
199.6  199.9  26.3
199.2  199.9  26.4
199.4  199.7  26.4
  ...    ...   ...

(722961, 3)
float64
```






reads the LAZ file | holds the N×3 array | voxels and clusters | draws the result


Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

Python passes the array, not the points



copy

new memory: costs time and RAM



view


same memory: free, writes show through

`las.xyz`	**copy**	new array, every access
`Vector3dVector(xyz)`	**copy**	float32: 39× slower
`np.asarray(pcd.points)`	**view**	writes reach the point cloud
`pv.PolyData(pts)`	**view**	same memory as pts

Each xyz copy costs 24 B per point: 0.5 GB per 1 km AHN file.

Conditions: Ryzen 7 5700X, Python 3.13.15, NumPy 2.5.3; 722 961 points, median of 7 runs; AHN5 crop (CC BY 4.0). Full: results/python_facts.json.

Six steps turn a point cloud into labels




Load	**Voxel downsampling**	**Ground removal**	**Clustering**	**Labelling**	**Visualisation**
laspy	Open3D	Open3D	Open3D, SciPy	NumPy, SciPy	SciPy, PyVista

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

1 Load:
laspy hands you NumPy

```python
import laspy
import open3d as o3d
las = laspy.read("crop.laz")
xyz = las.xyz - las.header.mins
v = o3d.utility.Vector3dVector(xyz)
pcd = o3d.geometry.PointCloud(v)
```

Subtract a local origin before anything else.



Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

2 Voxel downsampling: one average per voxel

```
down = pcd.voxel_down_sample(0.5)
P = np.asarray(down.points)
print(len(xyz), "->", len(P))
```

722 961 points in,
232 180 out at 0.5 m voxels.




Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

3 Ground removal: one plane per tile

```
o3d.utility.random.seed(0)
ground = np.zeros(len(P), bool)
for i in tiles(P, 25):
    z0 = np.percentile(P[i, 2], 2)
    low = i[P[i, 2] < z0 + 1.5]
    t = down.select_by_index(low)
    _, inl = t.segment_plane(
        0.4, 3, 300,
        probability=1.0)
    ground[low[inl]] = z0 < 5
```

Scored against AHN's ground:
98 % precision, 94 % recall.




Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

4 Clustering: DBSCAN groups what touches

```
hag = height_above(P, ground)
up = ~ground & (hag > 0.3)
rest = down.select_by_index(
    np.flatnonzero(up))
lab = rest.cluster_dbscan(
    eps=0.75, min_points=6)
ids = np.asarray(lab)
print(ids.max() + 1, "clusters")
```

1 024 clusters. Clusters are not labels yet.




Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

5 Labelling: rules name the clusters

```
def name(c):
    if c.multi > 0.4 and c.top > 1:
        return VEGETATION
    if c.foot > 25 and c.top > 2.5:
        return BUILDINGS
    if c.to_building < 2:  # facade
        return BUILDINGS
    if c.slender and c.free:
        return STREET_FURNITURE
    return UNLABELLED
```

Leaf-off scan: bare trees echo several times.



Street furniture: 3 objects, 53 points, drawn enlarged. Poles nearly vanish.

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.


6 Visualisation: PyVista paints every point

```
P = np.asarray(down.points)
_, j = KDTree(P).query(
    xyz, workers=-1)
pl = pv.Plotter(off_screen=True)
pl.add_points(xyz, point_size=3,
    scalars=RGB[cls[j]], rgb=True)
pl.camera_position = CAM
pl.screenshot("f6_final.png")
```

Fixed camera, off-screen, one PNG per step.

Street furniture: 3 objects, 53 points, drawn enlarged. Poles nearly vanish.

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.




What the six steps did


Step	Library	Result	Time
Load	laspy	722 961 points	57 ms
Voxels	Open3D	232 180 voxels	84 ms
Ground	Open3D	98 % precision	81 ms
Clusters	Open3D	1 024 clusters	137 ms
Labels	NumPy	4 classes	151 ms
Paint-back	SciPy	all points	99 ms

0.6 s from file to labels, and no loop over points.

One run, indicative; renders not included. Street furniture drawn enlarged.

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.





Expectation vs reality: street furniture

Expectation: the BGT register

61 poles

51 lamp posts, 10 bollards

Reality: our pipeline

3 objects

2 of them on a lamp post

42 of 61 poles get no LiDAR point above 1.5 m.



2021 · Robot8A · CC BY-SA 4.0



2014 · V. van Werkhooven · CC BY 3.0

Poles: BGT (Kadaster, CC BY 4.0) via PDOK, 2026-10-12. Points: within 0.6 m, over 1.5 m above ground. Photos: Jaarbeursplein, Wikimedia Commons.

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.

Quiz: which is faster, and by how much?

Distance of every point to the ground plane, 722 961 points.

A

```
a, b, c, d = plane
h = np.empty(len(P))  # distances
for i, p in enumerate(P):
    x, y, z = p[0], p[1], p[2]
    h[i] = abs(a*x + b*y + c*z + d)
```

B

```
a, b, c, d = plane
x, y, z = P.T  # columns, no copy
h = np.abs(a*x + b*y + c*z + d)
```


The faster one wins by about:

2× 10× 100× 1000×

Both give identical results (np.array_equal). P: the crop's xyz from slide 11, column-ordered. plane: one seeded segment_plane on the whole crop.

How much slower is the loop over rows?


130× slower



Same data, same answer, far fewer calls into compiled code.

Conditions: Ryzen 7 5700X, Python 3.13.15, NumPy 2.5.3; 722 961 points, median of 7 runs; AHN5 crop (CC BY 4.0). Full: results/bench_cliff.json.

Every trip into compiled code pays a toll




439 ns per loop step (several NumPy calls)

C++ libraries too: even an empty k = 16 KDTree query costs 9.8 µs.

Conditions: Ryzen 7 5700X, Python 3.13.15, NumPy 2.5.3; 722 961 points, median of 7 runs; AHN5 crop (CC BY 4.0). Full: results/bench_cliff.json.

Profile before you vectorise

```
$ scalene run --cpu-only loop.py
```



The loop's last line takes 88 % of the run. As one NumPy expression: 0.7 %.


Conditions: Ryzen 7 5700X, Python 3.13.15, Scalene 2.3.0 (--cpu-only, a sample every 1 ms); 722 961 points, both versions 30 times per run, median of 3 runs; AHN5 crop (CC BY 4.0). Shares are of the whole run, imports and reading the file included. Full: results/profile_scalene.json.

Will free-threaded Python save my loop?


5.5×

faster on 8 free threads

With the GIL, threads gain nothing; one NumPy call is still 27× faster.



Conditions: Ryzen 7 5700X, CPython 3.14.7 free-threaded and 3.14.7, NumPy 2.5.4; 722 961 points, median of 7 runs; AHN5 crop (CC BY 4.0). Full: results/bench_freethreaded.json.



Loading this area's AHN file outgrows 32 GB

86 B

per point in our pipeline

926 203 338 points × 86 B each.

Bytes per point measured on the 1 km AHN file 135000_455000 (21 013 926 points); totals for 2023_C_31HZ2.LAZ computed, not run. Our pipeline: load and voxel downsampling (slides 11 and 12), all arrays kept, after gc.collect() and malloc_trim(0); peak 154 B per point.

It works on my machine (31.3 GiB RAM).

Conditions: Ryzen 7 5700X, Python 3.13.15, NumPy 2.5.3; 21 013 926 points, median of 3 runs, each in a fresh process; AHN5 1 km file (CC BY 4.0). 1 GB = 2^{30} B. Full: results/memory.json.

Stream chunks, keep the first point per voxel


```
v, keys, pts = 0.5, [], []                          # voxel size: 0.5 m
with laspy.open(path) as f:
    lo, hi = f.header.mins, f.header.maxs           # local origin, extent
    dims = ((hi - lo) // v).astype(np.int64) + 1    # voxels per axis
    for c in f.chunk_iterator(1_000_000):           # a million points
        xyz = np.c_[c.x, c.y, c.z] - lo
        ijk = (xyz // v).astype(np.int64).T         # voxel index per axis
        key = np.ravel_multi_index(ijk, dims)       # one int64 per voxel
        k, first = np.unique(key, return_index=True)
        keys.append(k); pts.append(xyz[first])      # first per voxel
k, first = np.unique(np.concatenate(keys), return_index=True)
points = np.concatenate(pts)[first]                 # earliest chunk wins
```

3.0 GB → 0.8 GB

peak memory, 1 km AHN file

Conditions: Ryzen 7 5700X, Python 3.13.15, NumPy 2.5.3; 21 013 926 points, median of 3 runs, each in a fresh process; AHN5 1 km file (CC BY 4.0). 1 GB = 2^{30} B. Full: results/memory.json.

Why it works: memory over time



Profiled with Scalene. Load everything: memory follows the file. Chunked: memory follows what you keep.

Conditions: Ryzen 7 5700X, Python 3.13.15, Scalene 2.3.0; 21 013 926 points, median of 3 runs; AHN5 1 km file (CC BY 4.0). Scalene counts allocations, not resident memory (slide 25). Full: results/memory_scalene.json.

Six gotchas I hit building this

`read_point_cloud("x.laz")`	Empty cloud, no error
`pip install laspy`	LAZ files will not open
`xyz.astype(np.float32)`	1.6 cm steps in RD
`Vector3dVector(float32)`	39× slower copy
`segment_plane(seed)`	Differs unless probability=1
`classification == 1`	Class 1 is not trees

Take the four rules home

1 **Think in arrays, not points**

722 961 × 3, as views

slides 5, 9

2 **Look before you compute**

61 poles on the map, 3 found

slides 18, 27

3 **Make it small first**

3.0 GB → 0.8 GB peak

slides 12, 25, 26

4 **Let compiled code loop**

130× faster than a loop

slides 19 to 23

Copy the pipeline

Your loop is still running. Your coffee is cold.



github.com/Sloppy1999/pycon-nl-2026-3d-data-science

Sergio Peral
sergioperalgarijo99@gmail.com
github.com/Sloppy1999

Point cloud: AHN5, Actueel Hoogtebestand Nederland (ahn.nl), Het Waterschapshuis, CC BY 4.0. AHN file 135000_455000, cropped and processed.
Licence: creativecommons.org/licenses/by/4.0
[Optional: Title shared with F. Poux, 3D Data Science with Python, O'Reilly 2025; this talk is independent.]