

TABLE
THE SELECTED PROPERTIES IN FIVE DATASETS.

Dataset	Property	Type	Continuous	Description
Banking	account id	Int	No	Each account id represents a user's account.
	merchant id	Int	No	Each merchant id represents a merchant in a B2C transaction.
	place id	Int	No	Each place id represents an issuing area of banking cards used for transactions.
	time	String	Yes	The exact time when the transaction occurred.
	amount	Float	Yes	The amount of money transferred to the merchant in a B2C transaction.
	ip	String	No	Whether a commonly used IP address or not in a transaction.
	last result	Boolean	No	Judgment of the last transaction in the relevant account id.
	type	String	No	Each type represents a transaction of different type.
Kyoto	service	String	No	The connection's service type, e.g., http, telnet, etc.
	destination bytes	Int	Yes	The number of data bytes sent by the destination IP.
	count	Int	Yes	The number of connections whose source IP address and destination IP address are the same to those of the current connection in the past two seconds.
	same srv rate	Float	Yes	% of connections to the same service in count property address.
	error rate	Float	Yes	% of connections that have 'SYN' errors in count property.
	srv error rate	Float	Yes	% of connections that have 'SYN' errors in srv count (the number of connections whose service type is the same to that of the current connection in the past two seconds) property.
	dst host srv count	Int	Yes	Among the past 100 connections whose destination IP address is the same to that of the current connection, the number of connections whose service type is also the same to that of the current connection.
	dst host error rate	Float	Yes	% of connections that have 'SYN' errors in dst host count property.
Darknet	idle max	Int	Yes	The maximum amount of time time a flow was idle before becoming active.
	fwd seg size min	Int	Yes	The minimum size of segment in forward direction.
	bwd packet length min	Int	Yes	The minimum length of packet in backward direction.
	protocol	String	No	The captured protocols of network flow.
	idle mean	Int	Yes	The average amount of time time a flow was idle before becoming active.
	fwd init win	Int	Yes	The number of bytes in initial window in forward direction.
	fin flag count	Int	Yes	The number of flag FIN.
	subflow bwd bytes	Int	Yes	The number of bytes in a sub flow in backward direction.
Gowalla	bwd packet length max	Int	Yes	The maximum length of packet in backward direction.
	user	Int	No	The identification of a user check-in.
	check-in time	String	Yes	The occurrence time of a user check-in.
	latitude	Float	Yes	The latitude of a user check-in geolocation.
	longitude	Float	Yes	The longitude of a user check-in geolocation.
CICDDoS	location id	Int	No	The location identifier for a user check-in location.
	max packet length	Int	Yes	The maximum length of packet.
	fwd packet length max	Int	Yes	The maximum length of packet in forward direction.
	fwd packet length min	Int	Yes	The minimum length of packet in forward direction.
	average packet size	Int	Yes	The average size of packet.
	min packet length	Int	Yes	The minimum length of packet.
	fwd packets/s	Float	Yes	The average rate of packets in forward direction.
	min seq size forward	Int	Yes	The minimum size of segment in forward direction.
	protocol	String	No	The captured protocols of network flow.
	fwd header length	Int	Yes	The length of header in forward direction.
	fwd header length.1	Int	Yes	The length.1 of header in forward direction.