

[TECHNICAL SYNTHESIS: BIOTIC HARDWARE ARCHITECTURE]

Design Framework for Bio-Inspired Radiant Systems: NFMI Architecture and Tuning in the *ELF* Spectrum (12.5 Hz)

Author: Santi López Puiggené

DOI: <https://doi.org/10.17605/OSF.IO/N3PB7>

THEORETICAL FRAMEWORK SYNTHESIS

The evolution of human technological infrastructure toward low-entropy, high-sustainability models requires a departure from extractive manufacturing paradigms. This study proposes a design framework for transmission in the Extremely Low Frequency (ELF) band, introducing a novel mapping between biological morphology and ELF-compatible electromagnetic architectures, using the morphology of the MS 408 manuscript as a library of deterministic patterns. The MS 408 mapping is used strictly as a geometric abstraction layer, not as historical evidence. Rather than interpreting its botanical, balneological, and astronomical iconography linguistically, these elements are treated as functional layers of a wireless communication system.

The central hypothesis establishes a functional isomorphism between organic fractal geometries and the hardware components required to tune the *Schumann Resonance* at 12.5 Hz, proposing an architecture in which hardware emerges as an extension of doped biological structures rather than an external construct.

The system's theoretical viability is articulated through the functional scaling axiom $k = 100$, which acts as a bridge between micro-scale illustration geometry and macro-scale electromagnetic behavior. Under this framework, root-like and vascular structures are interpreted as fractal load inductors designed to maximize effective electrical length within constrained physical volumes. Given the near-zero radiation resistance of sub-wavelength emitters in the ELF range, the model shifts from conventional far-field radiation to a Near-Field Magnetic Induction (*NFMI*) coupling approach. To enable physical plausibility, the architecture incorporates ionic doping with manganese-zinc (MnZn) ferrites, increasing substrate permeability and reducing phase velocity to facilitate resonance with the Earth-ionosphere cavity.

The framework integrates thermodynamic regulation and network synchronization into a unified operational system. The manuscript's balneological section is interpreted as a *thermal support layer*, where heat dissipation from induced currents is managed through ionic mass-flow cooling. This mechanism is essential for maintaining structural integrity under high inductive loads. In parallel, the pharmaceutical section defines a *materials layer* based on biomineralization processes that enable semi-conductive behavior and galvanic signal propagation. Signal emission and detection are modeled as a distributed *phased array*, coordinated through synchronization patterns derived from the astronomical section. These

temporal structures enable beamforming and constructive interference within the ionospheric waveguide, enhancing signal-to-noise ratio through distributed gain and coordinated spatial processing.

All physical constraints regarding radiation efficiency are addressed in the full model via NFMI coupling, distributed array gain, and substrate conduction. Aligned with contemporary electromagnetic theory, this framework establishes a conceptual basis for future Finite Element Analysis (*FEA*) simulations aimed at quantifying the network density required for practical implementation. The use of biomineralized magnetic cores and naturally occurring geometries outlines a potential pathway toward biodegradable, resilient communication infrastructures. Ultimately, this work explores whether bio-integrated technological systems can provide a viable route for sustainable advancement, reframing communication networks as extensions of planetary morphology and biological processes. In this paradigm, technology is not industrially manufactured, but cultivated and tuned in harmony with the Earth system, independent of the historical intent of the manuscript.