



Capacity 28kWh

sufficient to store the daily production of a small photovoltaic installation (up to 8kWp).

Safe LiFePO₄ chemistry

Lithium-iron-phosphate design without cobalt eliminates the risk of rapid temperature rise.

Top cell manufacturers

lifespan up to 6000 cycles.

Intelligent protection

The BMS prevents overcharging, excessive discharging, and ensures operation under optimal conditions.

Connection module

allows installation away from the photovoltaic inverter and distribution board.

Parallel connection

allows for an expansion of the energy storage system's capacity



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

TECHNICAL SPECIFICATION

Voltage and capacity

Nominal voltage	51.2V
Max. operating voltage range	42.0-58.4V
Nominal operating voltage range	48.0-54.4V
Capacity	560Ah 28.672kWh
Cycle life	≥ 6000 cycles*
Efficiency	94%
Configuration	2P16S

Operating conditions

Charge temperature	0°C~40°C
Discharge temperature	-5°C~40 °C
Storage < 3m	-5°C~35 °C
Storage > 6m	25°C
Humidity	5~80%
Altitude	<3000m

Charge and discharge

Model	28/60
Nominal charge current	180A
Max. charge current	200A**
Nominal charge power	9.21kW
Nominal discharge current	60A
Max. discharge current	60A
Nominal discharge power	3.072kW

Others

Dimensions HxWxD	829x800x280mm
Communication	CAN/RS485/Bluetooth
Weight	210 kg

*Under recommended operating conditions.

** At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

TECHNICAL SPECIFICATION

Voltage and capacity

Nominal voltage	51.2V
Max. operating voltage range	42.0-58.4V
Nominal operating voltage range	48.0-54.4V
Capacity	560Ah 28.672kWh
Cycle life	≥ 6000 cycles*
Efficiency	94%
Configuration	2P16S

Operating conditions

Charge temperature	0°C~40°C
Discharge temperature	-5°C~40 °C
Storage < 3m	-5°C~35 °C
Storage > 6m	25°C
Humidity	5~80%
Altitude	<3000m

Charge and discharge

Model	28/90
Nominal charge current	180A
Max. charge current	200A**
Nominal charge power	9.21kW
Nominal discharge current	90A
Max. discharge current	90A
Nominal discharge power	4.608kW

Others

Dimensions HxWxD	829x800x280mm
Communication	CAN/RS485/Bluetooth
Weight	210 kg

*Under recommended operating conditions.

** At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

TECHNICAL SPECIFICATION

Voltage and capacity

Nominal voltage	51.2V
Max. operating voltage range	42.0-58.4V
Nominal operating voltage range	48.0-54.4V
Capacity	560Ah 28.672kWh
Cycle life	≥ 6000 cycles*
Efficiency	94%
Configuration	2P16S

Operating conditions

Charge temperature	0°C~40°C
Discharge temperature	-5°C~40 °C
Storage < 3m	-5°C~35 °C
Storage > 6m	25°C
Humidity	5~80%
Altitude	<3000m

Charge and discharge

Model	28/140
Nominal charge current	180A
Max. charge current	200A**
Nominal charge power	9.21kW
Nominal discharge current	140A
Max. discharge current	140A
Nominal discharge power	7.168kW

Others

Dimensions HxWxD	829x800x280mm
Communication	CAN/RS485/Bluetooth
Weight	210 kg

*Under recommended operating conditions.

** At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

TECHNICAL SPECIFICATION

Voltage and capacity

Nominal voltage	51.2V
Max. operating voltage range	42.0-58.4V
Nominal operating voltage range	48.0-54.4V
Capacity	560Ah 28.672kWh
Cycle life	≥ 6000 cycles*
Efficiency	94%
Configuration	2P16S

Operating conditions

Charge temperature	0°C~40°C
Discharge temperature	-5°C~40 °C
Storage < 3m	-5°C~35 °C
Storage > 6m	25°C
Humidity	5~80%
Altitude	<3000m

Charge and discharge

Model	28/180
Nominal charge current	180A
Max. charge current	200A**
Nominal charge power	9.21kW
Nominal discharge current	180A
Max. discharge current	200A**
Nominal discharge power	9.21kW

Others

Dimensions HxWxD	829x800x280mm
Communication	CAN/RS485/Bluetooth
Weight	210 kg

*Under recommended operating conditions.

** At temperatures of 25 ± 2°C