



## Capacity 32kWh

sufficient to store the daily production of a small photovoltaic installation (up to 8kWp).

## Safe LiFePO<sub>4</sub> chemistry

Lithium-iron-phosphate design without cobalt eliminates the risk of rapid temperature rise.

## Top cell manufacturers

lifespan up to 8000 cycles.

## Intelligent protection

The BMS prevents overcharging, excessive discharging, and ensures operation under optimal conditions.

## Connection module

allows installation away from the photovoltaic inverter and distribution board.

allows for an expansion of the energy storage system's capacity



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

Home 32/190A  
TECHNICAL SPECIFICATION

Voltage and capacity

|                                 |                |
|---------------------------------|----------------|
| Nominal voltage                 | 51.2V          |
| Max. operating voltage range    | 42.0-58.4V     |
| Nominal operating voltage range | 48.0-54.4V     |
| Capacity                        | 628Ah   32kWh  |
| Cycle life                      | ≥ 8000 cycles* |
| Efficiency                      | 94%            |
| Configuration                   | 2P16S          |

Operating conditions

|                       |            |
|-----------------------|------------|
| Charge temperature    | 0°C~40°C   |
| Discharge temperature | -5°C~40 °C |
| Storage < 3m          | -5°C~35 °C |
| Storage > 6m          | 25°C       |
| Humidity              | 5~80%      |
| Altitude              | <3000m     |

Charge and discharge

|                        |         |
|------------------------|---------|
| Model                  | 32/190  |
| Max. charge current    | 190A**  |
| Max. charge power      | 9.728kW |
| Max. discharge current | 190A**  |
| Max. discharge power   | 9.728kW |

Others

|                  |                     |
|------------------|---------------------|
| Dimensions HxWxD | 829x800x280mm       |
| Communication    | CAN/RS485/Bluetooth |
| Weight           | 210 kg              |

\*Under recommended operating conditions.

\*\* At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

Home 32/150A  
TECHNICAL SPECIFICATION

Voltage and capacity

|                                 |                |
|---------------------------------|----------------|
| Nominal voltage                 | 51.2V          |
| Max. operating voltage range    | 42.0-58.4V     |
| Nominal operating voltage range | 48.0-54.4V     |
| Capacity                        | 628Ah   32kWh  |
| Cycle life                      | ≥ 8000 cycles* |
| Efficiency                      | 94%            |
| Configuration                   | 2P16S          |

Operating conditions

|                       |            |
|-----------------------|------------|
| Charge temperature    | 0°C~40°C   |
| Discharge temperature | -5°C~40 °C |
| Storage < 3m          | -5°C~35 °C |
| Storage > 6m          | 25°C       |
| Humidity              | 5~80%      |
| Altitude              | <3000m     |

Charge and discharge

|                        |         |
|------------------------|---------|
| Model                  | 32/150  |
| Max. charge current    | 190A**  |
| Max. charge power      | 9.728kW |
| Max. discharge current | 150A    |
| Max. discharge power   | 7.68kW  |

Others

|                  |                     |
|------------------|---------------------|
| Dimensions HxWxD | 829x800x280mm       |
| Communication    | CAN/RS485/Bluetooth |
| Weight           | 210 kg              |

\*Under recommended operating conditions.

\*\* At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

Home 32/90A  
TECHNICAL SPECIFICATION

Voltage and capacity

|                                 |                |
|---------------------------------|----------------|
| Nominal voltage                 | 51.2V          |
| Max. operating voltage range    | 42.0-58.4V     |
| Nominal operating voltage range | 48.0-54.4V     |
| Capacity                        | 628Ah   32kWh  |
| Cycle life                      | ≥ 8000 cycles* |
| Efficiency                      | 94%            |
| Configuration                   | 2P16S          |

Operating conditions

|                       |            |
|-----------------------|------------|
| Charge temperature    | 0°C~40°C   |
| Discharge temperature | -5°C~40 °C |
| Storage < 3m          | -5°C~35 °C |
| Storage > 6m          | 25°C       |
| Humidity              | 5~80%      |
| Altitude              | <3000m     |

Charge and discharge

|                        |         |
|------------------------|---------|
| Model                  | 32/90   |
| Max. charge current    | 190A**  |
| Max. charge power      | 9.728kW |
| Max. discharge current | 90A     |
| Max. discharge power   | 4.608kW |

Others

|                  |                     |
|------------------|---------------------|
| Dimensions HxWxD | 829x800x280mm       |
| Communication    | CAN/RS485/Bluetooth |
| Weight           | 210 kg              |

\*Under recommended operating conditions.

\*\* At temperatures of 25 ± 2°C



SECURITY FEATURES

- ✗ Single cell overvoltage
- ✗ Single cell undervoltage
- ✗ Battery pack overvoltage
- ✗ Battery pack undervoltage
- ✗ Battery pack overtemperature
- ✗ Battery pack undertemperature
- ✗ Overcurrent protection
- ✗ Overcharge and over-discharge protection
- ✗ Short-circuit protection

Home 32/60A  
TECHNICAL SPECIFICATION

Voltage and capacity

|                                 |                |
|---------------------------------|----------------|
| Nominal voltage                 | 51.2V          |
| Max. operating voltage range    | 42.0-58.4V     |
| Nominal operating voltage range | 48.0-54.4V     |
| Capacity                        | 628Ah   32kWh  |
| Cycle life                      | ≥ 8000 cycles* |
| Efficiency                      | 94%            |
| Configuration                   | 2P16S          |

Operating conditions

|                       |            |
|-----------------------|------------|
| Charge temperature    | 0°C~40°C   |
| Discharge temperature | -5°C~40 °C |
| Storage < 3m          | -5°C~35 °C |
| Storage > 6m          | 25°C       |
| Humidity              | 5~80%      |
| Altitude              | <3000m     |

Charge and discharge

|                        |         |
|------------------------|---------|
| Model                  | 32/60   |
| Max. charge current    | 190A**  |
| Max. charge power      | 9.728kW |
| Max. discharge current | 60A     |
| Max. discharge power   | 3.072kW |

Others

|                  |                     |
|------------------|---------------------|
| Dimensions HxWxD | 829x800x280mm       |
| Communication    | CAN/RS485/Bluetooth |
| Weight           | 210 kg              |

\*Under recommended operating conditions.

\*\* At temperatures of 25 ± 2°C