

Besov Spaces over Good Grids

Current Lean 4 Formalization

Daniel Smania

June 2026

Abstract

This document describes the current Lean 4 formalization in the `BesovSpacesGoodGrid` repository. The project develops a reusable weak-grid framework for atomic Besov-ish spaces, proves scale inclusions, representation-limit and compactness theorems, proves completeness for the coefficient-cost norm, and formalizes a substantial weak-grid transmutation pipeline. It also contains a good-grid specialization based on Souza atoms. The current good-grid layer also relates the standard atomic representation norm, the L^2 -normalized Haar representation norm, and the mean-oscillation norm by finite-constant comparison theorems. The principal public results are summarized in Section 10.

Contents

1	Introduction	3
1.1	Purpose of the Project	3
1.2	Current Pipeline	3
2	Grid Structures	4
2.1	Good Grids	4
2.2	Weak Grids	4
3	Atoms	5
3.1	Cells and Local Spaces	5
3.2	Atom Families	5
4	Besov-ish Spaces	6
4.1	Level Blocks	6
4.2	Representations and Costs	6
4.3	Besov-ish Space and Cost Gauge	6
5	Scale Inclusions	8
6	Representation Limits and Completeness	9
6.1	Analytic Grid Hypothesis	9
6.2	Limit Theorems	9
6.3	Compactness and Completeness	9

7	Weak-Grid Transmutation	10
7.1	Setup	10
7.2	Transmutation Objects	10
7.3	Claims	10
8	Good-Grid Souza Spaces	12
8.1	Besov Atoms and the Souza/Besov Comparison	13
8.2	Haar, Standard, and Mean-Oscillation Norms	13
9	Auxiliary Files	15
9.1	Distributions	15
9.2	Block-Sum Notation	15
9.3	Repository Status	15
10	Main Theorems	16
11	File Guide	17
12	Conclusion	18

1 Introduction

1.1 Purpose of the Project

The project formalizes part of the atomic decomposition theory from

Daniel Smania, *Besov-ish spaces through atomic decomposition*, Analysis & PDE 15 (2022), no. 1, 123–174.

The emphasis is on a Lean library that can be reused in later developments: the basic theory is first stated for weak grids and abstract atom families, and good-grid/Souza spaces are then obtained as a specialization.

1.2 Current Pipeline

The aggregate Lean file `BesovSpacesGoodGrid.lean` is intended to import the following pipeline:

1. define quantitative good grids and general weak grids;
2. package weak-grid cells and local Banach spaces;
3. define atom families with support, convexity, phase invariance, and atom-size estimates;
4. build levelwise atomic blocks and infinite L^p representations;
5. define the Besov-ish space and the coefficient-cost gauge `Norm_Costpq`;
6. prove scale constructions and a smoothness-scale inclusion;
7. prove representation-limit theorems, compactness statements, and completeness of the Besov-ish space for the cost norm;
8. prove transmutation claims moving atomic representations from one weak grid to another;
9. specialize the transmutation machinery to compare Souza atoms, Besov atoms, and atom families sandwiched between them on good grids;
10. introduce Haar and standard representation gauges on good grids and compare them with the mean-oscillation norm.

The repository also contains good-grid Souza-space results and auxiliary block-sum notation. At the date of this document the newest comparison modules check individually, while the aggregate root module still has an import/name organization issue involving `GoodGridSpace.GoodGridCell.toLevelCell`.

2 Grid Structures

2.1 Good Grids

Definition 2.1 (Good grid). The Lean structure

`GoodGridSpace.GoodGrid`

extends the grid structure from the `UnbalancedHaarWavelet` dependency. It adds constants $\lambda_1, \lambda_2 : \mathbb{R}$ with

$$0 < \lambda_1 \leq \lambda_2 < 1$$

and lower and upper measure-ratio estimates for a child cell s inside a parent cell t :

$$\lambda_1 \mu(t) \leq \mu(s), \quad \mu(s) \leq \lambda_2 \mu(t).$$

Definition 2.2 (Good-grid space). The structure

`GoodGridSpace.GoodGridSpace`

is the ambient object used by good-grid files. It consists of a measurable space with a fixed good grid. The associated measure is exposed as `GoodGridSpace.measure`.

2.2 Weak Grids

Definition 2.3 (Weak grid). The Lean structure

`WeakGridSpace.WeakGrid`

is a measure together with a sequence of finite cell families $\mathcal{P}^k$. Each cell is measurable and has positive measure; the whole measure is finite; at least one level is nonempty; and there is a uniform same-level overlap bound `Cmult1`.

The term “partition” appears in field names because of the mathematical source, but a weak grid does not require disjointness or covering. The important primitive is the overlap neighborhood

$$\Omega_Q^k = \{P \in \mathcal{P}^k : P \cap Q \neq \emptyset\},$$

implemented as `overlapFinset`.

Lemma 2.1 (Overlap double counting). The theorem

`WeakGridSpace.WeakGrid.overlap_double_sum_le`

states that if f is nonnegative on the level- k cells, then summing f over all overlap neighborhoods costs at most the multiplicity constant:

$$\sum_{Q \in \mathcal{P}^k} \sum_{P \in \Omega_Q^k} f(P) \leq C_{\text{mult}1} \sum_{P \in \mathcal{P}^k} f(P).$$

3 Atoms

3.1 Cells and Local Spaces

Definition 3.1 (Weak-grid cell). The structure

`WeakGridSpace.WeakGridCell`

bundles a level k , a set Q , and the proof that $Q \in \mathcal{P}^k$. The theorem `measurable` records that every such cell is measurable.

Definition 3.2 (Local Banach space). The structure

`WeakGridSpace.LocalBanachSpace`

packages a complex normed complete vector space together with an injective linear realization map into functions $\alpha \rightarrow \mathbb{C}$. This lets different cells carry different local model spaces.

3.2 Atom Families

Definition 3.3 (Atom family). The Lean structure

`WeakGridSpace.AtomFamily`

is the central abstraction for atomic decompositions. For parameters s, p, u , it records:

- (i) the Holder conjugate u' ;
- (ii) assumptions $s > 0$, $1 \leq p < \infty$, and $1 \leq u \leq \infty$;
- (iii) a local Banach space $B(Q)$ for every weak-grid cell Q ;
- (iv) a nonempty atom set $A(Q) \subset B(Q)$;
- (v) membership of local functions in L^{pu} ;
- (vi) support inside Q ;
- (vii) convexity and phase invariance of the atom set;
- (viii) the atom-size estimate

$$\|a\|_{L^{pu}} \leq \mu(Q)^{s-1/(u'p)}.$$

The namespace `AtomFamily` exposes convenience definitions and lemmas: `toFunction`, `IsAtom`, `AtomsOn`, `allAtoms`, `atom_memLp`, `local_memLp_p`, `atom_support`, and `atom_norm_bound`. It also records optional compactness and finite-dimensional hypotheses: `StronglyCompactAtoms`, `WeaklySequentiallyCompactAtoms`, and `FiniteDimensionalAtoms`.

4 Besov-ish Spaces

4.1 Level Blocks

Definition 4.1 (Level block). For an atom family A , the structure

$$\text{WeakGridSpace.LevelBlock } A \ k$$

chooses one coefficient and one atom for each cell of the level k . Its value in L^p is the finite sum over that level:

$$\sum_{Q \in \mathcal{P}^k} c_Q a_Q.$$

Lean names this value `LevelBlock.toLp`.

The file proves that zero and scalar multiples of level blocks behave as expected. It also proves basic closure properties of the set `LevelBlockSet A k`.

4.2 Representations and Costs

Definition 4.2 (Atomic representation). The structure

$$\text{WeakGridSpace.LpGridRepresentation } A \ g$$

is a sequence of level blocks whose infinite sum is g in L^p :

$$\text{HasSum } (k \mapsto \text{toLp}(B_k)) (g).$$

Definition 4.3 (Coefficient cost). For a representation R , Lean defines `levelCoeffPower`, `lpCost`, `pqCost`, and `pqCostENNReal`. The finite-cost predicate is

$$\text{LpGridRepresentation.FinitePQCost}.$$

It is the formal version of the usual (p, q) -coefficient summability condition, with the endpoint $q = \infty$ represented by a supremum bound.

4.3 Besov-ish Space and Cost Gauge

Definition 4.4 (Besov-ish membership). The predicates

$$\text{MemBesovish}, \quad \text{MemBesovishCoeffCost}$$

say that an L^p function admits an atomic representation, respectively an atomic representation with finite (p, q) -coefficient cost.

Definition 4.5 (Besov-ish space). The Lean definition

$$\text{WeakGridSpace.BesovishSpace } A \ q$$

is the complex submodule of L^p consisting of elements satisfying `MemBesovishCoeffCost A q`.

Definition 4.6 (Coefficient-cost gauge). For $g \in \text{BesovishSpace } A \ q$, the gauge

$$\text{BesovishSpace.Norm_Costpq } A \ q \ g$$

is the infimum of the pqCost over all finite-cost representations of g .

Theorem 4.1 (Normed-space summary). The theorem

`BesovishSpace.normedSpace_and_lp_embedding`

packages the main structural facts about `Norm_Costpq`: nonnegativity, triangle inequality, homogeneity, a named cost-normed group/space structure, and an explicit L^t embedding estimate for exponents

$$p \leq t \leq pu.$$

5 Scale Inclusions

Definition 5.1 (Smoothness scaling). The file `WeakGrid/Scales.lean` defines

`smoothnessScaleFactor`, `smoothnessScaleAtoms`, `smoothnessScaleAtomFamily`.

These rescale atoms cell by cell by the deterministic factor

$$\mu(Q)^{\tilde{s}-s}.$$

Definition 5.2 (Smoothness-integrability scaling). When $u = \infty$, the file also defines the two-parameter scaling

`smoothnessIntegrabilityScaleAtomFamily`.

The scale factor is

$$\mu(Q)^{\tilde{s}-s+1/p-1/\tilde{p}}.$$

Theorem 5.1 (Smoothness-scale inclusion). The theorem

`smoothnessScaleBesovishSpace_subset`

shows that, under the deterministic summability hypothesis `scaleCoefficientFinite` and the monotonicity assumption $s \leq \tilde{s}$, the Besov-ish space for the smoothness-scaled atom family is contained in the original Besov-ish space.

Theorem 5.2 (Linear inclusion and cost bound). The definition

`smoothnessScaleBesovishSpaceInclusion`

packages the preceding set inclusion as a linear map. The theorem

`smoothnessScaleBesovishSpaceInclusion_Norm_Costpq_le`

gives the corresponding explicit bound for the cost gauge.

6 Representation Limits and Completeness

6.1 Analytic Grid Hypothesis

Definition 6.1 (Assumption G2). The predicate

`WeakGridSpace.AssumptionG2 G s p u q`

combines two requirements:

- (i) the coefficient-weight series needed for the $t = p$ embedding is finite;
- (ii) the maximal measure of cells at level k tends to zero as $k \rightarrow \infty$.

This hypothesis is used to control tails of atomic representations uniformly.

6.2 Limit Theorems

Theorem 6.1 (Representation limit). The theorem

`representation_limit`

formalizes the weak L^p version of Proposition `compa2` from the development. If representations have uniformly bounded coefficient cost, their coefficients converge cellwise, and their atoms converge weakly, then the limiting blocks define a Besov-ish function with the same cost bound and the represented functions converge weakly.

Theorem 6.2 (Strong representation limit). The theorem

`representation_limit_strong`

is the strong L^p version: strong convergence of the atoms gives strong convergence of the represented functions.

The existence theorems `representation_limit_strong_existence` and `representation_limit_w` start from a bare limit block sequence, prove it is summable, and package the resulting limit as a genuine representation.

6.3 Compactness and Completeness

Theorem 6.3 (Formal block summability). The theorem

`formalBlockSeq_summable`

says that under `AssumptionG2`, any formal block sequence with finite abstract (p, q) -cost is summable in L^p .

Theorem 6.4 (Closed cost balls). The theorem

`closed_Norm_Costpq_ball_strongly_seqCompact`

proves sequential compactness of closed coefficient-cost balls in the ambient strong L^p topology, assuming the compactness hypothesis `AssumptionA5`.

Theorem 6.5 (Completeness). The theorem

`besovishSpace_costNorm_completeSpace`

states that `BesovishSpace A q`, endowed with the local `costNormedAddCommGroup` structure associated to `Norm_Costpq`, is complete.

7 Weak-Grid Transmutation

7.1 Setup

The file `WeakGrid/Transmutation.lean` formalizes the transfer of an atomic representation from a source weak grid G to a target weak grid W . The source coefficients are measured by `CoeffPLevel`, `CoeffPQCost`, and `CoeffFinitePQCost`.

Definition 7.1 (Almost linear level selector). The predicate

`AlmostLinearSequence k`

says that the target level $k(i)$ attached to a source level i stays between two affine functions with the same positive slope:

$$ri + A \leq k(i) \leq ri + B.$$

It is used to prove finiteness of certain level interactions and to reduce coefficient estimates to convolution bounds.

Definition 7.2 (Representation hypothesis). The predicate

`RepresentationWsubGandALS`

records the structural hypothesis that every source atom has a target-grid atomic representation with localization, decay, and almost-linear level control.

7.2 Transmutation Objects

For each truncation level N , the file defines:

- `PartialSumLevels`: the source partial expansion;
- `TransmutationCoeff`: the target coefficient $m_{P,N}$;
- `TransmutationAtom` and `TransmutationAtomLocal`: the normalized target atoms $d_{P,N}$;
- `TransmutationBlock`: the target level block at level j .

It also defines stable limiting objects: `TransmutationCoeffLimit`, `TransmutationAtomLimit`, and `TransmutationBlockLimit`.

7.3 Claims

Theorem 7.1 (Claim I). The theorem

`ClaimI`

is the exact bookkeeping identity. The transmuted target representation at truncation N sums to the source partial expansion `PartialSumLevels ... N`. The theorem `ClaimI_top` is the endpoint $q = \infty$ version.

Theorem 7.2 (Claim II). The theorem

ClaimII

states that each finite transmutation block sequence is a genuine Besov-ish representation of the source partial expansion and that its (p, q) -cost is bounded by the source coefficient cost times explicit geometric, decay, and convolution constants. The theorem `ClaimII_top` treats the endpoint $q = \infty$.

Theorem 7.3 (Claim III). The theorem

ClaimIII

passes to the stable limiting transmutation data. It produces an L^p -limit g_∞ , proves that the stable blocks form a Besov-ish representation of g_∞ , and proves strong convergence of the truncated source sums to that limit. The theorem `ClaimIII_top` is the endpoint version.

Theorem 7.4 (Identity-level Claim C constant). For the identity level selector used in the good-grid Besov-atom comparison, the theorem

`LpGridRepresentation.cCoefficientInt_transmutationKernelZ_zero_one`

computes the integer transmutation coefficient of the Claim C kernel as the ordinary geometric sum:

$$C_{co, \mathbb{Z}}(p, \infty, n \mapsto \lambda^n \mathbf{1}_{n \geq 0}) = (1 - \rho)^{-1}, \quad \lambda = \rho^p.$$

This is the constant simplification used in the final Souza/Besov atom comparison.

8 Good-Grid Souza Spaces

The file `GoodGrid/BesovSpace.lean` specializes the weak-grid theory to good grids and Souza atoms.

Definition 8.1 (Induced weak grid). The definition

`GoodGridSpace.toWeakGrid`

turns a good grid into a weak grid. Since good-grid partitions are disjoint, the same-level overlap multiplicity is 1. The induced weak-grid space is `GoodGridSpace.toWeakGridSpace`.

Definition 8.2 (Souza atoms). The predicate

`GoodGridSpace.IsSouzaAtom`

says that an atom is supported on a good-grid cell, is constant on that cell, and has size at most

$$\mu(Q)^{s-1/p}.$$

The definitions `canonicalSouzaAtom`, `souzaLocalBanachSpace`, `souzaAtomsSet`, and `souzaAtomFamily` package these atoms as an `AtomFamily` with $u = \infty$.

Definition 8.3 (Souza Besov space). The definition

`GoodGridSpace.SouzaBesovSpace`

is the Besov-ish space associated to the Souza atom family on the weak grid induced by the good grid.

Theorem 8.1 (Good-grid completeness). The theorem

`souzaBesovSpace_costNorm_completeSpace`

specializes the weak-grid completeness theorem to Souza atoms on a good grid.

Theorem 8.2 (Compact balls). Theorems

`souza_closedCostBallInLp_isSeqCompact`,
`souza_closedCostBallInLp_isCompact`, `souza_closedCostBallInL1_isCompact`

state compactness of closed cost balls in the ambient L^p topology and, after the finite-measure inclusion, in L^1 .

Theorem 8.3 (Density). Theorems

`souzaBesovSpace_dense`, `souzaBesovSpace_dense_inL1`

prove density of the Souza Besov space in the ambient L^p space and density of its image in L^1 .

8.1 Besov Atoms and the Souza/Besov Comparison

The file `GoodGrid/BesovAtoms.lean` introduces Besov atoms on a good grid. A Besov atom on a cell Q is a function supported on Q whose induced Besov-ish norm of order β is controlled by the scale $\mu(Q)^{s-\beta}$. The construction is phrased using induced weak grids and the transmutation API.

Definition 8.4 (Besov-atom normalizing constant). The definition

`besovAtomConstant`

is the geometric normalizing constant for Besov atoms. The theorem `besovAtomConstant_nonneg` proves nonnegativity, and `one_le_besovAtomConstant` proves the lower bound $1 \leq \text{besovAtomConstant}$, which is used to simplify the final Claim C constant.

Theorem 8.4 (Besov atom to Souza representation). The theorem

`besovAtom_to_induced_souzaS_representation_decay_claimC`

packages the paper's transmutation claim for a single Besov atom: after passing to the weak grid induced on its supporting cell, the atom admits a Souza-atom representation with geometric coefficient decay

$$(\lambda_2^{\beta-s})^{pk}.$$

Theorem 8.5 (Souza atoms and Besov atoms). The theorem

`atoms_between_souza_atoms_and_besov_atoms`

formalizes the sandwich proposition. If an atom family A lies between Souza atoms and Besov atoms, then the Besov-ish spaces generated by Souza atoms, by A , and by Besov atoms are equal. The theorem also gives the continuous norm bounds

$$\|f\|_A \leq C_1 \|f\|_{\text{Souza}}, \quad \|f\|_{\text{Souza}} \leq \frac{C_2}{1 - \lambda_2^{\beta-s}} \|f\|_A.$$

The second inequality is obtained by applying explicit Claim C and the geometric-sum constant computation above.

8.2 Haar, Standard, and Mean-Oscillation Norms

The newer good-grid files formalize three analytic gauges associated with an integrable function f :

- the standard atomic representation norm `standardRepresentationNorm`;
- the L^2 -normalized Haar representation norm `haarL2RepresentationNorm`;
- the mean-oscillation norm `meanOscillationNorm`, built from a global L^p term and levelwise local oscillations.

Theorem 8.6 (Haar controls standard). The theorem

`exists_standardRepresentationNorm_le_const_mul_haarL2RepresentationNorm`

states that, for fixed good-grid data and parameters, the standard atomic representation norm is bounded by a finite constant times the Haar representation norm.

Theorem 8.7 (Finite standard norm endpoint). The theorem

`finite_standardRepresentationNorm_implies_memBesov_and_standardRepresentation`

packages the endpoint consequence of finite standard norm. It gives L^p membership, the canonical standard `LpGridRepresentation`, finite (p, q) -coefficient cost, and membership in the Souza Besov space, with the expected cost bounds.

Theorem 8.8 (Finite Haar norm endpoint). The theorem

`finite_haarL2RepresentationNorm_implies_memLp_and_hasSum`

states that finite Haar representation norm implies $f \in L^p$ and that the normalized Haar expansion has sum f in L^p .

Theorem 8.9 (Standard controls mean oscillation). The theorem

`exists_meanOscillationNorm_le_const_mul_standardRepresentationNorm`

proves the manuscript direction in which the standard representation norm controls the mean-oscillation norm. The proof separates the L^p term from the oscillation seminorm. The oscillation estimate uses the fact that low-frequency Souza blocks are constant on finer cells, so local oscillation is controlled by the high-frequency tail, followed by a geometric discrete convolution estimate.

Theorem 8.10 (Mean oscillation controls Haar). The theorem

`exists_haarL2RepresentationNorm_le_const_mul_meanOscillationNorm`

proves the reverse analytic comparison from mean oscillation to Haar norm. The cellwise estimate is the Lean analogue of testing $f - c_Q$ against the zero-mean Haar wavelets over a parent cell Q :

$$|d_S| \leq C \operatorname{osc}_p(f, Q) \mu(Q)^{1/p' - 1/2}.$$

After summing over branches and levels, this gives a finite constant C such that

$$\|f\|_{\text{Haar}} \leq C \|f\|_{\text{mean osc}}.$$

9 Auxiliary Files

9.1 Distributions

The file `GoodGrid/Distribution.lean` defines:

- `atomIndicator`: a simple-function indicator attached to a good-grid cell;
- `atomIndicators`: the set of all such indicators;
- `TestFunctions`: the real submodule spanned by the indicators;
- `Distributions`: the algebraic dual of the test-function module.

9.2 Block-Sum Notation

The file `Sums.lean` provides reusable indexing types and notation for block sums:

- `BlockIndex` for global pairs (k, Q) ;
- `ChildIndex` and `ParentIndex` for strict descendants and ancestors;
- `blockTsum`, `childTsum`, and `parentTsum`;
- notation such as `sumb`, `sum+`, and `sum-` in the source file.

9.3 Repository Status

At this snapshot, project Lean files outside `.lake/packages` contain no Lean `sorry`, no Lean `admit`, no project-local `axiom` declarations, and no project-local `constant` declarations. The former Besov-atom comparison target is proved as `atoms_between_souza_atoms_and_besov_atoms` in `GoodGrid/BesovAtoms.lean`. The newest oscillation and Haar comparison modules also check individually.

The aggregate root file `BesovSpacesGoodGrid.lean` currently has a known import/name organization issue: when checked directly, Lean reports that the environment already contains `GoodGridSpace.GoodGridCell.toLevelCell` from `GoodGrid/BesovSpace.lean` while importing `GoodGrid/BesovAtoms.lean`. This is recorded in `status.md` as the next repository-level cleanup item.

10 Main Theorems

The most important public results currently include:

- `BesovishSpace.normedSpace_and_lp_embedding`: structural summary for the coefficient-cost gauge and the L^t embedding estimate.
- `smoothnessScaleBesovishSpace_subset` and `smoothnessScaleBesovishSpaceInclusion_Norm`: inclusion and norm bound for smoothness-scaled Besov-ish spaces.
- `representation_limit` and `representation_limit_strong`: weak and strong representation-limit theorems.
- `representation_limit_weak_existence` and `representation_limit_strong_existence`: existence-packaged forms of the representation-limit statements.
- `closed_Norm_Costpq_ball_strongly_seqCompact`: sequential compactness of closed cost balls in the strong L^p topology.
- `besovishSpace_costNorm_completeSpace`: completeness of the Besov-ish space for `Norm_Costpq`.
- `ClaimI`, `ClaimII`, and `ClaimIII`, plus the `_top` endpoint versions: the weak-grid transmutation pipeline.
- `Transmutation_of_Atoms_continuous_embedding_explicit` and `LpGridRepresentation.cCo`: explicit Claim C embedding and the identity-level geometric constant.
- `atoms_between_souza_atoms_and_besov_atoms`: equality of the Souza, intermediate, and Besov-atom Besov-ish spaces with the paper's norm constants.
- `souzaBesovSpace_costNorm_completeSpace`, `souza_closedCostBallInLp_isCompact`, `souza_closedCostBallInL1_isCompact`, `souzaBesovSpace_dense`, and `souzaBesovSpace_dense_inL1`: good-grid/Souza consequences.
- `exists_standardRepresentationNorm_le_const_mul_haarL2RepresentationNorm`: the Haar representation norm controls the standard atomic representation norm.
- `finite_standardRepresentationNorm_implies_memBesov_and_standardRepresentation`: finite standard norm gives L^p , a canonical representation, finite cost, and Souza-Besov membership.
- `finite_haarL2RepresentationNorm_implies_memLp_and_hasSum`: finite Haar norm gives L^p membership and convergence of the normalized Haar expansion to f .
- `exists_meanOscillationNorm_le_const_mul_standardRepresentationNorm`: standard representation norm controls the mean-oscillation norm.
- `exists_haarL2RepresentationNorm_le_const_mul_meanOscillationNorm`: mean oscillation controls the Haar representation norm.

11 File Guide

- `BesovSpacesGoodGrid.lean`: main library entry point.
- `GoodGrid/Definition.lean`: good-grid structures.
- `WeakGrid/Definition.lean`: weak-grid structures and overlap estimates.
- `WeakGrid/Atoms.lean`: cells, local spaces, and atom families.
- `WeakGrid/BesovishSpaces.lean`: level blocks, representations, costs, Besov-ish spaces, and the cost gauge.
- `WeakGrid/Scales.lean`: scaled atom families and inclusions.
- `WeakGrid/Completeness.lean`: limit, compactness, and completeness theorems.
- `WeakGrid/InducedGrid.lean`: induced weak grids on a fixed cell and the contraction into the ambient Besov-ish space.
- `WeakGrid/Transmutation.lean`: transmutation objects and Claims I, II, III, including the explicit Claim C embedding constants.
- `GoodGrid/BesovSpace.lean`: Souza atoms and good-grid Besov spaces.
- `GoodGrid/BesovAtoms.lean`: Besov atoms on good grids and the Souza/Besov atom comparison theorem.
- `GoodGrid/AlternativeRepresentationsAndNorms.lean`: public aggregator for the Haar, standard, and mean-oscillation representation and norm-comparison files.
- `GoodGrid/AlternativeRepresentationsAndNorms/HaarRepresentationNorm.lean`: normalized Haar coefficients and the Haar representation gauge.
- `GoodGrid/AlternativeRepresentationsAndNorms/standardRepresentation.lean`: standard atomic coefficients and the standard representation gauge.
- `GoodGrid/AlternativeRepresentationsAndNorms/standardNormleqHaarRepresentenstionNorm.lean`: control of the standard representation norm by the Haar representation norm.
- `GoodGrid/AlternativeRepresentationsAndNorms/FiniteStandardNormimpliesBesov.lean`: finite standard norm endpoint and Souza-Besov membership.
- `GoodGrid/AlternativeRepresentationsAndNorms/FiniteHaarNormimpliesLp.lean`: finite Haar norm endpoint.
- `GoodGrid/AlternativeRepresentationsAndNorms/MeanOscillationNorm.lean`: mean-oscillation definitions and reusable local oscillation lemmas.
- `GoodGrid/AlternativeRepresentationsAndNorms/OscillationNormleqBesovNorm.lean`: control of mean oscillation by the standard representation norm.
- `GoodGrid/AlternativeRepresentationsAndNorms/HaarNormleqOscillationNorm.lean`: control of the Haar representation norm by mean oscillation.

- `GoodGrid/Distribution.lean`: test functions and distributions.
- `Sums.lean`: block-index and block-sum infrastructure.

12 Conclusion

The repository now contains a substantial weak-grid atomic-decomposition library: it defines Besov-ish spaces, develops their coefficient-cost norm, proves scale, compactness, completeness, and transmutation statements, and specializes the theory to Souza atoms on good grids. The good-grid layer now also contains the main finite-constant comparisons among the standard atomic norm, Haar representation norm, and mean-oscillation norm. The most reusable API is currently the weak-grid layer; the good-grid files show how the abstract machinery is intended to specialize to concrete Besov spaces.