

A: Datasheet

Algorithm: dahua_003

Developer: Dahua Technology Co Ltd

Submission Date: 2020_11_18

Template size: 2048 bytes

Template time (2.5 percentile): 722 msec

Template time (median): 723 msec

Template time (97.5 percentile): 730 msec

Investigation:

Frontal mugshot ranking 18 (out of 329) -- FNIR(1600000, 0, 1) = 0.0012 vs. lowest 0.0009 from sensetime_006

Mugshot webcam ranking 10 (out of 291) -- FNIR(1600000, 0, 1) = 0.0072 vs. lowest 0.0057 from sensetime_006

Mugshot profile ranking 44 (out of 260) -- FNIR(1600000, 0, 1) = 0.2060 vs. lowest 0.0550 from sensetime_006

Immigration visa-border ranking 18 (out of 218) -- FNIR(1600000, 0, 1) = 0.0020 vs. lowest 0.0009 from sensetime_006

Immigration visa-kiosk ranking 19 (out of 215) -- FNIR(1600000, 0, 1) = 0.0725 vs. lowest 0.0487 from cubox_000

Identification:

Frontal mugshot ranking 52 (out of 329) -- FNIR(1600000, T, L+1) = 0.0138, FPIR=0.001000 vs. lowest 0.0017 from nec_005


Mugshot webcam ranking 42 (out of 289) -- FNIR(1600000, T, L+1) = 0.0410, FPIR=0.001000 vs. lowest 0.0120 from nec_005

Mugshot profile ranking 25 (out of 259) -- FNIR(1600000, T, L+1) = 0.5790, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa-border ranking 32 (out of 217) -- FNIR(1600000, T, L+1) = 0.0125, FPIR=0.001000 vs. lowest 0.0032 from paravision_009

Immigration visa-kiosk ranking 23 (out of 212) -- FNIR(1600000, T, L+1) = 0.1356, FPIR=0.001000 vs. lowest 0.0728 from paravision_009


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec_005)




C: Evolution of accuracy for DAHUA algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_006)



L: Investigational mode: FNIR(1600000, R, 0) by probe type




M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.


Algorithm: dahua_003, Dataset: Border-Crossing Ageing N = 1600000
Text encodes FNIR, Color encodes log(FNIR)



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.


Algorithm: dahua_003, Dataset: Border-Crossing Ageing
Threshold: 8754.840000 set to achieve FPIR(30-45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

