Configure Automation Tests

Learn about test groups and how to exclude tests from your project



Test Groups

Test groups are sets of tests collected from a list of filters based on test names.

You can refer to them through the command line argument —ExecCmds="Automation RunTest" or through the **Test Automation** window filter. This is useful to collect tests that belong to different sections.

You can define a test group by editing the DefaultEngine.ini config file and adding the following line:.

```
1 +Groups=(Name="Group1", Filters=((Contains=".Some String.")))
2 +Groups=(Name="Group2", Filters=((Contains="Group2.", MatchFromStart=true),(Contains=".Group2.")))
```

Copy full snippet

Afterward, you can reference a test group with Group: <GroupName> in the ExecCmds argument and in Gauntlet.

Excluding Tests

During project development, you may need to exclude tests temporarily.

To exclude a test, edit the (DefaultEngine.ini) or the corresponding platform config file with the following line:

+ExcludeTest=(Test="<test or section name>",Reason="<a reason>",Warn=False)

Copy full snippet



You can exclude all tests that start with a string by inputting a partial name.

You can exclude by Rendering Hardware Interface (RHI) by adding the following line:

+ExcludeTest=(Test="<test or section name>",Reason="<a reason>", RHIs=("Vulkan", "DirectX 11"),Warn=False)

Copy full snippet

The RHI name must match the syntax from (Engine\Source\Runtime\AutomationTest\Public\AutomationTestExcludelist.h)

| You can also exclude tests in the Editor from the Test Automation window by selecting the Exclude button next to the test's selection checkbox. | |
|---|--|

Excluded tests will show as "Skipped" with the reason attached as an info event.